

SELECTION & SPECIFICATION DATA

Type	Asphalt Cutback Primer
Description	Blackhawk 5103 SP Asphalt is a concrete prime coat for bituminous mastic type protective coatings and adhesives. After curing, BH 5103 SP Asphalt's penetrative value improves the cohesion between weakly bonded particles and provides a firm surface to which heavier compounds can bond. BH SP Asphalt is an excellent black coating with good hiding power and is recommended for covering weathered vapor seals to rehabilitate and restore their appearance and as a general-purpose asphalt coating or primer.
Uses	<ul style="list-style-type: none"> • Prime coat for porous and rough surfaces • Asphalt base coating • Vapor and moisture barrier coating
Color	Black
Topcoats	Consult ErgonArmor
Finish	Matte
Dry Film Thickness	5 – 15 mils
Solids Content	By weight 50% +/- 5%
Theoretical Coverage Rate	160 sq ft per gallon at 10 wet mils
VOC Value(s)	Less than 450 g/L (3.76 lbs/gal)

SUBSTRATES & SURFACE PREPARATION

All	All surfaces must be clean and free from debris and loose scale material or anything that may interfere with adhesion or act as a bond breaker with the desired substrate.
Mixing	No mixing necessary
Thinning	Do not thin
Spray Application	Listed below are general equipment guidelines for the application of this product. Job site conditions may require modifications to these guidelines to achieve the desired results.
Airless Spray Single Leg	Pump Size 15:1 or greater Hose Length/Diameter - 200 ft x 1/2 in Whip Length/Diameter - 15 ft x 1/4 in
Brush	Apply with a wide fiber brush in order to create a smooth uniform film.
Roller	Use a low nap phenolic core roller.

CLEANUP & SAFETY

Cleanup	Mineral spirits or equivalent solvent.
Safety	Mixes and applications of this product present a number of hazards. Read and follow the hazard information, precautions and first aid directions on the individual product labels and safety data sheets before using.

PACKAGING, HANDLING & STORAGE

Ventilation	Thorough air circulation must be used during and after application until the product is cured. User should test and monitor exposure levels to ensure all personnel are within safe limits. Consult product SDS for further information.
Shelf Life	12 months at 75°F (24°C) when kept at recommended storage conditions and in original unopened containers.
Storage Temperature & Humidity	40° – 110°F (4° – 43°C) 0 – 100% relative humidity
Storage	Store indoors. This product is not affected by excursions below published storage temperatures. Always inspect the product prior to use to make sure it is smooth and homogeneous.
Sizing and Specifications	5 gallon (4.7 net fill) 55 gallon (53 net fill)

PERFORMANCE DATA

Specifications	Category	Results
ASTM D41	-	Pass

Rev 11/18

TERMS AND CONDITIONS OF SALE

While statements, technical information and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user. For all Terms and Conditions of Sale see ergonarmor.com.