# **SAFETY DATA SHEET**



# 1. Identification

Product identifier	TTS GROUT FILLER - FINE, COARSE (ALL COLORS)		
Other means of identification Synonyms	PERMACOLOR QUARTZ – FINE, MEDIUM (ALL COLORS)		
Recommended use	Not available.		
<b>Recommended restrictions</b>	None known.		
Manufacturer/Importer/Supp	lier/Distributor information		
Company Name Address	ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc. 2829 Lakeland Drive Jackson, MS 39232 USA		
After hours telephone number	1-800-222-7122		
Normal work hours telephone number Website	1-877-982-7667 www.ergonarmor.com		
E-mail	sds@ergon.com		
Emergency 24-hour telephone number Information on operation hours	CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887 8:00 a.m. to 5:00 p.m.		

# 2. Hazard(s) identification

Physical hazards	Not classified.
Health hazards	Not classified.
Environmental hazards	Not classified.
OSHA defined hazards	Not classified.
Label elements	
Hazard symbol	None.
Signal word	None.
Hazard statement	Not available.
Precautionary statement	
Prevention	Not applicable.
Response	Not applicable.
Storage	Not applicable.
Disposal	Not applicable.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

# 3. Composition/information on ingredients

## Mixtures

Chemical name	Common name and synonyms	CAS number	%
QUARTZ		14808-60-7	90 - 100
RESIN		Proprietary	1 - 10
TITANIUM DIOXIDE		13463-67-7	< 1
INORGANIC COLARANTS		Proprietary	< 0.10

# 4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing is difficult, give oxygen. Get medical attention.
Skin contact	Wash skin thoroughly with soap and water. Remove contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention.
Eye contact	Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Do not induce vomiting without advice from poison control center. Never give anything by mouth to a victim who is unconscious or is having convulsions. Get medical attention.
Most important symptoms/effects, acute and delayed	Exposed individuals may experience eye tearing, redness, and discomfort. Dusts may irritate the respiratory tract, skin and eyes. Coughing. May cause eye irritation. May cause skin irritation.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Keep victim under observation. Keep victim warm.

# 5. Fire-fighting measures

Suitable extinguishing media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	No unusual fire or explosion hazards noted.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	In the event of fire, cool tanks with water spray.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

# 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Avoid the generation of dusts during clean-up. Stop the flow of material, if this is without risk. Large Spills: Remove with vacuum trucks or pump to storage/salvage vessels. Sweep up or vacuum up spillage and collect in suitable container for disposal.
	Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal. Following product recovery, flush area with water. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read
	and understood. Minimize dust generation and accumulation. Keep away from heat, sparks and
	open flame. Provide appropriate exhaust ventilation at places where dust is formed. Do not
	breathe dust. Do not get in eyes, on skin, on clothing. Avoid prolonged exposure. Should be
	handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash
	hands thoroughly after handling. Avoid release to the environment. Wash contaminated
	clothing before reuse. Observe good industrial hygiene practices.

# 8. Exposure controls/personal protection

#### **Occupational exposure limits**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components QUARTZ (CAS 14808-60-7) TITANIUM DIOXIDE (CAS 13463-67-7) US. OSHA Table Z-3 Permiss Components QUARTZ (CAS 14808-60-7) TITANIUM DIOXIDE (CAS 13463-67-7) US. ACGIH Threshold Limit V Components QUARTZ (CAS 14808-60-7) TITANIUM DIOXIDE (CAS 13463-67-7) NIOSH. Immediately Dange Components QUARTZ (CAS 14808-60-7)	sible Exposure Limits (PEL) for Air Type PEL PEL sible Exposure Limits (PEL) for Mir Type TWA TWA TWA TWA TWA	<b>Value</b> 0.05 mg/m3 15 mg/m3	Form Respirable dust. Total dust.		
TITANIUM DIOXIDE (CAS 13463-67-7) US. OSHA Table Z-3 Permiss Components QUARTZ (CAS 14808-60-7) TITANIUM DIOXIDE (CAS 13463-67-7) US. ACGIH Threshold Limit V Components QUARTZ (CAS 14808-60-7) TITANIUM DIOXIDE (CAS 13463-67-7) NIOSH. Immediately Dange Components QUARTZ (CAS 14808-60-7)	PEL sible Exposure Limits (PEL) for Mir Type TWA TWA Values (TLV) Type TWA	15 mg/m3 heral Dusts (29 CFR 1910.1 Value 0.1 mg/m3 2.4 mppcf 5 mg/m3 15 mg/m3 50 mppcf 15 mppcf 15 mppcf Value 0.025 mg/m3	Total dust. <b>Dot</b> Form Respirable. Respirable fraction. Total dust. Total dust. Respirable fraction. <b>Form</b>		
13463-67-7) US. OSHA Table Z-3 Permiss Components QUARTZ (CAS 14808-60-7) TITANIUM DIOXIDE (CAS 13463-67-7) US. ACGIH Threshold Limit V Components QUARTZ (CAS 14808-60-7) TITANIUM DIOXIDE (CAS 13463-67-7) NIOSH. Immediately Dange Components QUARTZ (CAS 14808-60-7)	sible Exposure Limits (PEL) for Mir Type TWA TWA Values (TLV) Type TWA	heral Dusts (29 CFR 1910.1 Value 0.1 mg/m3 2.4 mppcf 5 mg/m3 15 mg/m3 50 mppcf 15 mppcf 15 mppcf <b>Value</b> 0.025 mg/m3	<b>Form</b> Respirable. Respirable. Respirable fraction. Total dust. Total dust. Respirable fraction.		
Components QUARTZ (CAS 14808-60-7) TITANIUM DIOXIDE (CAS 13463-67-7) US. ACGIH Threshold Limit V Components QUARTZ (CAS 14808-60-7) TITANIUM DIOXIDE (CAS 13463-67-7) NIOSH. Immediately Dange Components QUARTZ (CAS 14808-60-7)	Type TWA TWA Values (TLV) TWA	Value         0.1 mg/m3         2.4 mppcf         5 mg/m3         15 mg/m3         50 mppcf         15 mppcf         Value         0.025 mg/m3	Form Respirable. Respirable fraction. Total dust. Total dust. Respirable fraction.		
QUARTZ (CAS 14808-60-7) TITANIUM DIOXIDE (CAS 13463-67-7) US. ACGIH Threshold Limit V Components QUARTZ (CAS 14808-60-7) TITANIUM DIOXIDE (CAS 13463-67-7) NIOSH. Immediately Dange Components QUARTZ (CAS 14808-60-7)	TWA TWA <b>/alues (TLV)</b> TWA	0.1 mg/m3 2.4 mppcf 5 mg/m3 15 mg/m3 50 mppcf 15 mppcf <b>Value</b> 0.025 mg/m3	Respirable. Respirable. Respirable fraction. Total dust. Total dust. Respirable fraction.		
TITANIUM DIOXIDE (CAS 13463-67-7) US. ACGIH Threshold Limit V Components QUARTZ (CAS 14808-60-7) TITANIUM DIOXIDE (CAS 13463-67-7) NIOSH. Immediately Dange Components QUARTZ (CAS 14808-60-7)	TWA Values (TLV) TWA	2.4 mppcf 5 mg/m3 15 mg/m3 50 mppcf 15 mppcf <b>Value</b> 0.025 mg/m3	Respirable. Respirable fraction. Total dust. Total dust. Respirable fraction.		
13463-67-7) US. ACGIH Threshold Limit V Components QUARTZ (CAS 14808-60-7) TITANIUM DIOXIDE (CAS 13463-67-7) NIOSH. Immediately Dange Components QUARTZ (CAS 14808-60-7)	<b>Values (TLV) Type</b> TWA	5 mg/m3 15 mg/m3 50 mppcf 15 mppcf <b>Value</b> 0.025 mg/m3	Respirable fraction. Total dust. Total dust. Respirable fraction. <b>Form</b>		
13463-67-7) US. ACGIH Threshold Limit V Components QUARTZ (CAS 14808-60-7) TITANIUM DIOXIDE (CAS 13463-67-7) NIOSH. Immediately Dange Components QUARTZ (CAS 14808-60-7)	<b>Values (TLV) Type</b> TWA	15 mg/m3 50 mppcf 15 mppcf <b>Value</b> 0.025 mg/m3	Total dust. Total dust. Respirable fraction. <b>Form</b>		
Components QUARTZ (CAS 14808-60-7) TITANIUM DIOXIDE (CAS 13463-67-7) NIOSH. Immediately Dange Components QUARTZ (CAS 14808-60-7)	<b>Type</b> TWA	50 mppcf 15 mppcf <b>Value</b> 0.025 mg/m3	Total dust. Respirable fraction. <b>Form</b>		
Components QUARTZ (CAS 14808-60-7) TITANIUM DIOXIDE (CAS 13463-67-7) NIOSH. Immediately Dange Components QUARTZ (CAS 14808-60-7)	<b>Type</b> TWA	15 mppcf <b>Value</b> 0.025 mg/m3	Respirable fraction.		
Components QUARTZ (CAS 14808-60-7) TITANIUM DIOXIDE (CAS 13463-67-7) NIOSH. Immediately Dange Components QUARTZ (CAS 14808-60-7)	<b>Type</b> TWA	<b>Value</b> 0.025 mg/m3	Form		
Components QUARTZ (CAS 14808-60-7) TITANIUM DIOXIDE (CAS 13463-67-7) NIOSH. Immediately Dange Components QUARTZ (CAS 14808-60-7)	<b>Type</b> TWA	0.025 mg/m3			
QUARTZ (CAS 14808-60-7) TITANIUM DIOXIDE (CAS 13463-67-7) NIOSH. Immediately Dange Components QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3			
TITANIUM DIOXIDE (CAS 13463-67-7) NIOSH. Immediately Dange Components QUARTZ (CAS 14808-60-7)		-	Respirable fraction.		
13463-67-7) NIOSH. Immediately Dange Components QUARTZ (CAS 14808-60-7)	TWA	2.5 ma/m3	Deenivelale for secole		
Components QUARTZ (CAS 14808-60-7)			Respirable finescale particles		
Components QUARTZ (CAS 14808-60-7)		0.2 mg/m3	Respirable nanoscale particles		
,	rous to Life or Health (IDLH) Value Type	es, as amended Value			
	IDLH	50 mg/m3			
TITANIUM DIOXIDE (CAS 13463-67-7)	IDLH	5000 mg/m3			
US. NIOSH: Pocket Guide to Components	Chemical Hazards Recommended Type	Exposure Limits (REL) Value	Form		
QUARTZ (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.		
	No biological exposure limits noted for the ingredient(s).				
posure guidelines	Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.				
propriate engineering ntrols	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. If engineering measures are not sufficient to maintain concentrations of dust particulates below the Occupational Exposure Limit (OEL), suitable respiratory protection must be worn. If material is ground, cut, or used in any operation which may generate dusts, use appropriate local exhaust ventilation to keep exposures below the recommended exposure limits.				
	, such as personal protective equi Goggles/face shield are recommended				
Skin protection Hand protection	PVC or rubber gloves are recommend	led. Leather gloves.			
-	Chemical/oil resistant clothing is recon	-			
Respiratory protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.				

**Thermal hazards** 

Wear appropriate thermal protective clothing, when necessary.

General hygiene<br/>considerationsObserve any medical surveillance requirements. Always observe good personal hygiene<br/>measures, such as washing after handling the material and before eating, drinking, and/or<br/>smoking. Routinely wash work clothing and protective equipment to remove contaminants.<br/>Always observe good personal hygiene measures, such as washing after handling the material<br/>and before eating, drinking, and/or smoking. Routinely wash work clothing. Routinely wash work clothing and protective<br/>equipment to remove contaminants.

## 9. Physical and chemical properties

5. Thysical and chemical	properties
Appearance	Powder.
Physical state	Solid.
Form	Powder.
Color	Not available.
Odor	Odorless.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	Not available.
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or ex	plosive limits
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Insoluble
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Percent volatile	<1 %
Specific gravity	2.65

# 10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials. None under normal conditions.
Incompatible materials	This product reacts with hydrofluoric acid.
Hazardous decomposition products	No hazardous decomposition products are known.

# **11.** Toxicological information

#### Information on likely routes of exposure

Inhalation	Dust may irritate respiratory system. Prolonged inhalation may be harmful.
Skin contact	Dust or powder may irritate the skin. Prolonged skin contact may cause temporary irritation.
Eye contact	Dust may irritate the eyes. Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	Dusts may irritate the respiratory tract, skin and eyes. Irritating to eyes, respiratory system and skin. Coughing.

#### Information on toxicological effects

Information on toxicological e	effects			
Acute toxicity	Not known.			
Components	Species	Test Results		
TITANIUM DIOXIDE (CAS 13463-	67-7)			
Acute				
Dermal			10000	
LD50	Hamster		>= 10000 mg/kg	
<b>Oral</b> LD50	Dat		> 10000 mg/kg	
ED30	Rat		> 10000 mg/kg	
* Estimates for product may	be based on additional compor	nent data not shown.		
Skin corrosion/irritation	Causes mild skin irritation.			
Serious eye damage/eye irritation	Prolonged exposure may cause irritation to eyes.			
Respiratory or skin sensitization				
Respiratory sensitization	Not a respiratory sensitizer.			
Skin sensitization	Prolonged skin contact may cause temporary irritation.			
Germ cell mutagenicity	No data available to indicate mutagenic or genotoxic.	product or any compo	nents present at greater than 0.1% are	
Carcinogenicity	This product contains crystalline encapsulated form the norma		own carcinogen; however in this re unavailable.	
IARC Monographs. Overall Evaluation of Carcinogenicity				
QUARTZ (CAS 14808-60-7)1 Carcinogenic to humans.				
TITANIUM DIOXIDE (CAS 13463-67-7) 2B Possibly carcinogenic to humans. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)				
QUARTZ (CAS 14808-60	•	Cancer		
	rogram (NTP) Report on Care			
QUARTZ (CAS 14808-60-	-7)	Known To Be Humar	n Carcinogen.	
Reproductive toxicity	Not classified.			
Specific target organ toxicity - single exposure	Not classified.			
Specific target organ toxicity - repeated exposure	Not classified.			
Aspiration hazard	Not an aspiration hazard.			
Chronic effects	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.			
Further information	This product has no known adverse effect on human health.			

# **12. Ecological information**

Ecotoxicity

Not expected to be harmful to aquatic organisms.

Product		Species	Test Results
TTS GROUT FILLER -	FINE, COARSE (AL	L COLORS)	
Aquatic			
Acute			
Crustacea	EC50	Daphnia	101010.1016 mg/l, 48 hours estimated
Fish	LC50	Fish	101010.1016 mg/l, 96 hours estimated

\* Estimates for product may be based on additional component data not shown.

Persistence and degradability	No data is available on the degradability of any ingredients in the mixture.
<b>Bioaccumulative potential</b>	No data available.
Mobility in soil	No data available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

# **14. Transport information**

#### DOT

Not regulated as dangerous goods.

#### IATA

Not regulated as dangerous goods.

#### IMDG

Not regulated as dangerous goods.

#### Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

## 15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

#### Toxic Substances Control Act (TSCA)

One or more components of the mixture are not on the TSCA 8(b) inventory or are designated "inactive".

## TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

## CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

## SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

QUARTZ (CAS 14808-60-7)

Cancer lung effects immune system effects kidney effects

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

## SARA 302 Extremely hazardous substance

Not listed.

No

SARA 313 (TRI reporting) Not regulated.

#### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

# Safe Drinking Water Act Not regulated. (SDWA)

## US state regulations

#### **California Proposition 65**



**WARNING:** This product can expose you to chemicals including QUARTZ, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

#### California Proposition 65 - CRT: Listed date/Carcinogenic substance

QUARTZ (CAS 14808-60-7)	Listed: October 1, 1988
TITANIUM DIOXIDE (CAS 13463-67-7)	Listed: September 2, 2011

#### **International Inventories**

Country(s) or region	Inventory name On inventory (ye	es/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)		

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

Issue date	12-31-2024
Version #	01
Further information	HMIS® is a registered trade and service mark of the NPCA.
References	ACGIH ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices EPA: AQUIRE database HSDB® - Hazardous Substances Data Bank IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens NLM: Hazardous Substances Data Base US. IARC Monographs on Occupational Exposures to Chemical Agents

Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Ergon Armor cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.
<b>Revision information</b>	Product and Company Identification: Synonyms Regulatory information: US federal regulations