

1. Identification**Product identifier** PENNCHEM™ POWDER**Other means of identification** None.**Recommended use** Not available.**Recommended restrictions** None known.**Manufacturer/Importer/Supplier/Distributor information****Company Name** ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.**Address** 2829 Lakeland Drive

Jackson, MS 39232

USA

After hours telephone number 1-800-222-7122**Normal work hours telephone number** 1-877-982-7667**Website** www.ergonarmor.com**E-mail** sds@ergon.com**Emergency 24-hour telephone number** CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887**Information on operation hours** 8:00 a.m. to 5:00 p.m.**2. Hazard(s) identification****Physical hazards** Not classified.**Health hazards**
Sensitization, skin Category 1
Carcinogenicity Category 1
Specific target organ toxicity, repeated exposure Category 1 (lungs)**Environmental hazards** Not classified.**OSHA defined hazards** Not classified.**Label elements****Signal word** Danger**Hazard statement** May cause cancer. May cause an allergic skin reaction. Causes damage to organs through prolonged or repeated exposure.**Precautionary statement****Prevention**

Avoid breathing dust/fume/gas/mist/vapors/spray. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Response

IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse. IF exposed or concerned: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment see Section 4 of this SDS. Get medical advice/attention if you feel unwell.

Storage

Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
QUARTZ		14808-60-7	< 100
BENZOYL PEROXIDE		94-36-0	< 1

4. First-aid measures

Inhalation Move to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. If breathing is difficult, give oxygen. Get medical attention.

Skin contact In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention if symptoms occur. Wash contaminated clothing before reuse. Destroy or thoroughly clean contaminated shoes.

Eye contact In case of contact, immediately flush eyes with large amounts of water, continuing to flush for 15 minutes. Get medical attention.

Ingestion Do not induce vomiting without advice from poison control center. Never give anything by mouth to a victim who is unconscious or is having convulsions. Get medical attention.

Most important symptoms/effects, acute and delayed May cause an allergic skin reaction. Dusts may irritate the respiratory tract, skin and eyes. Coughing.

Indication of immediate medical attention and special treatment needed In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information IF exposed or concerned: Get medical advice/attention. Keep victim warm. Keep victim under observation. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting equipment/instructions In the event of fire, cool tanks with water spray.

Specific methods Cool containers exposed to flames with water until well after the fire is out.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Do not touch or walk through spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. For personal protection, see section 8 of the SDS. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up Avoid dust formation.

Large Spills: Dike far ahead of spill for later disposal. Remove with vacuum trucks or pump to storage/salvage vessels.

Small Spills: Sweep up or gather material and place in appropriate container for disposal. Following product recovery, flush area with water.

Never return spills in original containers for re-use.

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling Eliminate all sources of ignition. Use only with adequate ventilation. Do not breathe dust. Do not get in eyes, on skin, on clothing. Wear personal protective equipment. Prevent dust accumulation to minimize explosion hazard. Use non-sparking tools and explosion-proof equipment. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. Shower after work. Wash contaminated clothing before reuse. Take precautionary measures against static discharges. Avoid release to the environment.

Conditions for safe storage, including any incompatibilities Keep container tightly closed. Keep out of reach of children. Store in a cool, dry place. Use care in handling/storage.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
BENZOYL PEROXIDE (CAS 94-36-0)	PEL	5 mg/m ³	
QUARTZ (CAS 14808-60-7)	PEL	0.05 mg/m ³	Respirable dust.

US. OSHA Table Z-3 Permissible Exposure Limits (PEL) for Mineral Dusts (29 CFR 1910.1000)

Components	Type	Value	Form
QUARTZ (CAS 14808-60-7)	TWA	0.1 mg/m ³	Respirable.
		2.4 mppcf	Respirable.

US. ACGIH Threshold Limit Values (TLV)

Components	Type	Value	Form
BENZOYL PEROXIDE (CAS 94-36-0)	TWA	5 mg/m ³	
QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m ³	Respirable fraction.

NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended

Components	Type	Value
QUARTZ (CAS 14808-60-7)	IDLH	50 mg/m ³

US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL)

Components	Type	Value	Form
BENZOYL PEROXIDE (CAS 94-36-0)	TWA	5 mg/m ³	
QUARTZ (CAS 14808-60-7)	TWA	0.05 mg/m ³	Respirable dust.

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelines Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.

Appropriate engineering controls Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Ensure adequate ventilation, especially in confined areas.

Individual protection measures, such as personal protective equipment

Eye/face protection Goggles/face shield are recommended.

Skin protection

Hand protection Wear protective gloves.

Other Wear appropriate clothing to prevent any possibility of skin contact with solutions containing 10% or more of this chemical.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	Powder.
Physical state	Liquid.
Form	Powder.
Color	Red. Black. Grey. Natural color.
Odor	Odorless.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	Not available.
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Insoluble
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	None under normal conditions.
Incompatible materials	Strong oxidizing agents. Strong bases.
Hazardous decomposition products	Oxides of silicon.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause cancer by inhalation. Inhalation of dusts may cause respiratory irritation.
Skin contact	May cause an allergic skin reaction.
Eye contact	May be irritating to eyes.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Coughing. May cause an allergic skin reaction. Lungs. Dusts may irritate the respiratory tract, skin and eyes.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
BENZOYL PEROXIDE (CAS 94-36-0)		
Acute		
Oral		
LD50	Rat	7710 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Not available.
Serious eye damage/eye irritation	May be irritating to eyes.
Respiratory or skin sensitization	
Respiratory sensitization	Not available.
Skin sensitization	May cause allergic skin disorders in sensitive individuals.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Hazardous by OSHA criteria. Hazardous by WHMIS criteria. In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled. In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer. Risk of cancer cannot be excluded with prolonged exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity

BENZOYL PEROXIDE (CAS 94-36-0)	3 Not classifiable as to carcinogenicity to humans.
QUARTZ (CAS 14808-60-7)	1 Carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

QUARTZ (CAS 14808-60-7)	Cancer
-------------------------	--------

US. National Toxicology Program (NTP) Report on Carcinogens

QUARTZ (CAS 14808-60-7)	Known To Be Human Carcinogen.
-------------------------	-------------------------------

Reproductive toxicity	Not classified.
Specific target organ toxicity - single exposure	Not available.
Specific target organ toxicity - repeated exposure	Causes damage to organs through prolonged or repeated exposure. Lungs.
Aspiration hazard	Not available.
Chronic effects	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.
Further information	This product has no known adverse effect on human health.

12. Ecological information

Ecotoxicity	Not expected to be harmful to aquatic organisms.
--------------------	--

Product	Species	Test Results
PENNCHEM™ POWDER		
Aquatic		
<i>Acute</i>		
Crustacea	EC50 Daphnia	111111.1094 mg/l, 48 hours estimated

Product	Species	Test Results
Fish	LC50	111111.1094 mg/l, 96 hours estimated

* Estimates for product may be based on additional component data not shown.

Persistence and degradability Not available.

Bioaccumulative potential Not available.

Partition coefficient n-octanol / water (log Kow)
 BENZOYL PEROXIDE 3.46

Mobility in soil Not available.

Other adverse effects Not available.

13. Disposal considerations

Disposal instructions Dispose of contents/container in accordance with local/regional/national/international regulations. Do not discharge into drains, water courses or onto the ground.

Waste from residues / unused products Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Avoid discharge into water courses or onto the ground.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT
 Not regulated as dangerous goods.

IATA
 Not regulated as dangerous goods.

IMDG
 Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not available.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
 All components are on the U.S. EPA TSCA Inventory List.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
 Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)
 Not listed.

SARA 304 Emergency release notification
 Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)
 QUARTZ (CAS 14808-60-7) Cancer
 lung effects
 immune system effects
 kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance
 Not listed.

SARA 311/312 Hazardous chemical Yes

Classified hazard categories Respiratory or skin sensitization
 Carcinogenicity
 Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.**US state regulations**

WARNING: This product contains a chemical known to the State of California to cause cancer.

California Proposition 65**California Proposition 65 - CRT: Listed date/Carcinogenic substance**

QUARTZ (CAS 14808-60-7)

Listed: October 1, 1988

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision**Issue date** 02-27-2025**Version #** 01**Further information** HMIS® is a registered trade and service mark of the NPCA.

References

ACGIH
 EPA: AQUIRE database
 NLM: Hazardous Substances Data Base
 US. IARC Monographs on Occupational Exposures to Chemical Agents
 HSDB® - Hazardous Substances Data Bank
 IARC Monographs. Overall Evaluation of Carcinogenicity
 National Toxicology Program (NTP) Report on Carcinogens
 ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision information This document has undergone significant changes and should be reviewed in its entirety.