

**1. Identification****Product identifier** BLACKHAWK™ 5600 SEAL KOTE HEAVY**Other means of identification** None.**Recommended use** Not available.**Recommended restrictions** None known.**Manufacturer/Importer/Supplier/Distributor information****Company Name** ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.**Address** 2829 Lakeland Drive

Jackson, MS 39232

USA

**After hours telephone number** 1-800-222-7122**Normal work hours telephone number** 1-877-982-7667**Website** www.ergonarmor.com**E-mail** sds@ergon.com**Emergency 24-hour telephone number** CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887**Information on operation hours** 8:00 a.m. to 5:00 p.m.**2. Hazard(s) identification**

<b>Physical hazards</b>	Flammable liquids	Category 3
<b>Health hazards</b>	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2
	Germ cell mutagenicity	Category 1
	Carcinogenicity	Category 1
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2
<b>Environmental hazards</b>	Not classified.	
<b>OSHA defined hazards</b>	Not classified.	

**Label elements****Signal word** Danger**Hazard statement** Flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer. May cause damage to organs through prolonged or repeated exposure.**Precautionary statement  
Prevention**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Wash thoroughly after handling. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/protective clothing/eye protection/face protection. Use explosion-proof electrical/ventilating/lighting equipment. Use only outdoors or in a well-ventilated area.

<b>Response</b>	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Take off contaminated clothing and wash before reuse. Call a POISON CENTER or doctor/physician if you feel unwell. Specific treatment see Section 4 of this SDS. IF exposed or concerned: Get medical advice/attention. In case of fire: Use appropriate media for extinction.
<b>Storage</b>	Store locked up. Keep container tightly closed. Store in a well-ventilated place. Keep cool.
<b>Disposal</b>	Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Hazard(s) not otherwise classified (HNOC)</b>	None known.
<b>Supplemental information</b>	None.

### 3. Composition/information on ingredients

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
ASPHALT		8052-42-4	50 - 60
MINERAL SPIRITS		8052-41-3/64742-48-9	10 - 30
SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.		64742-95-6	1 - 5
QUARTZ		14808-60-7	< 1

### 4. First-aid measures

<b>Inhalation</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. For breathing difficulties, oxygen may be necessary. Call a poison center or doctor/physician if you feel unwell.
<b>Skin contact</b>	For hot product, immediately immerse in or flush the affected area with large amounts of cold water to dissipate heat. Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. For minor skin contact, avoid spreading material on unaffected skin. Wash contaminated clothing before reuse.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Rinse mouth thoroughly. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical attention if symptoms occur.
<b>Most important symptoms/effects, acute and delayed</b>	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Direct contact with eyes may cause temporary irritation. Skin irritation. May cause redness and pain.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	Take off all contaminated clothing immediately. In case of shortness of breath, give oxygen. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Keep victim under observation. Keep victim warm. Wash contaminated clothing before reuse.

### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire. Do not use water jet.
<b>Specific hazards arising from the chemical</b>	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.

**Fire fighting equipment/instructions**

In case of fire and/or explosion do not breathe fumes. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Move containers from fire area if you can do so without risk. Do not get water inside container. Some of these materials, if spilled, may evaporate leaving a flammable residue.

**Specific methods**

In the event of fire and/or explosion do not breathe fumes.

**General fire hazards**

Flammable liquid and vapor.

**6. Accidental release measures****Personal precautions, protective equipment and emergency procedures**

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

**Methods and materials for containment and cleaning up**

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Never return spills in original containers for re-use.

**Environmental precautions**

Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

**7. Handling and storage****Precautions for safe handling**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Do not use in areas without adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Do not empty into drains. Observe good industrial hygiene practices. Hydrogen sulfide, a very highly toxic gas, may be present with this material. Keep face clear of tank and/or tank car openings. Avoid release to the environment.

**Conditions for safe storage, including any incompatibilities**

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep container dry. Keep away from food, drink and animal feedingstuffs. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS). Keep container closed. Keep out of reach of children.

**8. Exposure controls/personal protection****Occupational exposure limits**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

**US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value	Form
QUARTZ (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.

**US. OSHA Table Z-3 Permissible Exposure Limits (PEL) for Mineral Dusts (29 CFR 1910.1000)**

Components	Type	Value	Form
QUARTZ (CAS 14808-60-7)	TWA	0.1 mg/m <sup>3</sup>	Respirable.
		2.4 mppcf	Respirable.

**US. ACGIH Threshold Limit Values (TLV)**

Components	Type	Value	Form
ASPHALT (CAS 8052-42-4)	TWA	0.5 mg/m <sup>3</sup>	Inhalable fume.
QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m <sup>3</sup>	Respirable fraction.

**NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended**

Components	Type	Value
QUARTZ (CAS 14808-60-7)	IDLH	50 mg/m <sup>3</sup>

**US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL)**

Components	Type	Value	Form
ASPHALT (CAS 8052-42-4)	Ceiling	5 mg/m <sup>3</sup>	Fume.
QUARTZ (CAS 14808-60-7)	TWA	0.05 mg/m <sup>3</sup>	Respirable dust.

**Biological limit values****ACGIH Biological Exposure Indices (BEI)**

Components	Value	Determinant	Specimen	Sampling Time
ASPHALT (CAS 8052-42-4)	2.5 µg/l	1-Hydroxypyrene, with hydrolysis (1-HP)	Urine	*

\* - For sampling details, please see the source document.

**Appropriate engineering controls** Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Wear safety glasses; chemical goggles (if splashing is possible).

**Skin protection**

**Hand protection** Wear appropriate chemical resistant gloves. Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves.

**Other** Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. It is a good industrial hygiene practice to minimize skin contact. Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapor contact.

**Respiratory protection** When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations** Observe any medical surveillance requirements. When using, do not eat, drink or smoke. Avoid contact with eyes. Avoid contact with skin. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical and chemical properties**

<b>Appearance</b>	Viscous liquid
<b>Physical state</b>	Solid.
<b>Form</b>	Liquid.
<b>Color</b>	Brown to Black
<b>Odor</b>	Mild Petroleum Odor
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	Not available.
<b>Initial boiling point and boiling range</b>	Not available.

<b>Flash point</b>	≥ 100.0 - ≤ 140.0 °F (≥ 37.8 - ≤ 60.0 °C) Cleveland Open Cup
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	Not available.
<b>Vapor density</b>	Not available.
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Not available.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	Not available
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Explosive properties</b>	Not explosive.
<b>Oxidizing properties</b>	Not oxidizing.
<b>VOC</b>	≤350 g/l

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Stable at normal conditions.
<b>Possibility of hazardous reactions</b>	Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong oxidizing agents.
<b>Hazardous decomposition products</b>	Irritants. Carbon oxides. Sulphur oxides.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	May cause drowsiness or dizziness. Headache. Nausea, vomiting.
<b>Skin contact</b>	Causes skin irritation. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Ingestion</b>	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.

**Symptoms related to the physical, chemical and toxicological characteristics** May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

### Information on toxicological effects

**Acute toxicity** Not known. Not classified.

<b>Components</b>	<b>Species</b>	<b>Test Results</b>
ASPHALT (CAS 8052-42-4)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg

Components	Species	Test Results
<b>Oral</b> LD50	Rat	> 5000 mg/kg

\* Estimates for product may be based on additional component data not shown.

<b>Skin corrosion/irritation</b>	Causes skin irritation.
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.
<b>Respiratory or skin sensitization</b>	
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.
<b>Skin sensitization</b>	Not a skin sensitizer.
<b>Germ cell mutagenicity</b>	May cause genetic defects.
<b>Carcinogenicity</b>	May cause cancer.

#### IARC Monographs. Overall Evaluation of Carcinogenicity

ASPHALT (CAS 8052-42-4)	2B Possibly carcinogenic to humans.
MINERAL SPIRITS (CAS 8052-41-3/64742-48-9)	3 Not classifiable as to carcinogenicity to humans.
QUARTZ (CAS 14808-60-7)	1 Carcinogenic to humans.
SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM. (CAS 64742-95-6)	3 Not classifiable as to carcinogenicity to humans.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

QUARTZ (CAS 14808-60-7)	Cancer
-------------------------	--------

#### US. National Toxicology Program (NTP) Report on Carcinogens

ASPHALT (CAS 8052-42-4)	Known To Be Human Carcinogen.
QUARTZ (CAS 14808-60-7)	Known To Be Human Carcinogen.

<b>Reproductive toxicity</b>	Not classified.
<b>Specific target organ toxicity - single exposure</b>	May cause drowsiness or dizziness.
<b>Specific target organ toxicity - repeated exposure</b>	May cause damage to organs through prolonged or repeated exposure.
<b>Aspiration hazard</b>	Not classified.
<b>Chronic effects</b>	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

## 12. Ecological information

**Ecotoxicity** Toxic to aquatic life with long lasting effects.

Product	Species	Test Results	
BLACKHAWK™ 5600 SEAL KOTE HEAVY			
<b>Aquatic</b>			
Crustacea	EC50	Daphnia	13999.3193 mg/l, 48 hours
Fish	LC50	Fish	58070.668 mg/l, 96 hours
<b>Acute</b>			
Crustacea	EC50	Daphnia	9784.3223 mg/l, 48 hours estimated
Fish	LC50	Fish	637.0981 mg/l, 96 hours estimated

\* Estimates for product may be based on additional component data not shown.

<b>Persistence and degradability</b>	No data is available on the degradability of any ingredients in the mixture.
<b>Bioaccumulative potential</b>	No data available.
<b>Mobility in soil</b>	No data available.
<b>Other adverse effects</b>	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

<b>Disposal instructions</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations. Do not allow this material to drain into sewers/water supplies.
------------------------------	---

<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Hazardous waste code</b>	D001: Waste Flammable material with a flash point <140 F The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. Transport information

### DOT

<b>UN number</b>	UN1999
<b>UN proper shipping name</b>	Tars, liquid including road oils and cut back bitumens
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary hazard</b>	-
<b>Label(s)</b>	3
<b>Packing group</b>	III
<b>Environmental hazards</b>	
<b>Marine pollutant</b>	No.
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling. If shipped by ground in individual containers that are less than 119 gallons (450 L): Not regulated as a hazardous material. (49 CFR 173.121)
<b>Special provisions</b>	B1, B13, IB3, T1, TP3
<b>Packaging exceptions</b>	150
<b>Packaging non bulk</b>	203
<b>Packaging bulk</b>	242

### IATA

<b>UN number</b>	UN1999
<b>UN proper shipping name</b>	Tars, liquid including road asphalt and oils, bitumen and cut backs
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary hazard</b>	-
<b>Packing group</b>	III
<b>Environmental hazards</b>	No.
<b>ERG Code</b>	3L
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Other information</b>	
<b>Passenger and cargo aircraft</b>	Allowed with restrictions.
<b>Cargo aircraft only</b>	Allowed with restrictions.

### IMDG

<b>UN number</b>	UN1999
<b>UN proper shipping name</b>	TARS, LIQUID including road oils, and cutback bitumens
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary hazard</b>	-
<b>Packing group</b>	III
<b>Environmental hazards</b>	
<b>Marine pollutant</b>	No.
<b>EmS</b>	F-E, S-E
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not established.

DOT



IATA; IMDG



#### General information

If shipped by ground in individual containers that are less than 119 gallons (450 L): Not regulated as a hazardous material (49 CFR 173.121). If shipped by vessel in individual containers that are less than 119 gallons (450 L) each, then IMDG 2.3.2.5 exception applies. Not subject to the provisions for marking, labelling, and testing of packages. "Transport in accordance with 2.3.2.5 of the IMDG code."

## 15. Regulatory information

### US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.  
CERCLA/SARA Hazardous Substances - Not applicable.

#### Toxic Substances Control Act (TSCA)

All components of the mixture on the TSCA 8(b) inventory are designated "active".

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

#### SARA 304 Emergency release notification

Not regulated.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

QUARTZ (CAS 14808-60-7)

Cancer  
lung effects  
immune system effects  
kidney effects

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### SARA 302 Extremely hazardous substance

Not listed.

#### SARA 311/312

Yes

#### Hazardous chemical

#### Classified hazard categories

Flammable (gases, aerosols, liquids, or solids)  
Skin corrosion or irritation  
Serious eye damage or eye irritation  
Germ cell mutagenicity  
Carcinogenicity  
Specific target organ toxicity (single or repeated exposure)

#### SARA 313 (TRI reporting)

Not regulated.

### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

ASPHALT (CAS 8052-42-4)



**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**Safe Drinking Water Act (SDWA)** Not regulated.**US state regulations****California Proposition 65****WARNING:** WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).**California Proposition 65 - CRT: Listed date/Carcinogenic substance**

QUARTZ (CAS 14808-60-7)

Listed: October 1, 1988

**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

**16. Other information, including date of preparation or last revision**

<b>Issue date</b>	11-30-2020
<b>Revision date</b>	03-07-2025
<b>Version #</b>	04
<b>NFPA ratings</b>	Health: 2 Flammability: 2 Instability: 0

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Ergon Armor cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

**Revision information**

This document has undergone significant changes and should be reviewed in its entirety.