SAFETY DATA SHEET



1. Identification

Product identifier FURALAC™ FN RESIN

Other means of identification None.

Recommended useNot available. **Recommended restrictions**None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.

Address 2829 Lakeland Drive

Jackson, MS 39232

USA

After hours telephone

1-800-222-7122

number

Website

1-877-982-7667

Normal work hours telephone number

1-0//-302-/00/

E-mail

sds@ergon.com

www.ergonarmor.com

Emergency 24-hour

CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

telephone number Information on operation hours

8:00 a.m. to 5:00 p.m.

2. Hazard(s) identification

Hazards for the product as sold

Physical hazardsFlammable liquidsCategory 4Health hazardsAcute toxicity, oralCategory 3

Acute toxicity, inhalation

Category 3

Skin corrosion/irritation

Category 2

Serious eye damage/eye irritation

Category 2

Carcinogenicity

Category 2

Category 2

Specific target organ toxicity, single

exposure

Specific target organ toxicity, repeated Category 2

exposure

Environmental hazards Not classified. **OSHA defined hazards** Not classified.

Label elements



Signal word Danger

Hazard statement Combustible liquid. Toxic if swallowed. Toxic if inhaled. Causes serious eye irritation. Causes skin

irritation. Suspected of causing cancer. May cause respiratory irritation. May cause damage to

Category 3 respiratory tract irritation

organs through prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been

read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Keep away from flames and hot surfaces-No smoking. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not eat, drink or

smoke when using this product. Wash thoroughly after handling.

5821 Version #: 03 Revision date: 08-20-2025 Issue date: 05-17-2022

Response IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF SWALLOWED:

Immediately call a POISON CENTER or doctor/physician. Rinse mouth. Specific treatment (see this label). IF ON SKIN: Gently wash with plenty of soap and water. Take off contaminated clothing and wash before reuse. If skin irritation occurs: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. In case of fire: Use appropriate media to extinguish. IF exposed or concerned: Get medical

advice/attention.

Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Storage

Disposal Dispose of contents/container in accordance with local/regional/national/international

regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS No./Unique ID	%
2-FURANCARBOXALDEHYDE		98-01-1	10 - 30
FURFURYL ALCOHOL		98-00-0	1 - 10
Other components below report	able levels		77

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. If breathing is difficult, trained personnel should give oxygen. Do not use mouth-to-mouth method if victim inhaled the substance. If unconscious, place in recovery position and get medical attention immediately. Maintain open airway. If it is suspected that gas or vapor is still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. Loosen tight clothing such as a collar, tie, belt, or waistband. Get medical attention immediately.

Skin contact

Immediately flush skin with plenty of water. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Remove contact lenses, if present and easy to do. Continue to rinse for at least 20 minutes.

Get medical attention.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Rinse mouth thoroughly. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Never give anything by mouth to a victim who is unconscious or is having convulsions. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt, or waistband.

Most important symptoms/effects, acute and delayed

Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Coughing. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects. Toxic if inhaled. Toxic if swallowed.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Keep victim under observation. Symptoms may be delayed.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

5821 Version #: 03 Revision date: 08-20-2025 Issue date: 05-17-2022

Specific hazards arising from the chemical

Combustible liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor or gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas. Vapors may travel considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard. Acid contamination can cause violent, exothermic polymerization.

Decomposition products may include the following materials: Carbon dioxide and carbon monoxide.

Special protective equipment and precautions for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. In the event of fire, cool tanks with water spray.

Specific methods
General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials.

Combustible liquid.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep out of low areas. Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Small Spills: Stop leak if you can do it without risk. Move containers from spill area. Dilute with water and mop up if water-soluble.

Large Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Stop the flow of material, if this is without risk. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent product from entering drains. Dike far ahead of spill for later disposal. Following product recovery, flush area with water.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not taste or swallow. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat and sources of ignition. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store in a segregated and approved area. Store away from incompatible materials (see Section 10 of the SDS). Do not store in unlabeled containers.

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000) Components Type Value

2-FURANCARBOXALDEHYD E (CAS 98-01-1) PEL 20 mg/m3

 Material name: FURALAC™ FN RESIN
 SDS US

 5821 Version #: 03 Revision date: 08-20-2025 Issue date: 05-17-2022
 3 / 10

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000) Components Value

FURFURYL ALCOHOL (CAS PEL 200 mg/m3 98-00-0)

50 ppm

US. ACGIH Threshold Limit Values (TLV)

Components	Туре	Value
2-FURANCARBOXALDEHYD E (CAS 98-01-1)	TWA	0.2 ppm
FURFURYL ALCOHOL (CAS 98-00-0)	TWA	0.2 ppm

NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended Components

Type

Value

2-FURANCARBOXALDEHYD

E (CAS 98-01-1)

FURFURYL ALCOHOL (CAS

IDLH

1.8 %

75 ppm

10 ppm

US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL)
Components Type Value

FURFURYL ALCOHOL (CAS STEL 60 mg/m3 98-00-0) 15 ppm

TWA 40 mq/m3

Biological limit values

98-00-0)

ACGIH Biological Exposure Indices (BEI)

Components	Value	Determinant	Specimen	Sampling Time
2-FURANCARBOXALDEHYD E (CAS 98-01-1)	200 mg/l	Furoic acid, with hydrolysis	Urine	*

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

2-FURANCARBOXALDEHYDE (CAS 98-01-1)

Can be absorbed through the skin.

Can be absorbed through the skin.

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

2-FURANCARBOXALDEHYDE (CAS 98-01-1) Skin designation applies. FURFURYL ALCOHOL (CAS 98-00-0) Skin designation applies.

US - Tennessee OELs: Skin designation

2-FURANCARBOXALDEHYDE (CAS 98-01-1) Can be absorbed through the skin. FURFURYL ALCOHOL (CAS 98-00-0) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

2-FURANCARBOXALDEHYDE (CAS 98-01-1) Danger of cutaneous absorption FURFURYL ALCOHOL (CAS 98-00-0) Danger of cutaneous absorption

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

FURFURYL ALCOHOL (CAS 98-00-0) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

2-FURANCARBOXALDEHYDE (CAS 98-01-1) Can be absorbed through the skin.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). If risk of splashing, wear safety goggles or face shield.

Material name: FURALAC™ FN RESIN

5821 Version #: 03 Revision date: 08-20-2025 Issue date: 05-17-2022

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Impervious gloves. Neoprene gloves. Latex gloves.

The most suitable glove must be chosen in consultation with the gloves supplier, who can

inform about the breakthrough time of the glove material.

Other Wear appropriate chemical resistant clothing. Wear appropriate footwear.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Wash hands and face before breaks and immediately after handling the product.

9. Physical and chemical properties

Physical state Liquid. **Form** Liquid.

Color Reddish-brown Odor Slightly. Pungent. Melting point/freezing point Not available. **Boiling point or initial boiling** Not available.

point and boiling range

Flammability Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower

(%)

Not available.

Explosive limit - upper

(%)

Not available.

Flash point 168.8 °F (76.0 °C) Pensky-Martens Closed Cup

Auto-ignition temperature Not available. **Decomposition temperature** Not available. Not available. pН Kinematic viscosity Not available.

Solubility

Slightly soluble in water. Solubility (water)

Partition coefficient Not available. (n-octanol/water)

Vapor pressure

<0.13 kPa (<1mm Hg) room temperature

Density and/or relative density **Relative density** 1.24

Not available. Vapor density **Particle characteristics** Not available.

10. Stability and reactivity

Reactivity Contact with acids can cause violent eruptions and/or explosions.

Material is stable under normal conditions. Chemical stability

Possibility of hazardous

reactions

Hazardous reactions or instability may occur under certain conditions of storage or use.

Conditions may include the following: Mixing with acids or acidic catalysts.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Do not Conditions to avoid

pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of

ignition. Contact with incompatible materials.

Incompatible materials Oxidizing material. Acids. Alkalis. Alcohols. Moisture.

Hazardous decomposition

products

Under normal conditions of storage and use, hazardous decomposition products should not be

produced.

5821 Version #: 03 Revision date: 08-20-2025 Issue date: 05-17-2022

11. Toxicological information

Information on likely routes of exposure

Inhalation Toxic if inhaled. May cause irritation to the respiratory system.

Skin contact Causes skin irritation.

Eye contact Causes serious eye irritation.

Ingestion Toxic if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. May cause redness and pain. Irritating to mouth, throat, and stomach.

Irritating to eyes, respiratory system and skin.

Information on toxicological effects

Toxic if swallowed. Toxic by inhalation. **Acute toxicity**

Product Species Test Results

FURALAC™ FN RESIN

Acute

Dermal

LD50 Rabbit 13333 mg/kg

Oral

Point estimate* 100 mg/kg bw

Components Species Test Results

FURFURYL ALCOHOL (CAS 98-00-0)

Acute Inhalation Vapor

Point estimate* 3 mg/l

* Point estimate = Converted acute toxicity point estimate

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

2-FURANCARBOXALDEHYDE (CAS 98-01-1) 3 Not classifiable as to carcinogenicity to humans.

FURFURYL ALCOHOL (CAS 98-00-0) 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity May cause respiratory irritation.

single exposure

Aspiration hazard

Specific target organ toxicity - repeated exposure

Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. May cause damage to organs through prolonged or

repeated exposure. Prolonged exposure may cause chronic effects.

May cause damage to organs through prolonged or repeated exposure.

Further information This product has no known adverse effect on human health.

Material name: FURALAC™ FN RESIN SDS US 6 / 10

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the

environment.

Product Species Test Results

FURALAC™ FN RESIN

Aquatic

Fish LC50 Fish 107.7375 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

2-FURANCARBOXALDEHYDE 0.41 FURFURYL ALCOHOL 0.28

Mobility in soilNo data available.Other adverse effectsNot available.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations. Incineration or landfill should only be considered when recycling in not feasible. Waste should not be disposed of untreated to the sewer unless

fully compliant with the requirements of all authorities with jurisdiction.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste codeThe waste code should be assigned in discussion between the user, the producer and the

waste disposal company.

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container

is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. DO NOT pressurize, cut, heat, or weld containers; they may explode and cause injury or death. Empty product containers may contain product residue. DO NOT reuse empty containers without commercial cleaning or reconditioning. All containers should be disposed of in an environmentally safe manner and in accordance with governmental

regulations.

14. Transport information

DOT

UN number UN2810

UN proper shipping name Toxic, liquids, organic, n.o.s. (Furfural Solution RQ = 25000 lbs)

Transport hazard class(es)

Class 6.1
Subsidiary hazard Label(s) 6.1
Packing group III
Environmental hazards

Marine pollutant No.

Special precautions for Re

user

Read safety instructions, SDS and emergency procedures before handling.

Special provisions IB3, T7, TP1, TP28

Packaging exceptions153Packaging non bulk203Packaging bulk241

IATA

UN number UN2810

UN proper shipping name Toxic liquid, organic, n.o.s. (Furfural Solution)

Transport hazard class(es)
Class 6.1

Subsidiary hazard Packing group III**Environmental hazards** No. **ERG Code** 6L

Special precautions for

user

Read safety instructions, SDS and emergency procedures before handling.

Other information Passenger and cargo

Allowed with restrictions.

aircraft Cargo aircraft only

Allowed with restrictions.

IMDG

UN2810 **UN** number

UN proper shipping name

TOXIC LIQUID, ORGANIC, N.O.S. (Furfural Solution)

Transport hazard class(es)

Class 6.1 **Subsidiary hazard Packing group** III**Environmental hazards**

Marine pollutant No. F-A, S-A **EmS**

Special precautions for Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Not established.

IMO instruments

DOT



IATA; IMDG



General information If shipped by ground in individual containers that are less than 119 gallons (450 L): Not

regulated as a hazardous material (49 CFR 173.121). Package sizes shipped in quantities less than the product reportable quantity are not subject to the RO (reportable quantity)

transportation requirements [25000 lbs / 11350 kg [2418 gal / 9153.2 L].

DOT RQ Details - 2-Furaldehyde [5000 lbs / 2270 kg [516.96 gal / 1956.9 L]

15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication **US** federal regulations

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SDS US

CERCLA Hazardous Substance List (40 CFR 302.4)

2-FURANCARBOXALDEHYDE (CAS 98-01-1)

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312

Yes

Hazardous chemical Classified hazard

categories

Flammable (gases, aerosols, liquids, or solids) Acute toxicity (any route of exposure)

Serious eye damage or eye irritation

Carcinogenicity

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Contains component(s) regulated under the Safe Drinking Water Act.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

2-FURANCARBOXALDEHYDE (CAS 98-01-1) High priority FURFURYL ALCOHOL (CAS 98-00-0) Low priority

US state regulations

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

FURFURYL ALCOHOL (CAS 98-00-0)

California Proposition 65



WARNING: This product can expose you to FURFURYL ALCOHOL, which is known to the State of California

to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

FURFURYL ALCOHOL (CAS 98-00-0) Listed: September 30, 2016

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes

Material name: FURALAC™ FN RESIN

SDS US

Country(s) or region **Inventory name** On inventory (yes/no)*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

05-17-2022 **Issue date** 08-20-2025 **Revision date**

Version # 03

HMIS® is a registered trade and service mark of the NPCA. **Further information**

References

EPA: AQUIRE database

NLM: Hazardous Substances Data Base

US. IARC Monographs on Occupational Exposures to Chemical Agents

Disclaimer Ergon Armor cannot anticipate all conditions under which this information and its product, or

the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

Material name: FURALAC™ FN RESIN 10 / 10

5821 Version #: 03 Revision date: 08-20-2025 Issue date: 05-17-2022

Yes