SAFETY DATA SHEET



1. Identification

Product identifier NOVOCOAT™ SC3300 NOVOLAC EPOXY LINING PART B

Other means of identification None.

Recommended use Not available. **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc. **Company Name**

Address 2829 Lakeland Drive Jackson, MS 39232

After hours telephone

number

1-800-222-7122

Normal work hours telephone number

1-877-982-7667

Website www.ergonarmor.com E-mail sds@ergon.com

Emergency 24-hour telephone number

CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

Information on operation

hours

8:00 a.m. to 5:00 p.m.

2. Hazard(s) identification

Not classified. **Physical hazards**

Health hazards Acute toxicity, dermal Category 4

> Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2 Sensitization, skin Category 1

Environmental hazards Not classified. **OSHA** defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction. Causes

serious eye irritation.

Precautionary statement

Prevention Avoid breathing dust/fume/gas/mist/vapors/spray. Wear protective gloves/protective clothing.

Wear eye/face protection. Wash thoroughly after handling. Contaminated work clothing should

not be allowed out of the workplace. Avoid release to the environment.

IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for Response

several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Take off

contaminated clothing and wash before reuse. If eye irritation persists: Get medical

advice/attention. If skin irritation or rash occurs: Get medical advice/attention. Call a POISON CENTER or doctor/physician if you feel unwell. Specific treatment see Section 4 of this SDS.

Collect spillage.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Material name: NOVOCOAT™ SC3300 NOVOLAC EPOXY LINING PART B 4841 Version #: 04 Revision date: 06-05-2023 Issue date: 11-01-2021

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
BENZYL ALCOHOL		100-51-6	15 - 25
[3-(AMINOMETHYL)PHENYL]METHA NAMINE		1477-55-0	10 - 20
[(DIMETHYLAMINO)METHYL]PHEN OL		25338-55-0	0 - 5
CYCLOHEXANAMINE, 4,4'-METHYLENEBIS-		1761-71-3	0 - 5
			21.42

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or

artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other

proper respiratory medical device. Call a physician or poison control center immediately.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Call a physician

or poison control center immediately. Chemical burns must be treated by a physician. For minor skin contact, avoid spreading material on unaffected skin. Wash contaminated clothing before

reuse. Wash clothing separately before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present,

DO NOT delay irrigation or attempt to remove the lens. Continue rinsing. Call a physician or poison

control center immediately.

Ingestion Call a physician or poison control center immediately. If swallowed, rinse mouth with water (only

if the person is conscious). Never give anything by mouth to a victim who is unconscious or is having convulsions. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way

valve or other proper respiratory medical device.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

General information

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including

blindness could result. May cause an allergic skin reaction. Dermatitis. Rash.

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from the chemical

Special protective equipment and precautions for

Fire fighting equipment/instructions

firefighters

Water fog. Alcohol foam. Foam. Dry chemical powder. Carbon dioxide (CO2).

Water. Do not use water jet as an extinguisher, as this will spread the fire.

Fire may produce irritating, corrosive and/or toxic gases.

Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.

demand breathing apparatus, protective clothing and face mask.

In the event of fire, cool tanks with water spray. Use water spray to cool unopened containers. Cool containers exposed to flames with water until well after the fire is out. Water runoff can cause environmental damage.

Specific methods In the event of fire, cool tanks with water spray. Use water spray to cool unopened containers.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Extinguish all flames in the vicinity. This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Do not get this material in contact with eyes. When using do not eat or drink. Do not get this material in contact with skin. Do not taste or swallow. Avoid prolonged exposure. Use personal protective equipment as required. Do not get this material on clothing. Observe good industrial hygiene practices. Do not breathe dust/fume/gas/mist/vapors/spray. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from food, drink and animal feedingstuffs.

8. Exposure controls/personal protection

Occupational exposure limits

-		-		
US.	ACGIH	Threshold	Limit	Values

Components	Туре	Value	
[3-(AMINOMETHYL)PHENYL]METHANAMINE (CAS 1477-55-0)	Ceiling	0.018 ppm	
US. NIOSH: Pocket Guide to Che Components	mical Hazards Type	Value	
[3-(AMINOMETHYL)PHENYL]METHANAMINE (CAS 1477-55-0)	Ceiling	0.1 mg/m3	

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Туре	Value	
BENZYL ALCOHOL (CAS 100-51-6)	TWA	44.2 mg/m3	
		10 ppm	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

US - California OELs: Skin designation

[3-(AMINOMETHYL)PHENYL]METHANAMINE Can be absorbed through the skin.

(CAS 1477-55-0)

US - Tennessee OELs: Skin designation

[3-(AMINOMETHYL)PHENYL]METHANAMINE Can be absorbed through the skin.

(CAS 1477-55-0)

US ACGIH Threshold Limit Values: Skin designation

[3-(AMINOMETHYL)PHENYL]METHANAMINE Danger of cutaneous absorption

(CAS 1477-55-0)

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

[3-(AMINOMETHYL)PHENYL]METHANAMINE

Can be absorbed through the skin.

(CAS 1477-55-0)

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined

occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical goggles and face shield are recommended.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Skin protection should include disposable chemical resistant coveralls with hoods. Hand protection Other

should include appropriate chemical resistant disposable gloves, such as nitrile rubber.

If in spray application, respiratory protection should include at a minimum a fullface air purifying Respiratory protection

> respirator (APR) with combination particulate (P100) and organic vapor (OV) cartridges. A full-face APR has an assigned protection factor (APF) of 50, as designated by OSHA. As a substitute, a PAPR with a loose-fitting hood could be used as respiratory protection.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Do not get in eyes. Do not get this material in contact with skin. Do not get this material on General hygiene considerations clothing. Wash hands before breaks and immediately after handling the product. Keep away from

food and drink.

9. Physical and chemical properties

Appearance Liquid.

> **Physical state** Liquid. **Form** Liquid.

Color Light Amber to Golden Odor Ammoniacal. Amine-like.

Odor threshold Not available. Hα Alkaline

Melting point/freezing point Not available. Initial boiling point and Not available.

boiling range

Flash point 200.0 °F (93.3 °C) **Evaporation rate** Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Explosive limit - lower

(%)

Not available.

Explosive limit - upper

(%)

Not available.

Vapor pressure Not available. Vapor density Not available. Not available. Relative density

Solubility(ies)

Partial Solubility (water)

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available. **Decomposition temperature** Not available. **Viscosity** Not available.

Other information

Density 8.40 lb/gal estimated Specific gravity 1.006 estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport. **Chemical stability** Stable at normal conditions.

Possibility of hazardous

reactions

Hazardous polymerization can occur with elevated temperatures.

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Acids. Alkaline metals. Amines. Peroxides. Fluorine. Chlorine. Phenols. Strong acids, alkalies and

oxidizing agents.

Hazardous decomposition

products

Toxic gas. If product is burned hazardous gases such as oxides of carbon and nitrogen and various hydrocarbons may be produced. Upon combustion, oxides of chlorine may be released.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Causes skin irritation. Harmful in contact with skin.

Eye contact Causes eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Irritation of eyes and mucous membranes.

Information on toxicological effects

Acute toxicity

Components Species Test Results

BENZYL ALCOHOL (CAS 100-51-6)

<u>Acute</u> Dermal

LD50 Rabbit 2000 mg/kg

Inhalation

LC50 - > 4.178 mg/l, 4 Hours

Oral

LD50 Rat 1230 - 3100 mg/kg

CYCLOHEXANAMINE, 4,4'-METHYLENEBIS- (CAS 1761-71-3)

<u>Acute</u>

Oral

LD50 Rat 380 mg/kg

Skin corrosion/irritation Irritating and may cause redness and pain.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization May cause sensitization by skin contact.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. This product

contains crystalline silica. Silica is a known carcinogen; however in this encapsulated form the

normal routes of exposure are unavailable.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Material name: NOVOCOAT™ SC3300 NOVOLAC EPOXY LINING PART B 4841 Version #: 04 Revision date: 06-05-2023 Issue date: 11-01-2021

^{*} Estimates for product may be based on additional component data not shown.

Specific target organ toxicity Not classified.

- single exposure

Specific target organ toxicity

- repeated exposure

Not classified.

Aspiration hazard Not available.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Harmful to aquatic life. Components of this product are hazardous to aquatic life. Accumulation in

aquatic organisms is expected.

Product Species Test Results

NOVOCOAT™ SC3300 NOVOLAC EPOXY LINING PART B

Aquatic

Acute

Fish LC50 Fish 44.964, 96 hours estimated

Components Species Test Results

BENZYL ALCOHOL (CAS 100-51-6)

Aquatic

Acute

Fish LC50 Bluegill (Lepomis macrochirus) 10, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

BENZYL ALCOHOL 1.1

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Dispose of contents/container in accordance with local/regional/national/international regulations.

This product, in its present state, when discarded or disposed of, is not a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria

for hazardous waste.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste codeThe waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues /

unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Offer rinsed packaging material to local recycling facilities.

14. Transport information

DOT

UN number UN2735

UN proper shipping name Amines, liquid, corrosive, n.o.s. ([3-(Aminomethyl)phenyl]methanamine)

Transport hazard class(es)

Class 8
Subsidiary risk Label(s) 8
Packing group III

Special precautions for

user

Not available.

Special provisions IB3, T7, TP1, TP28

Packaging exceptions 154
Packaging non bulk 203

Material name: NOVOCOAT™ SC3300 NOVOLAC EPOXY LINING PART B 4841 Version #: 04 Revision date: 06-05-2023 Issue date: 11-01-2021

Packaging bulk 241

IATA

UN number UN2735

UN proper shipping name Amines, liquid, corrosive, n.o.s. ([3-(Aminomethyl)phenyl]methanamine)

Transport hazard class(es)

Class 8
Subsidiary risk Packing group III
Environmental hazards No.
ERG Code 8L

Special precautions for Not available.

user

Other information

Passenger and cargo

una cargo

Allowed with restrictions.

aircraft Cargo aircraft only

Allowed with restrictions.

IMDG

UN number UN2735

UN proper shipping name AMINES, LIQUID, CORROSIVE, N.O.S. ([3-(Aminomethyl)phenyl]methanamine)

Transport hazard class(es)

Class 8
Subsidiary risk Packing group III
Environmental hazards

Marine pollutantNo.EmSF-A, S-BSpecial precautions forNot available.

user

Transport in bulk according to Not available.

Annex II of MARPOL 73/78

and the IBC Code

DOT



IATA; IMDG



15. Regulatory information

US federal regulationsThis product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard,

29 CFR 1910.1200.

CERCLA/SARA Hazardous Substances - Not applicable.

All components are on the U.S. EPA TSCA Inventory List.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

Classified hazard

Acute toxicity (any route of exposure)

categories

Skin corrosion or irritation

Serious eye damage or eye irritation Respiratory or skin sensitization

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

 Issue date
 11-01-2021

 Revision date
 06-05-2023

Version # 04

Material name: NOVOCOAT™ SC3300 NOVOLAC EPOXY LINING PART B 4841 Version #: 04 Revision date: 06-05-2023 Issue date: 11-01-2021

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

NFPA ratings Health: 2

Flammability: 0 Instability: 0

References EPA: AQUIRE database

US. IARC Monographs on Occupational Exposures to Chemical Agents

HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any

other materials or in any process, unless specified in the text.

Revision information Product and Company Identification: Alternate Trade Names

Ecological Information: Ecotoxicity

Material name: NOVOCOAT™ SC3300 NOVOLAC EPOXY LINING PART B 4841 Version #: 04 Revision date: 06-05-2023 Issue date: 11-01-2021