

Blackhawk™ 7010 Roof Primer

SELECTION & SPECIFICATION DATA

Type Non-fibered Asphalt Emulsion Concrete Primer

Description Blackhawk 7010 Roof Primer is a water-based, asphalt roof

primer for concrete substrates. It is designed to provide excellent surface conditions for hot-applied asphaltic

membranes.

• Extremely low VOCs

Single-component

Cold-applied

• Concrete primer for asphalt roofing

Color Brown applied, dries black

SUBSTRATES & SURFACE PREPARATION

All Surfaces must be clean and dry. Remove all dirt, dust, oil

and other contaminants.

MIXING & THINNING

Mixing Mix before application to ensure consistency.

Thinning Do not thin.

Cleanup Wet product can be cleaned up using water. Dried material

may be cleaned using mineral spirits or an equivalent

solvent

APPLICATION GUIDANCE

Brush Wide, fiber brush.

Roller Low-nap phenolic core roller.

PACKAGING, ESTIMATING & HANDLING

ITEM# PACKAGING

K-7010-005-001-PL Pail - 4.7 gallons

K-7010-053-001 Drum - 53 gallons

Theoretical Coverage

300 - 400 square feet per gallon depending on surface

orosity

Storage & Shelf Life

Estimated shelf life is 6 months when stored in a dry area at 75°F (24°C). Actual shelf life may vary with storage conditions. Do not store below 40°F (4°C) or above 110°F (43°C). Store indoors. Always inspect the product prior to

(43°C). Store indoors. Always inspect the product prior use to ensure proper uniformity.

SAFETY

Safety Mixes and applications of this product present a number

of hazards. Read and follow the hazard information, precautions and first aid directions on the individual product labels and safety data sheets before using.

Ventilation Use in well ventilated areas.

TYPICAL PHYSICAL PROPERTIES

PROPERTY VALUE

Density 8.7 lbs./gal \pm 0.1 lb./gal

Solids by volume $23\% \pm 1\%$

Dry time at 75°F (25°C) \leq 1 hour

Rev. 12/2025

TERMS AND CONDITIONS OF SALE

While statements, technical information and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user. For all Terms and Conditions of Sale see armor-inc.com.