

## SELECTION & SPECIFICATION DATA

<b>Type</b>	Oxidized Asphalt Cutback
<b>Description</b>	R-17-A-73 Asphalt Coating/Primer is a metal corrosion protection coating and asphalt primer packaged in a convenient aerosol spray can. It offers just the right amount of product for small jobs and touch up work.
<b>Features</b>	<ul style="list-style-type: none"> <li>• Packaged in convenient aerosol spray can</li> <li>• ANSI/NSF 61 certified</li> <li>• Penetrating and sealing primer</li> <li>• Quick drying (less than 5 minutes dry to touch)</li> </ul>
<b>Uses</b>	<ul style="list-style-type: none"> <li>• Metal corrosion protection</li> <li>• Potable water service</li> <li>• Paving maintenance</li> <li>• Roofing primer</li> <li>• Ductile iron pipe and fittings (ID and OD)</li> <li>• Vehicle underbody</li> </ul>
<b>Color</b>	Black
<b>Finish</b>	Gloss
<b>Topcoats</b>	Asphalt, acrylics, epoxies, polyurethanes. Consult ErgonArmor for more information.
<b>Dry Film Thickness (DFT)</b>	1 – 2 mils per coat
<b>Theoretical Coverage Rate</b>	40 square feet per can at 2 coats

## SUBSTRATES & SURFACE PREPARATION

<b>All</b>	All surfaces must be clean and free from debris and loose scale material or anything that may interfere with adhesion or act as a bond breaker with the desired substrate.
------------	--

## CLEANUP & SAFETY

<b>Cleanup</b>	Mineral spirits or equivalent solvent.
<b>Safety</b>	Mixes and applications of this product present a number of hazards. Read and follow the hazard information, precautions and first aid directions on the individual product labels and safety data sheets before using.
<b>Ventilation</b>	Thorough air circulation must be used during and after application until the product is cured. User should test and monitor exposure levels to ensure all personnel are within safe limits. Consult product SDS for further information.

## PACKAGING, HANDLING & STORAGE

<b>Shelf Life</b>	24 months at 75°F (24°C) when kept at recommended storage conditions and in original unopened containers.
<b>Storage Temperature &amp; Humidity</b>	40°F – 110°F (4°C – 43°C) 0 – 100% relative humidity
<b>Storage</b>	Store indoors. Always inspect the product prior to use.
<b>Package Sizes</b>	12 cans per case (16 lbs per case) 1 pallet (100 cases per pallet)

Rev 06/19

### TERMS AND CONDITIONS OF SALE

While statements, technical information and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user. For all Terms and Conditions of Sale see [ergonarmor.com](http://ergonarmor.com).