

Blackhawk™ 5510 Seal Kote Medium

SELECTION & SPECIFICATION DATA

Type	Modified Asphalt
Description	Blackhawk 5510 Seal Kote Medium is a single-component, asbestos-free asphaltic commercial roofing adhesive designed to adhere modified bituminous membranes, particularly in lower temperatures. It can be sprayed or applied using a squeegee. It demonstrates superior resilience to wind uplift testing with the help of an aggressive solvent. Blackhawk 5510 Seal Kote Medium is comprised of a special, low-odor formula that leads the bituminous roofing industry in adhesion under low-temperature conditions.
Features	<ul style="list-style-type: none"> • Superior wind uplift resistance • Low odor • Single-component • Cold-applied • Flexible • Quick-drying
Uses	Adhesive for single- and multi-ply SBS and select APP roofing membranes.
Color	Black
Primer	Self-priming
Solids Content	72% by weight
VOC Value(s)	<350 g/L (2.92 lbs/gal)
Limitations	Not all APP membranes are alike, and adhesion to these modified membranes should be tested. Do not use with membranes containing a burn-off film.

SUBSTRATES & SURFACE PREPARATION

All	All surfaces must be clean and free from debris and loose scale material or anything that may interfere with adhesion or act as a bond breaker with the desired substrate.
------------	--

MIXING & THINNING

Mixing	No mixing required
Thinning	Do not thin
Cleanup	Mineral spirits or similar solvent

APPLICATION GUIDANCE

Airless Spray Pump size: 45:1 or greater
Spray hose: 200 ft maximum x 3/4-inch ID
Whip length: 15 ft x 1/4-inch ID

Squeegee 1/4-inch serrated squeegee

PACKAGING, ESTIMATING & HANDLING

ITEM#	PACKAGING
K-5510-005-001	Pail - 4.7 gallons
K-5510-005-001-UN	UN Pail - 4.7 gallons
K-5510-053-001	Drum - 53 gallons
K-5510-053-001-UL	Drum - 53 gallons
K-5510-053-001-UN	UN Drum - 53 gallons

Theoretical Coverage Rate 1.5 - 2 gallons per square, depending on substrate.

Storage & Shelf Life Estimated shelf life is 12 months when stored in a dry area at 75°F (24°C). Actual shelf life may vary with storage conditions. Do not store below 40°F (4°C) or above 110°F (43°C). Storage indoors is recommended. Always inspect the product prior to use.

SAFETY

Safety Mixes and applications of this product present a number of hazards. Read and follow the hazard information, precautions and first aid directions on the individual product labels and safety data sheets before using.

Ventilation Use in well ventilated areas.

Rev. 08/2025

TERMS AND CONDITIONS OF SALE

While statements, technical information and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user. For all Terms and Conditions of Sale see ergonarmor.com.