SAFETY DATA SHEET



1. Identification

Product identifier PENNCOAT 331 RESIN (All Colors)

Other means of identification None.

Recommended useNot available. **Recommended restrictions**None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.

Address 2829 Lakeland Drive Jackson, MS 39232

USA

After hours telephone

number

1-800-222-7122

Normal work hours

telephone number

1-877-982-7667

Website www.ergonarmor.com
E-mail sds@ergon.com

Emergency 24-hour telephone number

CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

Information on operation

hours

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 3Health hazardsAcute toxicity, oralCategory 5Acute toxicity, inhalationCategory 4Skin corrosion/irritationCategory 2Serious eye damage/eye irritationCategory 2AGerm cell mutagenicityCategory 2

8:00 a.m. to 5:00 p.m.

Environmental hazards Hazardous to the aquatic environment, acute Category 3

hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Flammable liquid and vapor. May be harmful if swallowed. Causes skin irritation. Harmful if inhaled. Causes serious eye irritation. Suspected of causing genetic defects. Harmful to aquatic life.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep container tightly closed. Avoid release to the environment. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Keep away from heat/sparks/open flames and hot surfaces. No smoking.

Material name: PENNCOAT 331 RESIN (All Colors)

Response IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. IF exposed or concerned: Get medical advice/attention. If skin

irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical

advice/attention. In case of fire: Use appropriate media for extinction.

Storage Store in a well-ventilated place. Keep cool. Keep container tightly closed. Keep locked-up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

Se None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Vinyl Ester Resin		68002-44-8	60 - 80
Glass Flake			15 -25
STYRENE		100-42-5	5 - 15

4. First-aid measures

Inhalation Move to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if

victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician if symptoms

develop or persist.

Skin contact Wash off with soap and water. For minor skin contact, avoid spreading material on unaffected skin.

Get medical attention if irritation develops and persists.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention immediately.

Ingestion If swallowed, do NOT induce vomiting. Give a glass of water. Never give liquid to an unconscious

person. If ingestion of a large amount does occur, call a poison control center immediately. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

In case of shortness of breath, give oxygen. Oxygen, if needed. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

treatment needed

Not available.

General information Keep victim warm. Keep victim under observation. Ensure that medical personnel are aware of the

material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Carbon dioxide (CO2). Foam. Dry chemical.

Unsuitable extinguishing

media

Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from

the chemical

Fire may produce irritating, corrosive and/or toxic gases.

Special protective equipment

and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective stations will only provide limited protection.

Fire fighting

equipment/instructions

clothing will only provide limited protection.

In case of fire and/or explosion do not breathe fumes. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Move containers from fire area if you can do so without risk. In the event of fire, cool tanks with water spray. Cool containers exposed to flames with water

nozzles, if possible. If not, withdraw and let fire burn out. **Specific methods**In the event of fire and/or explosion do not breathe fumes

In the event of fire and/or explosion do not breathe fumes. Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. Use water spray to cool unopened containers.

SDS US

until well after the fire is out. For massive fire in cargo area, use unmanned hose holder or monitor

Material name: PENNCOAT 331 RESIN (All Colors)

5256 Version #: 05 Revision date: 10-15-2019 Issue date: 03-25-2015 2 / 8

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Methods and materials for containment and cleaning up

Keep unnecessary personnel away. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Ventilate closed spaces before entering them. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Not available.

Environmental precautions

Contain spillages with sand, earth or any suitable adsorbent material.

7. Handling and storage

Precautions for safe handling

All equipment used when handling the product must be grounded. Avoid contact with eyes, skin, and clothing. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid prolonged exposure. Wear personal protective equipment. Use only with adequate ventilation. Wash thoroughly after handling. Keep away from sources of ignition - No smoking.

Conditions for safe storage, including any incompatibilities

Store in cool place. The pressure in sealed containers can increase under the influence of heat. Keep away from heat and sources of ignition. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a well-ventilated place. Keep container tightly closed. Use care in handling/storage.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Туре	Value	
STYRENE (CAS 100-42-5)	Ceiling	200 ppm	
	TWA	100 ppm	
US. ACGIH Threshold Limit Valu	ues		
Components	Туре	Value	
STYRENE (CAS 100-42-5)	STEL	40 ppm	
	TWA	20 ppm	
US. NIOSH: Pocket Guide to Ch	emical Hazards		
Components	Туре	Value	
STYRENE (CAS 100-42-5)	STEL	425 mg/m3	
		100 ppm	
	TWA	215 mg/m3	
		50 ppm	

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
STYRENE (CAS 100-42-5)	40 μg/l	Styrene	Urine	*
	400 mg/g	Mandelic acid plus phenylglyoxylic acid	Creatinine in urine	*

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

STYRENE (CAS 100-42-5) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

STYRENE (CAS 100-42-5) Skin designation applies.

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection Goggles/face shield are recommended.

Material name: PENNCOAT 331 RESIN (All Colors)

5256 Version #: 05 Revision date: 10-15-2019 Issue date: 03-25-2015 3 / 8

Skin protection

Hand protection Wear protective gloves.

Other Wear appropriate clothing to prevent any possibility of skin contact with solutions containing 10%

or more of this chemical.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

Thermal hazards Not available.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to

remove contaminants.

9. Physical and chemical properties

Appearance Viscous liquid

Physical state Liquid.

Form Viscous Liquid.

Color Grey. Odor Styrene Odor threshold Not available. Not available. pН Melting point/freezing point Not available.

boiling range

Initial boiling point and 294 °F (145.56 °C)

89.6 - 95.0 °F (32.0 - 35.0 °C) Flash point

Evaporation rate Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower 1.1

(%)

Flammability limit -

upper (%)

6.1

Explosive limit - lower

(%)

Explosive limit - upper

(%)

Not available.

Not available.

Vapor pressure 7 hPa Vapor density 3.6 Relative density 1.07 - 1.08

Solubility(ies)

Solubility (water) Insoluble **Partition coefficient** Not available.

(n-octanol/water)

Auto-ignition temperature 914 °F (490 °C) estimated

Decomposition temperature Not available. **Viscosity** Not available.

Other information

VOC 30 - 40 %

10. Stability and reactivity

Not available. Reactivity

Chemical stability Material is stable under normal conditions. However, this material can undergo hazardous

polymerization.

Possibility of hazardous

reactions

Hazardous polymerization can occur. Heat will speed polymerization.

Conditions to avoid Contact with acids. Avoid contact with oxidizing agents. Heat, flames and sparks. **Incompatible materials**

Hazardous decomposition

products

Acids. Aluminum chlorides. Halogens.. Metal salts. Peroxides. Strong bases. Strong oxidizing agents. Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation May be harmful if inhaled.

Skin contact Causes skin irritation.

Eye contact Causes serious eye damage.

Ingestion Harmful if swallowed.

Symptoms related to the

Not available.

physical, chemical and toxicological characteristics

Information on toxicological effects

Harmful if swallowed - may enter lungs if swallowed or vomited Acute toxicity

Components **Species Test Results**

STYRENE (CAS 100-42-5)

Acute

Inhalation

LC50 Rat 24 mg/l, 4 Hours

Oral

LD50 Rat 1 g/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not available. Skin sensitization Not available.

Germ cell mutagenicity Suspected of causing genetic defects.

Carcinogenicity This product contains crystalline silica. Silica is a known carcinogen; however in this encapsulated

form the normal routes of exposure are unavailable.

IARC Monographs. Overall Evaluation of Carcinogenicity

STYRENE (CAS 100-42-5) 2A Probably carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

STYRENE (CAS 100-42-5) Reasonably Anticipated to be a Human Carcinogen.

Reproductive toxicity Not available. Specific target organ toxicity

- single exposure

Not available.

Specific target organ toxicity

repeated exposure

Causes damage to the following organs through prolonged or repeated exposure: Central nervous

system. Respiratory system.

Aspiration hazard May be harmful if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects

12. Ecological information

Ecotoxicity Harmful to aquatic life.

Test Results Components **Species**

STYRENE (CAS 100-42-5)

Aquatic

EC50 Water flea (Daphnia) 42 g/ml, 24 hours Crustacea

Material name: PENNCOAT 331 RESIN (All Colors) 5256 Version #: 05 Revision date: 10-15-2019 Issue date: 03-25-2015 SDS US 5/8 Components Species Test Results

Fish LC50 Sheepshead minnow (Cyprinodon 5.1 - 16 mg/l, 96 hours

variegatus)

Persistence and degradability Not available. **Bioaccumulative potential** Not available.

Partition coefficient n-octanol / water (log Kow)

STYRENE 2.95

Mobility in soilNot available.Other adverse effectsNot available.

13. Disposal considerations

Disposal instructionsDispose in accordance with all applicable regulations. **Hazardous waste code**Dispose in accordance with all applicable regulations.

Double Flammable material with a flash point <140 F

Waste from residues / Dispose of in accordance with local regulations. Avoid discharge into water courses or onto the

unused products ground.

Contaminated packaging Since emptied containers retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

UN number UN1866 UN proper shipping name Resin solution

Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
Packing group III

Special precautions for Not available.

user

Special provisions B1, B52, IB3, T2, TP1

Packaging exceptions 150
Packaging non bulk 173
Packaging bulk 242

IATA

UN number UN1866 **UN proper shipping name** Resin solution

Transport hazard class(es)
Class 3
Subsidiary risk Packing group III
Environmental hazards No.
ERG Code 3L

Special precautions for Not available.

user

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1866

UN proper shipping name RESIN SOLUTION

Transport hazard class(es)
Class 3
Subsidiary risk Packing group III
Environmental hazards

Marine pollutant

•

No

^{*} Estimates for product may be based on additional component data not shown.

EmS F-E, <u>S-E</u> Special precautions for Not available.

Transport in bulk according to Not available. Annex II of MARPOL 73/78

and the IBC Code

DOT



IATA; IMDG



15. Regulatory information

US federal regulations All components are on the U.S. EPA TSCA Inventory List.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard

29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

STYRENE (CAS 100-42-5) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

Classified hazard categories

Flammable (gases, aerosols, liquids, or solids)

Acute toxicity (any route of exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation

Germ cell mutagenicity

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
STYRENE	100-42-5	5 - 15

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

STYRENE (CAS 100-42-5)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Material name: PENNCOAT 331 RESIN (All Colors)

SDS US 5256 Version #: 05 Revision date: 10-15-2019 Issue date: 03-25-2015

Safe Drinking Water Act Not regulated.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

STYRENE (CAS 100-42-5) Other Flavoring Substances with OSHA PEL's

US state regulations WARNING: This product contains a chemical known to the State of California to cause cancer.

California Proposition 65

California Proposition 65 - CRT: Listed date/Carcinogenic substance

STYRENE (CAS 100-42-5) Listed: April 22, 2016

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

STYRENE (CAS 100-42-5)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

Issue date 03-25-2015 **Revision date** 10-15-2019

Version # 05

Further information HMIS® is a registered trade and service mark of the NPCA.

References **HSDB**

IARC Monographs. Overall Evaluation of Carcinogenicity

Disclaimer The information in the sheet was written based on the best knowledge and experience currently

available. The information given is based on data available for the material, the components of the

material, and similar materials.

Revision information Composition / Information on Ingredients: Undisclosed Ingredient Statement

> Physical & Chemical Properties: Multiple Properties Toxicological Information: Toxicological Property Data

Ecological Information: Ecotoxicity

Material name: PENNCOAT 331 RESIN (All Colors) SDS US

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).