# SAFETY DATA SHEET



# 1. Identification

**Product identifier** FLEXJOINT™ POURING GRADE RESIN - ALL COLORS

Other means of identification None.

Recommended use Not available. **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

**Company Name** ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.

2829 Lakeland Drive **Address** Jackson, MS 39232

**USA** 

After hours telephone

number

1-800-222-7122

**Normal work hours** 

telephone number

1-877-982-7667

Website www.ergonarmor.com E-mail sds@ergon.com

**Emergency 24-hour** telephone number

CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

Information on operation 8:00 a.m. to 5:00 p.m.

hours

# 2. Hazard(s) identification

**Physical hazards** Not classified.

**Health hazards** Skin corrosion/irritation Category 2

> Serious eye damage/eye irritation Category 2 Sensitization, skin Category 1 Category 3

**Environmental hazards** Hazardous to the aquatic environment, acute

hazard

**OSHA** defined hazards Not classified.

**Label elements** 



Signal word

**Hazard statement** May cause an allergic skin reaction. Causes serious eye irritation. Causes skin irritation. Harmful to

aquatic life with long lasting effects.

**Precautionary statement** 

**Prevention** Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the

workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye

protection/face protection.

Response IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical

advice/attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. If eye irritation persists: Get medical advice/attention.

Store locked up. Storage

Dispose of contents/container in accordance with local/regional/national/international regulations. Disposal

See section 13 of this SDS for disposal instructions.

Hazard(s) not otherwise

classified (HNOC)

None known.

## 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
QUARTZ		14808-60-7	30 - < 40
POLYPROPYLENE GLYCOL		26142-30-3	20 - < 30
BISPHENOL A-(EPICHLOROHYDRIN) EPOXY RESIN		25068-38-6	0 - 40
TITANIUM DIOXIDE		13463-67-7	< 1

#### 4. First-aid measures

Inhalation Move to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if

> victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention if symptoms

Skin contact Flush skin thoroughly with water. Remove and isolate contaminated clothing and shoes. Wash

contaminated clothing before reuse. Wash off with warm water and soap. For minor skin contact,

avoid spreading material on unaffected skin. Get medical attention if symptoms occur.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes, Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If ingestion of a large

amount does occur, call a poison control center immediately.

Most important

symptoms/effects, acute and

delayed

**Ingestion** 

**Indication of immediate** medical attention and special treatment needed

**General information** 

Not available.

In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves. IF exposed or concerned: Get medical advice/attention. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation.

#### 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water spray, foam, dry powder or carbon dioxide.

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Not applicable.

**Special protective equipment** and precautions for

firefighters

Wear suitable protective equipment. Wear self-contained breathing apparatus and protective

clothina.

Fire fighting equipment/instructions Firefighters must use standard protective equipment including flame retardant coat, helmet with

face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Move containers from fire area if you can do so without risk.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak. Keep out of low areas.

Material name: FLEXJOINT™ POURING GRADE RESIN - ALL COLORS

Methods and materials for containment and cleaning up Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth or absorbent material then place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to

remove residual contamination.

Never return spills in original containers for re-use.

**Environmental precautions** 

Not available.

## 7. Handling and storage

Precautions for safe handling

Do not get this material in contact with eyes. Avoid contact with skin. Wear personal protective

equipment. Avoid prolonged exposure.

Conditions for safe storage, including any incompatibilities

Keep container tightly closed. Store at ambient temperature and atmospheric pressure. Keep the

container in a well-ventilated place. Use care in handling/storage.

# 8. Exposure controls/personal protection

#### Occupational exposure limits

US. OSHA Table Z-1 Limits for A Components	Туре	Value	Form
QUARTZ (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.
TITANIUM DIOXIDE (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CFR 19	10.1000)		
Components	Туре	Value	Form
QUARTZ (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
TITANIUM DIOXIDE (CAS 13463-67-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
US. ACGIH Threshold Limit Valu	es		
Components	Туре	Value	Form
QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction
TITANIUM DIOXIDE (CAS 13463-67-7)	TWA	10 mg/m3	
US. NIOSH: Pocket Guide to Che	emical Hazards		
Components	Туре	Value	Form
QUARTZ (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
ogical limit values No h	piological exposure limits noted f	or the ingredient(s).	

## **Biological limit values**

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

#### Individual protection measures, such as personal protective equipment

**Eye/face protection** Do not get in eyes. Chemical goggles are recommended. Wear safety glasses with side shields (or

goggles). Eye wash fountain is recommended.

**Skin protection** 

**Hand protection** Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style

gloves.

Wear suitable protective clothing and eye/face protection. Other

Respiratory protection Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels

exceeding the exposure limits. If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

Material name: FLEXJOINT™ POURING GRADE RESIN - ALL COLORS

SDS US

Thermal hazards Not available.

**General hygiene** Do not get in eyes. Keep away from food and drink. Handle in accordance with good industrial

considerations hygiene and safety practice.

## 9. Physical and chemical properties

**Appearance** Pigmented, thick, opaque liquid

**Physical state** Liquid. **Form** Liquid. Color Various. Odor Mild.

**Odor threshold** Not available. pН Not available. Melting point/freezing point Not available. Initial boiling point and Not available.

boiling range

> 212.0 °F (> 100.0 °C) Flash point

**Evaporation rate** Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

(%)

Flammability limit -

upper (%)

Not available.

**Explosive limit - lower** 

(%)

Not available.

**Explosive limit - upper** 

(%)

Not available.

Vapor pressure Not available. Vapor density Not available. Not available. Relative density

Solubility(ies)

Solubility (water) Not available. **Partition coefficient** Not available.

(n-octanol/water)

**Auto-ignition temperature** Not available. **Decomposition temperature** Not available. Not available. **Viscosity** 

Other information

Specific gravity 1.15

# 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport

**Chemical stability** Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

**Conditions to avoid** Avoid temperatures exceeding the flash point.

**Incompatible materials** Powerful oxidizers. Chlorine.

**Hazardous decomposition** 

products

No hazardous decomposition products are known.

## 11. Toxicological information

## Information on likely routes of exposure

**Inhalation** Not classified.

Skin contact May cause sensitization by skin contact. Causes skin irritation. Eye contact Causes serious eye irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms related to the physical, chemical and toxicological characteristics Not available.

Information on toxicological effects

**Acute toxicity** Not applicable.

Skin corrosion/irritation Causes skin irritation. Serious eye damage/eye

irritation

Causes eye irritation.

Respiratory or skin sensitization

**Respiratory sensitization** Not available. Skin sensitization Not available. Germ cell mutagenicity Not available.

Carcinogenicity This product contains crystalline silica. Silica is a known carcinogen; however in this encapsulatec

form the normal routes of exposure are unavailable.

IARC Monographs. Overall Evaluation of Carcinogenicity

QUARTZ (CAS 14808-60-7) 1 Carcinogenic to humans.

TITANIUM DIOXIDE (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

OUARTZ (CAS 14808-60-7)

US. National Toxicology Program (NTP) Report on Carcinogens

QUARTZ (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicity Not available. Specific target organ toxicity Not available.

- single exposure

Specific target organ toxicity

Not available.

- repeated exposure

**Aspiration hazard** Not available.

**Chronic effects** Prolonged exposure may cause chronic effects.

**Further information** Product may contain small amounts of crystalline silica.

## 12. Ecological information

## **Ecotoxicity**

Product		Species	Test Results	
FLEXJOINT™ POURIN	G GRADE RESIN - A	ALL COLORS		
Aquatic				
Crustacea	EC50	Daphnia	22.6497 mg/l, 48 hours estimated	
Fish	LC50	Fish	12.5835 mg/l, 96 hours estimated	

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Persistence and degradability Not available. **Bioaccumulative potential** Not available. Mobility in soil Not available. Other adverse effects Not available.

## 13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This product, in

> its present state, when discarded or disposed of, is not a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste.

Dispose in accordance with all applicable regulations.

Waste from residues / unused products

Dispose of in accordance with local regulations.

#### **Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. Transport information

**DOT** 

Not regulated as dangerous goods.

**IATA** 

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

**Transport in bulk according to** Not available.

Annex II of MARPOL 73/78

and the IBC Code

**General information** DOT Regulated Marine Pollutant.

# 15. Regulatory information

**US federal regulations**This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard

29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

CERCLA/SARA Hazardous Substances - Not applicable.

## TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### **CERCLA Hazardous Substance List (40 CFR 302.4)**

Not listed.

#### SARA 304 Emergency release notification

Not regulated.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

QUARTZ (CAS 14808-60-7) Cancer

lung effects

immune system effects

kidney effects

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

## **SARA 302 Extremely hazardous substance**

Not listed.

**SARA 311/312** Yes

**Hazardous chemical** 

Classified hazard Skin corrosion or irritation

**categories** Serious eye damage or eye irritation Respiratory or skin sensitization

Specific target organ toxicity (single or repeated exposure)

#### SARA 313 (TRI reporting)

Not regulated.

#### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

# Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not re

Not regulated.

(SDWA)

## **US state regulations** WARNING: This product contains a chemical known to the State of California to cause cancer.

#### California Proposition 65

# California Proposition 65 - CRT: Listed date/Carcinogenic substance

QUARTZ (CAS 14808-60-7) Listed: October 1, 1988 TITANIUM DIOXIDE (CAS 13463-67-7) Listed: September 2, 2011

# US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

QUARTZ (CAS 14808-60-7) TITANIUM DIOXIDE (CAS 13463-67-7)

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

**Issue date** 12-15-2021

Version # 01

**Further information** HMIS® is a registered trade and service mark of the NPCA.

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

**Revision information** Physical & Chemical Properties: Multiple Properties

Toxicological Information: Toxicological Data

HazReg Data: North America

Material name: FLEXJOINT™ POURING GRADE RESIN - ALL COLORS 5470 Version #: 01 Issue date: 12-15-2021