

Novocoat™ TH1710 Thinner

SELECTION & SPECIFICATION DATA

Type	Solvent
Description	Novocoat TH1710 Thinner is a solvent-based additive for epoxy-based coating and lining systems.
Features	• Proven compatible with Novocoat products • No guesswork to determine dosage rates • One supplier for coating and thinner
Uses	• Lower product viscosity • Extend product pot life • Increase product dry time

MIXING & THINNING

Ratio	Refer to product data sheet for coating or lining product. Use as little thinner as possible, and do not exceed specified dosage rates.
Mixing	Refer to product data sheet for coating or lining product.
Pot Life	Addition of thinner to coating or lining product will extend pot life.
Dry Time	Addition of thinner to coating or lining product will increase dry time.

PACKAGING, ESTIMATING & HANDLING

ITEM #	PRODUCT	PACKAGING
M-TH1710-5GLB-001	Novocoat TH1710 Thinner	5 gal (19 L) Pail
Theoretical Coverage	5 gallons thinner per 100 gallons coating (6.5 fl. oz. per gallon) at 5% 5 gallons thinner per 40 gallons coating (16 fl. oz. per gallon) at 12%	
Storage & Shelf Life	Maintain products in original packaging and sealed until ready for use. Keep away from flames and hot surfaces. Store in a well-ventilated area. Estimated shelf life is 5 years when stored in a dry area below 80°F (27°C).	

SAFETY

Safety	Mixes and applications of this product present a number of hazards. Read and follow the hazard information, precautions and first aid directions on the individual product labels and safety data sheets before using.
Ventilation	Provide thorough air circulation during and after application until the material has cured when it is used in enclosed areas.

TYPICAL PHYSICAL PROPERTIES

PROPERTY	VALUE
Flash point	84°F (29°C) estimated
Density	6.9 lb/gal (0.83 kg/L)
VOC	7.2 lb/gal (0.86 kg/L) estimated

Rev. 10/2025

TERMS AND CONDITIONS OF SALE

While statements, technical information and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user. For all Terms and Conditions of Sale see ergonarmor.com.