# SAFETY DATA SHEET



# 1. Identification

**Product identifier NOVOCOAT™ SC3300-50 NOVOLAC EPOXY LINING PART A** 

Other means of identification None. Recommended use Lining

**Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

**Company Name** ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.

**Address** 2829 Lakeland Drive Jackson, MS 39232

**USA** 

After hours telephone

number

1-800-222-7122

**Normal work hours** 

telephone number

1-877-982-7667

Website www.ergonarmor.com E-mail sds@ergon.com

**Emergency 24-hour** telephone number

CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

Information on operation

hours

8:00 a.m. to 5:00 p.m.

# 2. Hazard(s) identification

**Physical hazards** Not classified.

**Health hazards** Skin corrosion/irritation Category 2

> Serious eye damage/eye irritation Category 2B Sensitization, skin Category 1B Carcinogenicity Category 2

**Environmental hazards** Not classified. **OSHA** defined hazards Not classified.

**Label elements** 



Signal word Warning

**Hazard statement** Suspected of causing cancer by ingestion. Causes skin irritation. Causes serious eye irritation. May

cause an allergic skin reaction.

**Precautionary statement** 

**Prevention** Wear protective gloves. Wear eye/face protection. Wash thoroughly after handling. Avoid

> breathing mist or vapor. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Do not handle until all safety precautions have been read and

understood. Obtain special instructions before use.

Response Specific treatment see Section 4 of this SDS. Wash contaminated clothing before reuse. IF exposed

> or concerned: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. If eye

irritation persists: Get medical advice/attention.

**Storage** Store in accordance with local/regional/national regulations.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Material name: NOVOCOAT™ SC3300-50 NOVOLAC EPOXY LINING PART A 4856 Version #: 01 Issue date: 11-03-2021

Hazard(s) not otherwise classified (HNOC)

None known.

**Supplemental information** 

None.

## 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
PHENOL-FORMALDEHYDE POLYM	ER .	28064-14-4	30 - 50
GLYCIDYL ETHER			
TALC (Mg3Si4O10(OH)2)		14807-96-6	20 - 40
QUARTZ		14808-60-7	5 - 15
TITANIUM DIOXIDE		13463-67-7	5 - 15
1,3-DIGLYCIDYLOXYBENZENE		101-90-6	1 - 10
Other components below reportab	le levels		20 - 40

#### 4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

> Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve

or other proper respiratory medical device. Get medical attention, if needed.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Call a POISON

CENTER or doctor/physician if you feel unwell. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. For minor skin contact, avoid spreading

material on unaffected skin. Take off contaminated clothing and wash before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO **Eye contact** 

NOT delay irrigation or attempt to remove the lens. Continue rinsing. Get medical attention

immediately.

Call a physician or poison control center immediately. Rinse mouth thoroughly. Never give anything **Ingestion** 

by mouth to a victim who is unconscious or is having convulsions. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other

proper respiratory medical device.

Most important symptoms/effects, acute and

delayed

Skin irritation. May cause an allergic skin reaction. Dermatitis. Rash. Irritant effects. May cause redness and pain. Prolonged exposure may cause chronic effects.

**Indication of immediate** medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

**General information** 

Take off contaminated clothing and shoes immediately. In case of shortness of breath, give oxygen IF exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

## 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

Water fog. Foam. Dry chemical powder. Alcohol foam. Carbon dioxide (CO2). Water. Do not use water jet as an extinguisher, as this will spread the fire.

media

Specific hazards arising from the chemical

Fire may produce irritating, corrosive and/or toxic gases.

**Special protective equipment** and precautions for

4856 Version #: 01 Issue date: 11-03-2021

Wear suitable protective equipment. Wear full protective clothing, including helmet, self-contained

firefighters Fire fighting positive pressure or pressure demand breathing apparatus, protective clothing and face mask.

equipment/instructions

Move containers from fire area if you can do so without risk. In the event of fire, cool tanks with water spray. Use water spray to cool unopened containers. Cool containers exposed to flames with water until well after the fire is out. Water runoff can cause environmental damage.

**Specific methods General fire hazards**  In the event of fire, cool tanks with water spray. Use water spray to cool unopened containers.

No unusual fire or explosion hazards noted.

Material name: NOVOCOAT™ SC3300-50 NOVOLAC EPOXY LINING PART A

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Immediately evacuate personnel to safe areas. Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Avoid skin contact and inhalation of vapors during disposal of spills. Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

# Methods and materials for containment and cleaning up

Extinguish all flames in the vicinity.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

## **Environmental precautions**

Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

# 7. Handling and storage

## Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Do not breathe mist or vapor. Do not get this material in contact with eyes. Do not taste or swallow. Avoid contact with skin. Avoid prolonged exposure. Avoid contact with clothing. Do not use in areas without adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash thoroughly after handling. Avoid release to the environment. Do not empty into drains.

Conditions for safe storage, including any incompatibilities

CAUTION Store locked up. Keep away from heat, sparks and open flame. Store in a closed container away from incompatible materials. Store in a well-ventilated place. Keep away from food, drink and animal feedingstuffs. Keep out of the reach of children. Store in accordance with local/regional/national/international regulation.

Value

**Form** 

## 8. Exposure controls/personal protection

#### **Occupational exposure limits**

Components

US. OSHA Table Z-1 Limits for	r Air Contamiı	inants (29 CFR 1910.1000)
-------------------------------	----------------	---------------------------

**Type** 

QUARTZ (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.
TITANIUM DIOXIDE (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
<b>US. OSHA Table Z-3 (29 CFR 19</b> :	( <b>0.1000</b> )		
Components	Туре	Value	Form
QUARTZ (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
TALC (Mg3Si4O10(OH)2) (CAS 14807-96-6)	TWA	0.1 mg/m3	Respirable.
		20 mppcf	
		2.4 mppcf	Respirable.
TITANIUM DIOXIDE (CAS 13463-67-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.

SDS US

US. ACGIH Threshold Limit Values			
Components	Туре	Value	Form
QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
TALC (Mg3Si4O10(OH)2) (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.
TITANIUM DIOXIDE (CAS 13463-67-7)	TWA	10 mg/m3	
US. NIOSH: Pocket Guide to Che	emical Hazards		
Components	Туре	Value	Form
QUARTZ (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.

(CAS 14807-96-6) **Biological limit values** No biological exposure limits noted for the ingredient(s).

Appropriate engineering Provide adequate ventilation, including appropriate local extraction, to ensure that the defined

controls occupational exposure limit is not exceeded. Individual protection measures, such as personal protective equipment

**Eye/face protection** Safety glasses. If risk of splashing, wear safety goggles or face shield.

**TWA** 

Skin protection

TALC (Mg3Si4O10(OH)2)

Hand protection Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style

gloves.

Other Wear appropriate clothing to prevent any possibility of skin contact.

When workers are facing concentrations above the exposure limit they must use appropriate **Respiratory protection** 

certified respirators.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

**General hygiene** considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

2 mg/m3

Respirable.

# 9. Physical and chemical properties

**Appearance** 

**Physical state** Liquid. **Form** Liquid.

Color Not available. Odor Not available. Not available. **Odor threshold** 7 estimated Not available. Melting point/freezing point

Initial boiling point and

boiling range

> 392 °F (> 200 °C)

> 302.0 °F (> 150.0 °C) Flash point

**Evaporation rate** Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

(%)

Flammability limit -

Not available.

upper (%)

**Explosive limit - lower** 

(%)

Not available.

**Explosive limit - upper** 

Not available.

(%)

82.00 Pa at 20°C Vapor pressure Vapor density Not available.

**Relative density** Not available.

Solubility(ies)

**Solubility (water)** Not available.

**Partition coefficient** 

> 3

(n-octanol/water)

Auto-ignition temperature 572 °F (300 °C)

Decomposition temperature Not available.

Viscosity Not available.

Other information

**Density** 12.39 lb/gal estimated

**Specific gravity** 1.48 estimated

# 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport

**Chemical stability** Stable.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

**Conditions to avoid** Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible

materials.

**Incompatible materials** Peroxides. Chlorine. Strong acids, alkalies and oxidizing agents.

**Hazardous decomposition** 

products

If product is burned hazardous gases such as oxides of carbon and nitrogen and various

hydrocarbons may be produced.

## 11. Toxicological information

## Information on likely routes of exposure

**Inhalation** Prolonged inhalation may be harmful.

**Skin contact**Causes skin irritation. **Eye contact**Causes eye irritation.

**Ingestion** Suspected of causing cancer by ingestion. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

## Information on toxicological effects

**Acute toxicity** Not available.

**Skin corrosion/irritation** Corrosive to skin and eyes.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

#### Respiratory or skin sensitization

**Respiratory sensitization** Not available.

**Skin sensitization** May cause sensitization by skin contact.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

**Carcinogenicity** Possible cancer hazard based on tests with laboratory animals. This product contains crystalline

silica. Silica is a known carcinogen; however in this encapsulated form the normal routes of

exposure are unavailable.

# **IARC Monographs. Overall Evaluation of Carcinogenicity**

1,3-DIGLYCIDYLOXYBENZENE (CAS 101-90-6) 2B Possibly carcinogenic to humans.

QUARTZ (CAS 14808-60-7) 1 Carcinogenic to humans.

TALC (Mg3Si4O10(OH)2) (CAS 14807-96-6) 2B Possibly carcinogenic to humans.

3 Not classifiable as to carcinogenicity to humans.

TITANIUM DIOXIDE (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

## OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

QUARTZ (CAS 14808-60-7) Cancer

## **US. National Toxicology Program (NTP) Report on Carcinogens**

1,3-DIGLYCIDYLOXYBENZENE (CAS 101-90-6)

Reasonably Anticipated to be a Human Carcinogen.

QUARTZ (CAS 14808-60-7)

Known To Be Human Carcinogen.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects

**Specific target organ toxicity** 

- single exposure

Not classified.

siligie exposure

Specific target organ toxicity

- repeated exposure

Not classified.

**Aspiration hazard** Not available.

**Chronic effects** Prolonged inhalation may be harmful.

# 12. Ecological information

**Ecotoxicity**The product components are not classified as environmentally hazardous. However, this does not

exclude the possibility that large or frequent spills can have a harmful or damaging effect on the

environment.

**Product Species Test Results** NOVOCOAT™ SC3300-50 NOVOLAC EPOXY LINING PART A Aquatic Crustacea EC50 10810.8105 mg/l, 48 hours estimated Daphnia Fish LC50 10810.8105 mg/l, 96 hours estimated Fish Components **Test Results** Species

PHENOL-FORMALDEHYDE POLYMER GLYCIDYL ETHER (CAS 28064-14-4)

**Aquatic** 

Acute

Fish LC50 Fish

1 - 10 mg/l

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential** Not available.

Partition coefficient n-octanol / water (log Kow)

NOVOCOAT™ SC3300-50 NOVOLAC EPOXY LINING PART A > 3

**Mobility in soil** No data available.

**Other adverse effects**No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

# 13. Disposal considerations

**Disposal instructions** Dispose in accordance with all applicable regulations. When this product as supplied is to be

discarded as waste, it does not meet the definition of a RCRA waste under 40 CFR 261.

Local disposal regulations

**ulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code**The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused products

Di re

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions).

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Offer rinsed packaging material to local recycling facilities.

# 14. Transport information

DOT

Not regulated as dangerous goods.

**IATA** 

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

Transport in bulk according to Not available.

Annex II of MARPOL 73/78

and the IBC Code

# 15. Regulatory information

**US federal regulations**This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard

29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

## TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### **CERCLA Hazardous Substance List (40 CFR 302.4)**

Not listed.

## SARA 304 Emergency release notification

Not regulated.

## OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

QUARTZ (CAS 14808-60-7) Cancer

lung effects

immune system effects

kidney effects

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312

Yes

**Hazardous chemical** 

**Classified hazard** 

Skin corrosion or irritation

categories

Serious eye damage or eye irritation Respiratory or skin sensitization

Carcinogenicity

#### SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
1,3-DIGLYCIDYLOXYBENZENE	101-90-6	1 - 10

## Other federal regulations

### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

## Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)

Not regulated.

**US state regulations** 

## **California Proposition 65**



**WARNING:** WARNING: This product contains a chemical known to the State of California to cause cancer.

## California Proposition 65 - CRT: Listed date/Carcinogenic substance

1,3-DIGLYCIDYLOXYBENZENE (CAS 101-90-6) Listed: July 1, 1989
QUARTZ (CAS 14808-60-7) Listed: October 1, 1988
TITANIUM DIOXIDE (CAS 13463-67-7) Listed: September 2, 2011

# US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

1,3-DIGLYCIDYLOXYBENZENE (CAS 101-90-6)

QUARTZ (CAS 14808-60-7)

TALC (Mg3Si4O10(OH)2) (CAS 14807-96-6) TITANIUM DIOXIDE (CAS 13463-67-7)

### **International Inventories**

New Zealand

**Philippines** 

Country(s) or region

	•	
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes

On inventory (yes/no)\*

Yes

Yes

SDS US

(PICCS)

**Inventory name** 

TaiwanTaiwan Chemical Substance Inventory (TCSI)YesUnited States & Puerto RicoToxic Substances Control Act (TSCA) InventoryYes

Philippine Inventory of Chemicals and Chemical Substances

# 16. Other information, including date of preparation or last revision

**New Zealand Inventory** 

**Issue date** 11-03-2021

Version # 01

NFPA ratings Health: 2

Flammability: 0 Instability: 0

**References** EPA: AQUIRE database

US. IARC Monographs on Occupational Exposures to Chemical Agents

HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

**Revision information** Product and Company Identification: Alternate Trade Names

Hazard(s) identification: Supplemental information

GHS: Classification

Material name: NOVOCOAT™ SC3300-50 NOVOLAC EPOXY LINING PART A

4856 Version #: 01 Issue date: 11-03-2021 8 / 8

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).