# SAFETY DATA SHEET



#### 1. Identification

Product identifier NOVOCOAT™ R7000 QUICK REPAIR TAPE

Other means of identification None.

**Recommended use** Pipe leak repair and rehabilitation

**Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

**Company Name** ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.

Address 2829 Lakeland Drive Jackson, MS 39232

USA

1-800-222-7122

After hours telephone

number

er al work hours 1-877-982-7667

Normal work hours telephone number

Website www.ergonarmor.com
E-mail sds@ergon.com

**Emergency 24-hour** telephone number

CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

Information on operation

hours

8:00 a.m. to 5:00 p.m.

## 2. Hazard(s) identification

**Physical hazards** Not classified.

**Health hazards** Acute toxicity, oral Category 4

Skin corrosion/irritation Category 2
Serious eye damage/eye irritation Category 2
Sensitization, respiratory Category 1
Sensitization, skin Category 1

**Environmental hazards** Not classified. **OSHA defined hazards** Not classified.

Label elements



Signal word Danger

**Hazard statement** Harmful if swallowed. Causes skin irritation. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

**Precautionary statement** 

**Prevention** Avoid breathing dust/fume/gas/mist/vapors/spray. Wear protective gloves/protective clothing/eye

protection/face protection. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. In case of

inadequate ventilation wear respiratory protection.

**Response** Rinse mouth. IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove victim to

fresh air and keep at rest in a position comfortable for breathing. If skin irritation or rash occurs: Get medical advice/attention. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Specific treatment (see this label). If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

**Storage** Store away from incompatible materials.

Material name: NOVOCOAT™ R7000 QUICK REPAIR TAPE 7677 Version #: 01 Issue date: 09-08-2023

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

**Supplemental information** 

None.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
FIBERGLASS		65997-17-3	44 - 46
PU PREPOLYMER		PROPRIETARY	16 - 27
MDI		26447-40-5	13 - 21
MDI HOMOPOLYMER		39310-05-9	5 - 9
ANTIFOAM		556-67-2	< 2
DMDEE		6425-39-4	< 2
AMSA		75-75-2	< 1
COLOR STABILIZER		6683-19-8	< 1

#### 4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or

artificial respiration if needed. Call a poison center or doctor/physician.

Skin contact Immediately flush skin with plenty of water. Remove contaminated clothing. Wash contaminated

clothing before reuse. Get medical attention if irritation develops and persists.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

**Ingestion** Rinse mouth. Drink plenty of water. If vomiting occurs, keep head low so that stomach content

doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance.

Get medical attention immediately.

Most important symptoms/effects, acute and

delayed

**Indication of immediate** medical attention and special treatment needed

Skin irritation. Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause redness and pain. May cause an allergic skin reaction. Dermatitis, Rash.

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. If you feel unwell, seek medical advice (show the label where possible).

#### 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Water. Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Special protective equipment and precautions for firefighters

During fire, gases hazardous to health may be formed.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting equipment/instructions Move containers from fire area if you can do so without risk. Cool containers exposed to heat with

water spray and remove container, if no risk is involved.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

**General fire hazards** No unusual fire or explosion hazards noted.

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: NOVOCOAT™ R7000 QUICK REPAIR TAPE 7677 Version #: 01 Issue date: 09-08-2023

# Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Allow product to cure and dispose of in normal manner in accordance to all applicable state, federal, and local news. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

**Environmental precautions** 

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

#### Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store in a well-ventilated place. Optimal storage temperature between 40-80°F (4-20°C). Store away from incompatible materials (see Section 10 of the SDS). Shelf life: 2 years from date of purchase.

# 8. Exposure controls/personal protection

#### **Occupational exposure limits**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. NIOSH: Pocket Guide to Che Components	emical Hazards Type	Value	Form
FIBERGLASS (CAS 65997-17-3)	TWA	3 fibers/cm3	Fiber.
		3 fibers/cm3	Fibrous dust.
		5 mg/m3	Fiber, total
		5 mg/m3	fibers, total dust
US. Workplace Environmental Ex	xposure Level (WEEL) Guides		
Components	Туре	Value	
ANTIFOAM (CAS 556-67-2)	TWA	10 ppm	

**Biological limit values** 

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Provide eyewash station and safety shower.

#### Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin protection** 

**Hand protection** Wear appropriate chemical resistant gloves. Rubber or plastic gloves.

**Other** Wear appropriate chemical resistant clothing.

**Respiratory protection** When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

# 9. Physical and chemical properties

**Appearance** Fiberglass cloth coated with white tacky resin

Physical stateSolid.FormSolid.ColorWhite

Odor Slight Odor **Odor threshold** Not available. Ηd Not available.

< 59 °F (< 15 °C) Resin only / Not known Melting point/freezing point

Initial boiling point and

boiling range

> 392 °F (> 200 °C)

Flash point 424.4 °F (218.0 °C)

**Evaporation rate** Not available. Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

**Explosive limit - lower** 

(%)

Not available.

**Explosive limit - upper** 

(%)

Not available.

Vapor pressure

0.00002 mm Hg @24°C(75°F) Resin

Vapor density Not available.

Relative density 1.21 g/cm3 Resin only

Solubility(ies)

Solubility (water) Insoluble. **Partition coefficient** Not available. (n-octanol/water)

Auto-ignition temperature

Not available.

**Decomposition temperature** > 392 °F (> 200 °C) Viscosity 45000 - 70000 cP

Other information

**Explosive properties** Not explosive. Oxidizing properties Not oxidizing. Specific gravity 1.133 Resin

# 10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Chemical stability Material is stable under normal conditions. Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid

Elevated temperatures. Moisture contamination may form CO<sub>2</sub> gas pressure.

Incompatible materials Strong bases. Alcohols. Metal compounds. Surface active agents.

**Hazardous decomposition** 

products

No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

Inhalation May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

**Ingestion** Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Gastrointestinal tract. Irritating to mouth, throat, and stomach. Irritating to eyes, respiratory system and skin. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Difficulty in breathing. Skin irritation. May cause redness and pain. May cause an allergic skin

> SDS US 4/7

reaction. Dermatitis. Rash.

#### Information on toxicological effects

Acute toxicity Harmful if swallowed. Skin corrosion/irritation Causes skin irritation. Serious eye damage/eye Causes serious eye irritation.

irritation

Material name: NOVOCOAT™ R7000 QUICK REPAIR TAPE

7677 Version #: 01 Issue date: 09-08-2023

Respiratory or skin sensitization

**Respiratory sensitization** May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

MDI (CAS 26447-40-5) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

**US. National Toxicology Program (NTP) Report on Carcinogens** 

FIBERGLASS (CAS 65997-17-3) Reasonably Anticipated to be a Human Carcinogen.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity

- single exposure

Not classified.

Specific target organ toxicity

Not available.

- repeated exposure Aspiration hazard

Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

No data is available on the degradability of any ingredients in the mixture. Persistence and degradability

**Bioaccumulative potential** 

Partition coefficient n-octanol / water (log Kow)

**AMSA** -2.38**ANTIFOAM** 5.1

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Dispose of in accordance with local regulations. Empty containers or liners may retain some Waste from residues / unused products

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

**IATA** 

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

Transport in bulk according to Not established.

Annex II of MARPOL 73/78

and the IBC Code

7677 Version #: 01 Issue date: 09-08-2023

## 15. Regulatory information

**US federal regulations** 

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard,

29 CFR 1910.1200.

**Toxic Substances Control Act (TSCA)** 

One or more components of the mixture are not on the TSCA 8(b)

inventory or are designated "inactive".

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

ANTIFOAM (CAS 556-67-2) 1.0 % One-Time Export Notification only.

**TSCA Chemical Action Plans, Chemicals of Concern** 

MDI (CAS 26447-40-5) Methylene Diphenyl Diisocyanate (MDI) And Related Compounds

Action Plan [RIN 2070-ZA15]

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Not listed.

**SARA 304 Emergency release notification** 

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

Classified hazard categories

Acute toxicity (any route of exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation Respiratory or skin sensitization

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

**US state regulations** 

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

ANTIFOAM (CAS 556-67-2) FIBERGLASS (CAS 65997-17-3)

MDI (CAS 26447-40-5)

#### **California Proposition 65**



**WARNING:** WARNING: This product contains a chemical known to the State of California to cause cancer. For

more information go to www.P65Warnings.ca.gov.

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes

Material name: NOVOCOAT™ R7000 QUICK REPAIR TAPE

Country(s) or region Inventory name On inventory (yes/no)\*

New ZealandNew Zealand InventoryYesPhilippinesPhilippine Inventory of Chemicals and Chemical SubstancesYes

(PICCS)

Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico

Toxic Substances Control Act (TSCA) Inventory

Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

**Issue date** 09-08-2023

Version # 01

NFPA ratings Health: 2

Flammability: 0 Instability: 0

**Disclaimer** Ergon Armor cannot anticipate all conditions under which this information and its product, or the

products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the

sheet was written based on the best knowledge and experience currently available.

Material name: NOVOCOAT $^{\text{\tiny{TM}}}$  R7000 QUICK REPAIR TAPE

7677 Version #: 01 Issue date: 09-08-2023 7 /