



1. Identification

Product identifier	NOVOCOAT™ SC1100 PRIMER/SEALER FC PART B HARDENER, NOVOLITE REPAIR MORTAR FC PART B HARDENER
Other means of identification	None.
Recommended use	Not available.
Recommended restrictions	None known.
Manufacturer/Importer/Suppl	ier/Distributor information
Company Name Address	ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc. 2829 Lakeland Drive Jackson, MS 39232 USA
After hours telephone number	1-800-222-7122
Normal work hours telephone number	1-877-982-7667
Website	www.ergonarmor.com
E-mail	sds@ergon.com
Emergency 24-hour telephone number	CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887
Information on operation hours	8:00 a.m. to 5:00 p.m.

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Skin corrosion/irritation	Category 1
	Serious eye damage/eye irritation	Category 1
	Sensitization, respiratory	Category 1
	Sensitization, skin	Category 1
	Germ cell mutagenicity	Category 2
	Reproductive toxicity	Category 2
	Specific target organ toxicity, single exposure	Category 1
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 1
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		

Signal word Hazard statement



Danger

Causes severe skin burns and eye damage. Causes serious eye damage. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. Suspected of causing genetic defects. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. Causes damage to organs. Causes damage to organs through prolonged or repeated exposure.

Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Wear protective gloves/protective clothing/eye protection/face protection. Contaminated work clothing should not be allowed out of the workplace. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. In case of inadequate ventilation wear respiratory protection. Use only outdoors or in a well-ventilated area.
Response	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If exposed or concerned: Call a poison center/doctor. Specific treatment see Section 4 of this SDS. Wash contaminated clothing before reuse. Immediately call a POISON CENTER or doctor/physician. Get medical advice/attention if you feel unwell.
Storage	Store locked up. Store in a well-ventilated place. Keep container tightly closed.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
[3-(AMINOMETHYL)PHENYL]METH NAMINE	A	1477-55-0	1 - 20
ALCOHOLS, C9-11, ETHOXYLATED		68439-46-3	1 - 20
FATTY ACIDS, TALL-OIL, REACTION PRODUCTS WITH POLYETHYLENEPOLYAMINES		68910-93-0	1 - 20
PHENOL, 4-NONYL-, BRANCHED		84852-15-3	1 - 20
3-AMINOMETHYL-3,5,5-TRIMETHY CYCLOHEXYLAMINE	L	2855-13-2	1 - 10
PHENOL		108-95-2	1 - 10
TRIETHYLENETETRAMINE		112-24-3	1 - 10
Other components below reportable	e levels		34.74

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a physician if symptoms develop or persist.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Chemical burns must be treated by a physician. Wash contaminated clothing before reuse. Call a physician or poison control center immediately.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.
Ingestion	Rinse mouth thoroughly. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Call a physician or poison control center immediately.
Most important symptoms/effects, acute and delayed	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Burning pain and severe corrosive skin damage. Abdominal pain. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Difficulty in breathing. May cause respiratory irritation.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
General information	In the case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In the event of fire, cool tanks with water spray. Use water spray to cool unopened containers. Cool containers exposed to flames with water until well after the fire is out. Water runoff can cause environmental damage.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Extinguish all flames in the vicinity. Prevent product from entering drains.
5.	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
Environmental precautions	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.
-	be not containing watch. Avoid discharge into drains, watch courses of onto the ground.
7. Handling and storage	
Precautions for safe handling	Provide adequate ventilation. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Do not use in areas without adequate ventilation. When using, do not eat, drink or smoke. Wash thoroughly after handling. Observe good industrial hygiene practices. Do not empty into drains. Avoid release to the environment.
Conditions for safe storage, including any incompatibilities	Store locked up. Keep container tightly closed. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	Туре	Value	
PHENOL (CAS 108-95-2)	PEL	19 mg/m3	
		5 ppm	
US. ACGIH Threshold Limit Value	es (TLV)		
US. ACGIH Threshold Limit Value Components	es (TLV) Type	Value	
	• • _	Value 0.018 ppm	

		Туре		Va	lue
PHENOL (CAS 108-95-2)		IDLH		1.8	· %
				250) ppm
US. NIOSH: Pocket Guide Components	to Chemical H	azards Type	Recommended	-	ts (REL) lue
[3-(AMINOMETHYL)PHENYL]METHANAMINE (CAS 1477-55-0)		Ceiling]	0.1	mg/m3
PHENOL (CAS 108-95-2)		Ceiling	7	60	mg/m3
					6 ppm
		TWA			mg/m3
					pm
US. OARS. Workplace Envi	ironmontal Ex	nocure	Nevel (WEEL) (P
Components		Туре			lue
TRIETHYLENETETRAMINE		TWA		6 n	ng/m3
(CAS 112-24-3)				1 p	pm
logical limit values					
ACGIH Biological Exposure	e Indices (BEI	[)			
Components V	/alue		Determinant	Specimen	Sampling Time
PHENOL (CAS 108-95-2) 2	250 mg/g		Phenol with hydrolysis	Creatinine in urine	*
* - For sampling details, pleas	se see the sour	ce docu	ment.		
osure guidelines					
US - California OELs: Skin	designation				
[3-(AMINOMETHYL)PHEN	-	1INE	Can be	abaarbad throw	ah tho chin
			Currbe	absorbed through	JII UIE SKIII.
(CAS 1477-55-0)	_				-
PHENOL (CAS 108-95-2)			Can be	absorbed through	-
PHENOL (CAS 108-95-2) US - Minnesota Haz Subs:	Skin designat		Can be plies	absorbed throug	gh the skin.
PHENOL (CAS 108-95-2) US - Minnesota Haz Subs: PHENOL (CAS 108-95-2)	Skin designat		Can be plies		gh the skin.
PHENOL (CAS 108-95-2) US - Minnesota Haz Subs: PHENOL (CAS 108-95-2) US - Tennessee OELs: Skir	Skin designat	tion ap	Can be plies Skin de	e absorbed throug	gh the skin. s.
PHENOL (CAS 108-95-2) US - Minnesota Haz Subs: PHENOL (CAS 108-95-2) US - Tennessee OELs: Skin [3-(AMINOMETHYL)PHEN	Skin designat	tion ap	Can be plies Skin de	absorbed throug	gh the skin. s.
PHENOL (CAS 108-95-2) US - Minnesota Haz Subs: PHENOL (CAS 108-95-2) US - Tennessee OELs: Skir	Skin designat n designation NYL]METHANAM	tion ap	Can be plies Skin de Can be	e absorbed throug	gh the skin. s. gh the skin.
PHENOL (CAS 108-95-2) US - Minnesota Haz Subs: PHENOL (CAS 108-95-2) US - Tennessee OELs: Skin [3-(AMINOMETHYL)PHEN (CAS 1477-55-0)	Skin designat n designation NYL]METHANAM	tion ap 1INE	Can be plies Skin de Can be Can be	e absorbed throug esignation applies absorbed throug	gh the skin. s. gh the skin.
PHENOL (CAS 108-95-2) US - Minnesota Haz Subs: PHENOL (CAS 108-95-2) US - Tennessee OELs: Skin [3-(AMINOMETHYL)PHEN (CAS 1477-55-0) PHENOL (CAS 108-95-2) US ACGIH Threshold Limit [3-(AMINOMETHYL)PHEN (CAS 1477-55-0)	Skin designat n designation NYL]METHANAM t Values: Skin NYL]METHANAM	tion ap 1INE design	plies Skin de Can be Can be	e absorbed throug esignation applies absorbed throug	gh the skin. s. gh the skin. gh the skin.
PHENOL (CAS 108-95-2) US - Minnesota Haz Subs: PHENOL (CAS 108-95-2) US - Tennessee OELs: Skin [3-(AMINOMETHYL)PHEN (CAS 1477-55-0) PHENOL (CAS 108-95-2) US ACGIH Threshold Limit [3-(AMINOMETHYL)PHEN (CAS 1477-55-0) PHENOL (CAS 108-95-2)	Skin designat n designation NYL]METHANAM t Values: Skin NYL]METHANAM	tion ap 1INE design 1INE	plies Skin de Can be Can be Can be Dange Dange	e absorbed throug esignation applies absorbed throug absorbed throug r of cutaneous al	gh the skin. s. gh the skin. gh the skin. osorption
PHENOL (CAS 108-95-2) US - Minnesota Haz Subs: PHENOL (CAS 108-95-2) US - Tennessee OELs: Skin [3-(AMINOMETHYL)PHEN (CAS 1477-55-0) PHENOL (CAS 108-95-2) US ACGIH Threshold Limit [3-(AMINOMETHYL)PHEN (CAS 1477-55-0) PHENOL (CAS 108-95-2) US NIOSH Pocket Guide to	Skin designat n designation NYL]METHANAM t Values: Skin NYL]METHANAM o Chemical Ha	tion ap 1INE design 1INE zards:	Can be Skin de Can be Can be Can be Dange Dange Skin designatio	e absorbed throug esignation applies absorbed throug absorbed throug r of cutaneous al r of cutaneous al n	gh the skin. s. gh the skin. gh the skin. osorption osorption
PHENOL (CAS 108-95-2) US - Minnesota Haz Subs: PHENOL (CAS 108-95-2) US - Tennessee OELs: Skin [3-(AMINOMETHYL)PHEN (CAS 1477-55-0) PHENOL (CAS 108-95-2) US ACGIH Threshold Limit [3-(AMINOMETHYL)PHEN (CAS 1477-55-0) PHENOL (CAS 108-95-2) US NIOSH Pocket Guide to [3-(AMINOMETHYL)PHEN (CAS 1477-55-0)	Skin designat n designation NYL]METHANAM t Values: Skin NYL]METHANAM o Chemical Ha	tion ap 1INE design 1INE zards:	Can be Skin de Can be Can be Can be Dange Skin designatio Can be	e absorbed throug esignation applies e absorbed throug e absorbed throug r of cutaneous al r of cutaneous al n e absorbed throug	gh the skin. s. gh the skin. gh the skin. osorption osorption gh the skin.
PHENOL (CAS 108-95-2) US - Minnesota Haz Subs: PHENOL (CAS 108-95-2) US - Tennessee OELs: Skin [3-(AMINOMETHYL)PHEN (CAS 1477-55-0) PHENOL (CAS 108-95-2) US ACGIH Threshold Limit [3-(AMINOMETHYL)PHEN (CAS 1477-55-0) PHENOL (CAS 108-95-2) US NIOSH Pocket Guide to [3-(AMINOMETHYL)PHEN (CAS 1477-55-0) PHENOL (CAS 108-95-2) PHENOL (CAS 108-95-2)	Skin designat n designation NYL]METHANAM t Values: Skin NYL]METHANAM o Chemical Ha NYL]METHANAM	tion ap 1INE design 1INE zards:	Can be Skin de Can be Can be Can be Dange Skin designatio Can be	e absorbed throug esignation applies absorbed throug absorbed throug r of cutaneous al r of cutaneous al n	gh the skin. s. gh the skin. gh the skin. osorption osorption gh the skin.
PHENOL (CAS 108-95-2) US - Minnesota Haz Subs: PHENOL (CAS 108-95-2) US - Tennessee OELs: Skin [3-(AMINOMETHYL)PHEN (CAS 1477-55-0) PHENOL (CAS 108-95-2) US ACGIH Threshold Limit [3-(AMINOMETHYL)PHEN (CAS 1477-55-0) PHENOL (CAS 108-95-2) US NIOSH Pocket Guide to [3-(AMINOMETHYL)PHEN (CAS 1477-55-0) PHENOL (CAS 108-95-2) US WEEL Guides: Skin des TRIETHYLENETETRAMIN	Skin designation n designation NYL]METHANAM t Values: Skin NYL]METHANAM o Chemical Ha NYL]METHANAM signation IE (CAS 112-24-	tion ap 1INE design 1INE zards: 1INE -3)	plies Skin de Can be Can be Can be Dange Skin designatio Can be Can be	e absorbed throug esignation applies absorbed throug absorbed throug r of cutaneous al n absorbed throug absorbed throug absorbed throug	gh the skin. s. gh the skin. gh the skin. psorption gh the skin. gh the skin.
 PHENOL (CAS 108-95-2) US - Minnesota Haz Subs: PHENOL (CAS 108-95-2) US - Tennessee OELs: Skin [3-(AMINOMETHYL)PHEN (CAS 1477-55-0) PHENOL (CAS 108-95-2) US ACGIH Threshold Limit [3-(AMINOMETHYL)PHEN (CAS 1477-55-0) PHENOL (CAS 108-95-2) US NIOSH Pocket Guide to [3-(AMINOMETHYL)PHEN (CAS 1477-55-0) PHENOL (CAS 108-95-2) US WIEL Guides: Skin des TRIETHYLENETETRAMIN US. OSHA Table Z-1 Limits 	Skin designat n designation NYL]METHANAM t Values: Skin NYL]METHANAM o Chemical Ha NYL]METHANAM signation Signation SE (CAS 112-24- s for Air Conta	tion ap 1INE design 1INE zards: 1INE -3)	Can be Skin de Can be Can be Can be Dange Skin designatio Can be Can be Can be	e absorbed throug esignation applies absorbed throug absorbed throug r of cutaneous al r of cutaneous al n e absorbed throug absorbed throug absorbed throug absorbed throug	gh the skin. s. gh the skin. gh the skin. osorption gh the skin. gh the skin.
PHENOL (CAS 108-95-2) US - Minnesota Haz Subs: PHENOL (CAS 108-95-2) US - Tennessee OELs: Skin [3-(AMINOMETHYL)PHEN (CAS 1477-55-0) PHENOL (CAS 108-95-2) US ACGIH Threshold Limit [3-(AMINOMETHYL)PHEN (CAS 1477-55-0) PHENOL (CAS 108-95-2) US NIOSH Pocket Guide to [3-(AMINOMETHYL)PHEN (CAS 1477-55-0) PHENOL (CAS 108-95-2) US WEEL Guides: Skin des TRIETHYLENETETRAMIN US. OSHA Table Z-1 Limits PHENOL (CAS 108-95-2)	Skin designat n designation NYL]METHANAM t Values: Skin NYL]METHANAM o Chemical Ha NYL]METHANAM signation NE (CAS 112-24- s for Air Conta	tion ap 11NE design 11NE zards: 11NE -3) minan	Can be Skin de Can be Can be Can be Dange Skin designatio Can be Can be Can be Can be	e absorbed throug esignation applies absorbed throug absorbed throug r of cutaneous al n absorbed throug absorbed throug absorbed throug .1000) absorbed throug	gh the skin. s. gh the skin. gh the skin. osorption gh the skin. gh the skin. gh the skin.
PHENOL (CAS 108-95-2) US - Minnesota Haz Subs: PHENOL (CAS 108-95-2) US - Tennessee OELs: Skin [3-(AMINOMETHYL)PHEN (CAS 1477-55-0) PHENOL (CAS 108-95-2) US ACGIH Threshold Limit [3-(AMINOMETHYL)PHEN (CAS 1477-55-0) PHENOL (CAS 108-95-2) US NIOSH Pocket Guide to [3-(AMINOMETHYL)PHEN (CAS 1477-55-0) PHENOL (CAS 108-95-2) US WEEL Guides: Skin des TRIETHYLENETETRAMIN US. OSHA Table Z-1 Limits PHENOL (CAS 108-95-2) propriate engineering	Skin designation n designation NYL]METHANAM t Values: Skin NYL]METHANAM o Chemical Ha NYL]METHANAM signation NE (CAS 112-24- s for Air Conta Provide adeq	tion ap 1INE design 1INE zards: 1INE -3) minan uate ve	Can be Skin de Can be Can be Can be Dange Skin designatio Can be Can be Can be Can be	e absorbed throug esignation applies absorbed throug absorbed throug r of cutaneous al n absorbed throug absorbed throug absorbed throug absorbed throug appropriate loca	gh the skin. s. gh the skin. gh the skin. osorption gh the skin. gh the skin. gh the skin.
PHENOL (CAS 108-95-2) US - Minnesota Haz Subs: PHENOL (CAS 108-95-2) US - Tennessee OELs: Skin [3-(AMINOMETHYL)PHEN (CAS 1477-55-0) PHENOL (CAS 108-95-2) US ACGIH Threshold Limit [3-(AMINOMETHYL)PHEN (CAS 1477-55-0) PHENOL (CAS 108-95-2) US NIOSH Pocket Guide to [3-(AMINOMETHYL)PHEN (CAS 1477-55-0) PHENOL (CAS 108-95-2) US WEEL Guides: Skin des TRIETHYLENETETRAMIN US. OSHA Table Z-1 Limits PHENOL (CAS 108-95-2) propriate engineering trols	Skin designation n designation NYL]METHANAM t Values: Skin NYL]METHANAM o Chemical Ha NYL]METHANAM signation NE (CAS 112-24- s for Air Conta Provide adeq occupational es, such as per	tion ap IINE design IINE zards: IINE -3) minan uate ve exposu rsonal	Can be Skin de Can be Can be Can be Dange Skin designatio Can be Can be Can be ts (29 CFR 1910 Can be ts ntilation, including re limit is not exce	e absorbed throug esignation applies absorbed throug absorbed throug r of cutaneous al n e absorbed throug absorbed throug absorbed throug absorbed throug absorbed throug appropriate loca eeded.	gh the skin. s. gh the skin. gh the skin. osorption gh the skin. gh the skin.
PHENOL (CAS 108-95-2) US - Minnesota Haz Subs: PHENOL (CAS 108-95-2) US - Tennessee OELs: Skin [3-(AMINOMETHYL)PHEN (CAS 1477-55-0) PHENOL (CAS 108-95-2) US ACGIH Threshold Limit [3-(AMINOMETHYL)PHEN (CAS 1477-55-0) PHENOL (CAS 108-95-2) US NIOSH Pocket Guide to [3-(AMINOMETHYL)PHEN (CAS 1477-55-0) PHENOL (CAS 108-95-2) US WEEL Guides: Skin des TRIETHYLENETETRAMIN US. OSHA Table Z-1 Limits PHENOL (CAS 108-95-2) propriate engineering trols ividual protection measure Eye/face protection	Skin designation n designation NYL]METHANAM t Values: Skin NYL]METHANAM o Chemical Ha NYL]METHANAM signation NE (CAS 112-24- s for Air Conta Provide adeq occupational es, such as per	tion ap IINE design IINE zards: IINE -3) minan uate ve exposu rsonal	Can be Skin de Can be Can be Can be Dange Skin designatio Can be Can be	e absorbed throug esignation applies absorbed throug absorbed throug r of cutaneous al n e absorbed throug absorbed throug absorbed throug absorbed throug absorbed throug appropriate loca eeded.	gh the skin. s. gh the skin. gh the skin. osorption gh the skin. gh the skin. gh the skin.
 PHENOL (CAS 108-95-2) US - Minnesota Haz Subs: PHENOL (CAS 108-95-2) US - Tennessee OELs: Skin [3-(AMINOMETHYL)PHEN (CAS 1477-55-0) PHENOL (CAS 108-95-2) US ACGIH Threshold Limit [3-(AMINOMETHYL)PHEN (CAS 1477-55-0) PHENOL (CAS 108-95-2) US NIOSH Pocket Guide to [3-(AMINOMETHYL)PHEN (CAS 1477-55-0) PHENOL (CAS 108-95-2) US WEEL Guides: Skin des TRIETHYLENETETRAMIN US. OSHA Table Z-1 Limits PHENOL (CAS 108-95-2) oropriate engineering trols 	Skin designation n designation NYL]METHANAM t Values: Skin NYL]METHANAM o Chemical Ha NYL]METHANAM signation NE (CAS 112-24- s for Air Conta Provide adeq occupational es, such as per Chemical gog	tion ap IINE design IINE zards: IINE -3) minan uate ve exposu rsonal ggles ar	Can be Skin de Can be Can be Can be Dange Skin designatio Can be Can be	e absorbed throug esignation applies absorbed throug absorbed throug r of cutaneous al n e absorbed throug absorbed throug absorbed throug absorbed throug absorbed throug appropriate loca eeded.	gh the skin. s. gh the skin. gh the skin. osorption gh the skin. gh the skin. gh the skin.

Respiratory protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using, do not eat, drink or smoke. Avoid contact with eyes. Avoid contact with skin. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

5. Thysical and chemical	higherines	
Appearance	Liquid.	
Physical state	Liquid.	
Form	Liquid.	
Color	Golden to Light Amber	
Odor	Ammoniacal. Amine-like.	
Odor threshold	Not available.	
рН	Alkaline	
Melting point/freezing point	-22 °F (-30 °C) estimated	
Initial boiling point and boiling range	Not available.	
Flash point	325.0 °F (162.8 °C) estimated	
Evaporation rate	Not available.	
Flammability (solid, gas)	Not applicable.	
Upper/lower flammability or e	-	
Explosive limit - lower (%)	3 % estimated	
Explosive limit - upper (%)	10 % estimated	
Vapor pressure	Not available.	
Vapor density	Not available.	
Relative density	Not available.	
Solubility(ies)		
Solubility (water)	Partial	
Partition coefficient (n-octanol/water)	Not available.	
Auto-ignition temperature	610 °F (321.11 °C) estimated	
Decomposition temperature	Not available.	
Viscosity	Not available.	
Other information		
Density	7.98 estimated	
Specific gravity	0.9576 estimated	
10. Stability and reactive	ty	
-	-	

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Alkaline metals.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

	6		M H H H H	
Skin contact	Causes severe skin burns and eye damage. May cause an allergic skin reaction.			
Eye contact		Causes serious eye damage.		
Ingestion	Expected to be a low ingestion hazard. However, ingestion is not likely to be a primary route of occupational exposure.			
Symptoms related to the physical, chemical and toxicological characteristics	May cause severe irritation or burns to the eyes, skin, gastrointestinal tract, and respiratory system. May cause redness and pain. Exposure may cause temporary irritation, redness, or discomfort. Asthma. May cause respiratory tract irritation, headache, dizziness, fatigue, confusion, visual disturbance, drowsiness, and weakness when exposed to high vapor concentrations. Wheezing. Unconsciousness. Reduced fetal weight. Irritating to mouth, throat, and stomach. May cause drowsiness or dizziness.			
Information on toxicological	effects			
Acute toxicity				
Components	Species		Test Results	
PHENOL (CAS 108-95-2)				
<u>Acute</u>				
Dermal				
LD50	Rat		669 mg/kg	
PHENOL, 4-NONYL-, BRANCHED	(CAS 84852-15-	-3)		
Acute				
Dermal				
LD50	Rabbit		2140 mg/kg	
Oral				
LD50	Rat		1600 mg/kg	
Skin corrosion/irritation	Causes severe skin burns and eye damage.			
Serious eye damage/eye irritation	Causes serious eye damage.			
Respiratory or skin sensitizat	ion			
Respiratory sensitization	May cause allergy or asthma symptoms or breathing difficulties if inhaled.			
Skin sensitization	May cause al	lergic skin disorders in ser	sitive individuals.	
Germ cell mutagenicity	Suspected of	causing genetic defects.		
Carcinogenicity	Not classifiab	Not classifiable as to carcinogenicity to humans.		
IARC Monographs. Overal	ll Evaluation o	f Carcinogenicity		
PHENOL (CAS 108-95-2) 3 Not classifiable as to carcinogenicity to humans.				
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)				
Not listed. US. National Toxicology Program (NTP) Report on Carcinogens				
Not listed.				
Reproductive toxicity	Suspected of	damaging fertility or the u	unborn child.	
Specific target organ toxicity - single exposure		Causes damage to organs. May cause drowsiness or dizziness. Central nervous system. Eyes. Narcotic effects.		
Specific target organ toxicity - repeated exposure	Causes dama Kidneys.	Causes damage to organs through prolonged or repeated exposure. Skin. Eyes. Blood. Liver.		
Aspiration hazard	Not an aspira	ation hazard.		
Chronic effects	•	halation may be harmful.		
	-	· · · · · · · · · · · · · · · · · · ·		
12. Ecological informati				
Ecotoxicity		The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.		
Product		Species		
	ER/SEALER FC F	PART B HARDENER, NOVO	LITE REPAIR MORTAR FC PART B HARDENER	
Aquatic				
<i>Acute</i> Crustacea	EC50	Daphnia	0.2947 mg/l, 48 hours estimated	
	2000	Dapinna	0.2977 mg/i, to hours estimated	

Product		Species	Test Results	
Fish	LC50	Fish	0.1342 mg/l, 96 hours estimate	
Components		Species	Test Results	
3-AMINOMETHYL-3,5,	5-TRIMETHYLCYCL	OHEXYLAMINE (CAS 2855-13-2)		
Aquatic				
Acute				
Crustacea	EC50	Water flea (Daphnia magna)	14.6 - 21.5 mg/l, 48 hours	
ALCOHOLS, C9-11, ET	HOXYLATED (CAS	68439-46-3)		
Aquatic				
Acute				
Crustacea	EC50	Water flea (Daphnia magna)	2.9 - 8.5 mg/l, 48 hours	
Fish	LC50	Fathead minnow (Pimephales promelas)	6 - 12 mg/l, 96 hours	
PHENOL (CAS 108-95-	-2)			
Aquatic				
Acute				
Crustacea	EC50	Water flea (Daphnia magna)	4.24 - 10.7 mg/l, 48 hours	
Fish	LC50	Asiatic knifefish (Notopterus notopterus)	6.85 mg/l, 96 hours	
PHENOL, 4-NONYL-, B	RANCHED (CAS 84	1852-15-3)		
Aquatic				
Acute				
Crustacea	EC50	Clam (Mulinia lateralis)	0.0379 mg/l, 48 hours	
Fish	LC50	Winter flounder (Pleuronectes americanus)	0.017 mg/l, 96 hours	
sistence and degrad	ability No data i	s available on the degradability of any ingredie	nts in the mixture.	
accumulative potent	-	5 , , , 5		
Partition coefficient		or (log Kow)		

Partition coefficient n-o	ctanol / water (log Kow)	
PHENOL		1.46
PHENOL, 4-NONYL-, BRAN	ICHED	5.71
Mobility in soil	No data available.	
Other adverse effects	The product contains volatile organic compounds which have a photochemical ozone creation potential.	

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT	
UN number	UN2735
UN proper shipping name	Amines, liquid, corrosive, n.o.s, or Polyamines, liquid, corrosive, n.o.s. ([3-(AMINOMETHYL)PHENYL]METHANAMINE)
Transport hazard class(es)	
Class	8
Subsidiary hazard	-
Label(s)	8
Packing group	III
Environmental hazards	
Marine pollutant	no

Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions Packaging exceptions Packaging non bulk Packaging bulk	IB3, T7, TP1, TP28 154 203 241
IATA	
UN number	UN2735
UN proper shipping name	Amines, liquid, corrosive, n.o.s. ([3-(AMINOMETHYL)PHENYL]METHANAMINE)
Transport hazard class(es)	
Class	8
Subsidiary hazard	
Packing group	III
Environmental hazards	No.
ERG Code	8L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
IMDG	
UN number	UN2735
UN proper shipping name	AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S. ([3-(AMINOMETHYL)PHENYL]METHANAMINE)
Transport hazard class(es)	
Class	8
Subsidiary hazard	
Packing group	III
Environmental hazards	
Marine pollutant	no
EmS	F-A, S-B
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not established.

DOT



IATA; IMDG



15. Regulatory information

15. Regulatory information 15. Regulatory	ntion					
US federal regulations	This produc 29 CFR 191		s Chemical" as defined	by the OSHA Hazard	Communication Standard,	
Toxic Substances Control Act (TSCA)			One or more components of the mixture are not on the TSCA 8(b) inventory or are designated "inactive".			
TSCA Section 12(b)	Export Notifica	ation (40 CFR 7	07, Subpt. D)			
PHENOL, 4-NONYI TSCA Chemical Actio) 1.0 % One-Time E rn	xport Notification only	у.	
PHENOL, 4-NONYI Toxic Substances Co 721, Subpt E)	, ,		, ,, ,,	, ,	oxylates (NPEs) Action Plan es (SNURs) (40 CFR	
PHENOL, 4-NONYI	-, BRANCHED (CAS 84852-15-3) 721.10765			
CERCLA Hazardous Subs	tance List (40	CFR 302.4)				
PHENOL (CAS 108-95-			Listed.			
SARA 304 Emergency re		ion				
Phenol (CAS 108-95-2)			1000 LBS			
OSHA Specifically Regula	ated Substanc	es (29 CFR 19.	10.1001-1053)			
Not listed.	D					
Superfund Amendments and SARA 302 Extremely haz			(SARA)			
•	AS number	Reportable quantity (pounds)	Threshold planning quantity (pounds)	Threshold planning quantity, lower value (pounds)	Threshold planning quantity, upper value (pounds)	
PHENOL 1	08-95-2	1000		500	10000	
SARA 311/312 Hazardou chemical	is Yes					
Classified hazard categories	Serious eye Respiratory Germ cell m Reproductiv Specific targ	e toxicity		xposure)		
SARA 313 (TRI reporting Chemical name	1)	CA	S number	% by wt.		
PHENOL		_	08-95-2	1 - 10		
PHENOL, 4-NONYL-, BI	RANCHED		4852-15-3	1 - 20		
Other federal regulations						
Clean Air Act (CAA) Sect		dous Air Pollut	ants (HAPS) List			
PHENOL (CAS 108-95- Clean Air Act (CAA) Sect	,	idental Releas	e Prevention (40 CF	R 68 130)		
Not regulated.						
Safe Drinking Water Act (SDWA)	Not regulate	ed.				
FEMA Priority Substa	ances Respirat	ory Health and	Safety in the Flavo	r Manufacturing Wo	orkplace	
PHENOL (CAS 108	-	-	Low priority	-		
US state regulations	-					
US. California. Candidate subd. (a))	e Chemicals Li	st. Safer Consı	imer Products Regu	lations (Cal. Code F	Regs, tit. 22, 69502.3,	
PHENOL (CAS 108-95-) PHENOL, 4-NONYL-, BI		84852-15-3)				
California Proposition 65	5					
California Safe Drinking is not known to contain more information go to	any chemicals	currently listed a				

International Inventories		
Country(s) or region	Inventory name On inventor	y (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
		()

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	01-22-2024
Version #	01
NFPA ratings	Health: 3 Flammability: 1 Instability: 0
Disclaimer	Ergon Armor cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.
Revision information	Hazard(s) identification: Prevention