SAFETY DATA SHEET



1. Identification

Product identifier NOVOCOAT™ EP3700FG CERAMIC CARBIDE HARDENER

Other means of identification None.

Recommended use Industrial tile adhesive and grout

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc. **Company Name**

Address 2829 Lakeland Drive Jackson, MS 39232

After hours telephone

number

1-800-222-7122

Normal work hours

telephone number

1-877-982-7667

Website www.ergonarmor.com E-mail sds@ergon.com

Emergency 24-hour telephone number

CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

Information on operation

hours

8:00 a.m. to 5:00 p.m.

2. Hazard(s) identification

Not classified. **Physical hazards**

Health hazards Skin corrosion/irritation Category 2

> Serious eye damage/eye irritation Category 2 Sensitization, skin Category 1 Reproductive toxicity Category 1

Environmental hazards Not classified. **OSHA** defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May

damage fertility or the unborn child.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

> and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective

gloves/protective clothing/eye protection/face protection/hearing protection.

Response Specific treatment see Section 4 of this SDS. IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN: Wash with plenty of water. If exposed or concerned: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.

Take off contaminated clothing and wash before reuse.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
QUARTZ		14808-60-7	1 - 20
1,3-BENZENEDIMETHANAMINE		1477-55-0	1 - 10
BISPHENOL A		80-05-7	1 - 10
PHENOL, 4-NONYL-, BRANCHED		84852-15-3	1 - 10
TRIETHYLENETETRAMINE		112-24-3	< 1
EPOXY RESIN		25068-38-6	< 0.5
Other components below reportable	levels		82.504

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Eve contact

Most important

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or

artificial respiration if needed. Call a physician or poison control center immediately.

Wash off immediately with soap and plenty of water. Remove contaminated clothing. Wash Skin contact

contaminated clothing before reuse. Get medical attention if irritation develops and persists.

Immediately flush eyes with plenty of water for at least 15 minutes, Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.

Rinse mouth. Do not induce vomiting. Never give anything by mouth to a victim who is **Ingestion**

unconscious or is having convulsions. If vomiting occurs, keep head low so that stomach content

doesn't get into the lungs. Call a physician or poison control center immediately.

symptoms/effects, acute and

delaved

Irritation of eves. Skin irritation. Rash. Dermatitis. May cause an allergic skin reaction. May cause respiratory irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. In case of shortness of breath, give oxygen. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

General information

Do not use water jet as an extinguisher, as this will spread the fire.

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapors and spray mists. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Ensure adequate ventilation. Do not touch or walk through spilled material. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Stop leak if you can do so without risk. Stop the flow of material, if this is without risk. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.

Large Spills: Wet down with water and dike for later disposal. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Shovel the material into waste container. Following product recovery, flush area with water.

Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes, on skin, or on clothing. Provide adequate ventilation. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid prolonged exposure. Should be handled in closed systems, if possible. Use personal protective equipment as required. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	Туре	Value	Form
QUARTZ (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.
US. OSHA Table Z-3 (29 CFR	1910.1000)		
Components	Туре	Value	Form
QUARTZ (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
US. ACGIH Threshold Limit V	alues		
Components	Туре	Value	Form
1,3-BENZENEDIMETHANAM INE (CAS 1477-55-0)	Ceiling	0.018 ppm	
QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide to	Chemical Hazards		
Components	Туре	Value	Form
1,3-BENZENEDIMETHANAM INE (CAS 1477-55-0)	Ceiling	0.1 mg/m3	
QUARTZ (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
US. Workplace Environmenta	l Exposure Level (WEEL) Guides		
Components	Туре	Value	
TRIETHYLENETETRAMINE (CAS 112-24-3)	TWA	6 mg/m3	
		1 ppm	

Occupational Exposure Limits are not relevant to the current physical form of the product.

US - California OELs: Skin designation

1 3-RENZENEDIMETHANAMINE (CAS 1

Exposure guidelines

1,3-BENZENEDIMETHANAMINE (CAS 1477-55-0) Can be absorbed through the skin.

US - Tennessee OELs: Skin designation

1,3-BENZENEDIMETHANAMINE (CAS 1477-55-0) Can be absorbed through the skin.

Material name: NOVOCOAT™ EP3700FG CERAMIC CARBIDE HARDENER

US ACGIH Threshold Limit Values: Skin designation

1,3-BENZENEDIMETHANAMINE (CAS 1477-55-0) Danger of cutaneous absorption

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

1,3-BENZENEDIMETHANAMINE (CAS 1477-55-0) Can be absorbed through the skin.

US WEEL Guides: Skin designation

TRIETHYLENETETRAMINE (CAS 112-24-3) Can be absorbed through the skin.

Appropriate engineering

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined

occupational exposure limit is not exceeded. controls

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles) and a face shield.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Other

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. Do not get in eyes, on skin, on clothing. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Highly filled paste. **Appearance**

Physical state Paste. **Form** Solid. Color Black Odor Amine-like. Odor threshold Not available. pΗ Not available. Melting point/freezing point Not available. Initial boiling point and Not available.

boiling range

> 200.0 °F (> 93.3 °C) Flash point

Evaporation rate Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits **Explosive limit - lower** Not available.

(%)

Explosive limit - upper

(%)

Not available.

Not available. Vapor pressure Vapor density Not available. 2.4 g/ml @20°C Relative density

Solubility(ies)

Solubility (water) Not available. **Partition coefficient** Not available.

(n-octanol/water)

Auto-ignition temperature Not available. **Decomposition temperature** Not available. Viscosity Not available.

Other information

2.4 @20°C Specific gravity

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Acids. Strong oxidizing agents. Powerful oxidizers. Chlorine.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Irritating to skin. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms related to the physical, chemical and toxicological characteristics

Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and

blurred vision. May cause an allergic skin reaction. Skin irritation.

Information on toxicological effects

Acute toxicity

Product Species Test Results

NOVOCOAT™ EP3700FG CERAMIC CARBIDE HARDENER

Acute Dermal

LD50 Rabbit 32590 mg/kg

Inhalation

LC50 Rat 26320 mg/l, 8 Hours

Oral

 LD50
 Rat
 16730 mg/kg

 Components
 Species
 Test Results

PHENOL, 4-NONYL-, BRANCHED (CAS 84852-15-3)

Acute Dermal

LD50 Rabbit 2140 mg/kg

Oral

LD50 Rat 1600 mg/kg

Skin corrosion/irritationIrritating to skin. **Serious eye damage/eye**Irritating to eyes.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity Not available.

Carcinogenicity This product contains crystalline silica. Silica is a known carcinogen; however in this

encapsulated form the normal routes of exposure are unavailable.

IARC Monographs. Overall Evaluation of Carcinogenicity

QUARTZ (CAS 14808-60-7) 1 Carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

QUARTZ (CAS 14808-60-7) Cancer

US. National Toxicology Program (NTP) Report on Carcinogens

QUARTZ (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicity May damage fertility or the unborn child.

^{*} Estimates for product may be based on additional component data not shown.

Specific target organ toxicity

- single exposure

Not classified.

Specific target organ toxicity

- repeated exposure

Not classified.

. openion experie

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product contains a substance which is toxic to aquatic organisms.

Product	Species	Test Results
---------	---------	---------------------

NOVOCOAT™ EP3700FG CERAMIC CARBIDE HARDENER

Aquatic

Crustacea EC50 Daphnia 1.5705, 48 hours Fish LC50 Fish 4.993, 96 hours

Acute

Crustacea EC50 Daphnia 1.9716, 48 hours estimated Fish LC50 Fish 0.8842, 96 hours estimated

Components Species Test Results

BISPHENOL A (CAS 80-05-7)

Aquatic

Acute

Crustacea EC50 Water flea (Daphnia magna) >= 9.2 - <= 11.4 mg/l, 48 hours Fish LC50 Fathead minnow (Pimephales promelas) >= 3.6 - <= 5.4 mg/l, 96 hours

PHENOL, 4-NONYL-, BRANCHED (CAS 84852-15-3)

Aquatic

Acute

Crustacea EC50 Clam (Mulinia lateralis) 0.0379, 48 hours
Fish LC50 Winter flounder (Pleuronectes americanus) 0.017, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

BISPHENOL A 3.32 PHENOL, 4-NONYL-, BRANCHED 5.71

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Dispose of this material and its container to hazardous or special waste collection point. Incinerate

the material under controlled conditions in an approved incinerator. Dispose of contents/container in accordance with local/regional/national/international regulations. When this product as supplied is to be discarded as waste, it does not meet the definition of a RCRA waste under 40 CFR 261.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code D002: Waste Corrosive material [pH <=2 or =>12.5, or corrosive to steel]

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

^{*} Estimates for product may be based on additional component data not shown.

14. Transport information

DOT

UN3077 **UN number**

UN proper shipping name Environmentally hazardous substances, solid, n.o.s. (METAXYLENEDIAMINE)

Transport hazard class(es)

9 Class **Subsidiary risk** Label(s) 9 **Packing group** TTT

Environmental hazards

Marine pollutant NO

Special precautions for

Special provisions

8, 146, 335, A112, B54, IB8, IP3, N20, T1, TP33

Packaging exceptions 155 Packaging non bulk 213 Packaging bulk 240

IATA

UN number UN3077

UN proper shipping name Environmentally hazardous substance, solid, n.o.s. (METAXYLENEDIAMINE)

Transport hazard class(es)

Class 9 **Subsidiary risk Packing group** III **Environmental hazards** YES **ERG Code** 9L

Special precautions for

user Other information Read safety instructions, SDS and emergency procedures before handling.

Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

Allowed with restrictions.

aircraft

Allowed with restrictions. Cargo aircraft only

IMDG

UN3077 **UN number**

UN proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (METAXYLENEDIAMINE), MARINE

POLLUTANT

Transport hazard class(es)

Class 9 **Subsidiary risk** Packing group III **Environmental hazards**

Marine pollutant Yes **EmS** F-A, S-F

Special precautions for Read safety instructions, SDS and emergency procedures before handling.


Transport in bulk according to

Annex II of MARPOL 73/78

and the IBC Code

Not applicable. Not established.

DOT; IATA; IMDG



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations All components are on the U.S. EPA TSCA Inventory List.

Toxic Substances Control Act (TSCA)One or more components of the mixture are not on the TSCA 8(b)

inventory or are designated "inactive".

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

PHENOL, 4-NONYL-, BRANCHED (CAS 84852-15-3) 1.0 % One-Time Export Notification only.

TSCA Chemical Action Plans, Chemicals of Concern

BISPHENOL A (CAS 80-05-7) Bisphenol A Action Plan

PHENOL, 4-NONYL-, BRANCHED (CAS 84852-15-3) Nonylphenol (NP) and Nonylphenol Ethoxylates (NPEs) Action Plan

CERCLA Hazardous Substance List (40 CFR 302.4)

BISPHENOL A (CAS 80-05-7) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

QUARTZ (CAS 14808-60-7) Cancer

lung effects

immune system effects

kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

Classified hazard Skin corrosion or irritation

categories Serious eye damage or eye irritation

Respiratory or skin sensitization

Reproductive toxicity

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
BISPHENOL A	80-05-7	1 - 10
PHENOL, 4-NONYL-, BRANCHED	84852-15-3	1 - 10

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

BISPHENOL A (CAS 80-05-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

BISPHENOL A (CAS 80-05-7) QUARTZ (CAS 14808-60-7)

California Proposition 65



WARNING: This product can expose you to chemicals including QUARTZ, which is known to the State of California to cause cancer, and BISPHENOL A, which is known to the State of California to cause

birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

QUARTZ (CAS 14808-60-7) Listed: October 1, 1988

California Proposition 65 - CRT: Listed date/Developmental toxin

BISPHENOL A (CAS 80-05-7) Listed: December 18, 2020

California Proposition 65 - CRT: Listed date/Female reproductive toxin

BISPHENOL A (CAS 80-05-7) Listed: May 11, 2015

International Inventories

ternational inventories		
Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

 Issue date
 04-19-2023

 Revision date
 04-21-2023

 Version #
 03

version # 03

NFPA ratings Health: 2 Flammability: 1

Instability: 0

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Ergon Armor cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best

knowledge and experience currently available.

Revision information Physical & Chemical Properties: Multiple Properties

Transport Information: Proper Shipping Name/Packing Group

Material name: NOVOCOAT™ EP3700FG CERAMIC CARBIDE HARDENER
7072 Version #: 03 Revision date: 04-21-2023 Issue date: 04-19-2023