

SAFETY DATA SHEET

1. Identification

Product identifier	NOVOCOAT™ EP3700FG CERAMIC CARBIDE HARDENER
Other means of identification	None.
Recommended use	Industrial tile adhesive and grout
Recommended restrictions	None known.
Manufacturer/Importer/Suppl	ier/Distributor information
Company Name	ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.
Address	2829 Lakeland Drive
	Jackson, MS 39232
	USA
After hours telephone number	1-800-222-7122
Normal work hours telephone number	1-877-982-7667
Website	www.ergonarmor.com
E-mail	sds@ergon.com
Emergency 24-hour telephone number	CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887
Information on operation hours	8:00 a.m. to 5:00 p.m.

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2
	Sensitization, skin	Category 1
	Reproductive toxicity	Category 1
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	

Label elements



	\mathbf{v} \mathbf{v}
Signal word	Danger
Hazard statement	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May damage fertility or the unborn child.
Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
Response	IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Specific treatment see Section 4 of this SDS. Take off contaminated clothing and wash before reuse.
Storage	Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
QUARTZ		14808-60-7	1 - 20
1,3-BENZENEDIMETHANAMINE		1477-55-0	1 - 10
BISPHENOL A		80-05-7	1 - 10
PHENOL, 4-NONYL-, BRANCHED		84852-15-3	1 - 10
TRIETHYLENETETRAMINE		112-24-3	< 1
EPOXY RESIN		25068-38-6	< 0.5
Other components below reportable	levels		82.504

Other components below reportable levels

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a physician or poison control center immediately.
Skin contact	Wash off immediately with soap and plenty of water. Remove contaminated clothing. Wash contaminated clothing before reuse. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.
Ingestion	Rinse mouth. Do not induce vomiting. Never give anything by mouth to a victim who is unconscious or is having convulsions. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Call a physician or poison control center immediately.
Most important symptoms/effects, acute and delayed	Irritation of eyes. Skin irritation. Rash. Dermatitis. May cause an allergic skin reaction. May cause respiratory irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. In case of shortness of breath, give oxygen. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.

6. Accidental release measures

Personal precautions, Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during protective equipment and clean-up. Avoid inhalation of vapors and spray mists. Use a NIOSH/MSHA approved respirator if emergency procedures there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Ensure adequate ventilation. Do not touch or walk through spilled material. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up	Stop leak if you can do so without risk. Stop the flow of material, if this is without risk. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.
	Large Spills: Wet down with water and dike for later disposal. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Shovel the material into waste container. Following product recovery, flush area with water.
	Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes, on skin, or on clothing. Provide adequate ventilation. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid prolonged exposure. Should be handled in closed systems, if possible. Use personal protective equipment as required. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	Туре	Value	Form
QUARTZ (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.
US. OSHA Table Z-3 Permi Components	ssible Exposure Limits (PEL) for M Type	lineral Dusts (29 CFR 1910.1) Value	000) Form
QUARTZ (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
US. ACGIH Threshold Limi	t Values (TLV)		
Components	Туре	Value	Form
1,3-BENZENEDIMETHANAM INE (CAS 1477-55-0)	Ceiling	0.018 ppm	
QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
NIOSH. Immediately Dang Components	gerous to Life or Health (IDLH) Va Type	lues, as amended Value	
QUARTZ (CAS 14808-60-7)	IDLH	50 mg/m3	
	to Chemical Hazards Recommende		F
Components	Туре	Value	Form
1,3-BENZENEDIMETHANAM INE (CAS 1477-55-0)	Ceiling	0.1 mg/m3	
QUARTZ (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
US. OARS. Workplace Envi	ironmental Exposure Level (WEEL)		
Components	Туре	Value	
TRIETHYLENETETRAMINE (CAS 112-24-3)	TWA	6 mg/m3	
		1 ppm	
ogical limit values	No biological exposure limits noted	for the ingredient(s).	
osure guidelines	Occupational Exposure Limits are no		

US - California OELs: Skin d	lesignation	
1,3-BENZENEDIMETHANA		Can be absorbed through the skin.
US - Tennessee OELs: Skin	designation	
1,3-BENZENEDIMETHANAMINE (CAS 1477-55-0)		Can be absorbed through the skin.
US ACGIH Threshold Limit	Values: Skin designation	
1,3-BENZENEDIMETHANAMINE (CAS 1477-55-0)		Danger of cutaneous absorption
US NIOSH Pocket Guide to	Chemical Hazards: Skin des	ignation
1,3-BENZENEDIMETHANA	. ,	Can be absorbed through the skin.
US WEEL Guides: Skin desi	gnation	
TRIETHYLENETETRAMINE	E (CAS 112-24-3)	Can be absorbed through the skin.
Appropriate engineering controls	Provide adequate ventilation, i occupational exposure limit is	ncluding appropriate local extraction, to ensure that the defined not exceeded.
Individual protection measures Eye/face protection		e equipment shields (or goggles) and a face shield.
Skin protection		
Hand protection	Wear appropriate chemical res	istant gloves.
Other	Wear appropriate chemical res	istant clothing. Use of an impervious apron is recommended.
Respiratory protection	In case of insufficient ventilation	on, wear suitable respiratory equipment.
Thermal hazards	Wear appropriate thermal prot	ective clothing, when necessary.
General hygiene considerations	observe good personal hygiene eating, drinking, and/or smoki	nce requirements. Do not get in eyes, on skin, on clothing. Always e measures, such as washing after handling the material and before ng. Routinely wash work clothing and protective equipment to inated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance	Highly filled paste.
Physical state	Paste.
Form	Solid.
Color	Black
Odor	Amine-like.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	>200.0 °F (>93.3 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or e	xplosive limits
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	2.4 g/ml @20°C
Solubility(ies) Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.

10. Stability and reactivity

Reactivity Chemical stability	The product is stable and non-reactive under normal conditions of use, storage and transport. Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid Incompatible materials	Avoid temperatures exceeding the flash point. Contact with incompatible materials. Acids. Strong oxidizing agents. Powerful oxidizers. Chlorine.
Hazardous decomposition	No hazardous decomposition products are known.
products	

11. Toxicological information

Information on likely routes of exposure

Information on likely routes o Inhalation	Prolonged inhalation may be harmful.		
Skin contact	-		
	Irritating to skin. May cause an allergic skin reactio		
Eye contact	Causes serious eye irritation.		
Ingestion	Expected to be a low ingestion hazard. However, ingestion is not likely to be a primary route of occupational exposure.		
Symptoms related to the physical, chemical and toxicological characteristics	Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. Skin irritation.		
Information on toxicological	effects		
Acute toxicity			
Product	Species	Test Results	
NOVOCOAT™ EP3700FG CERAMI	C CARBIDE HARDENER		
Acute			
Dermal			
LD50	Rabbit	32589 mg/kg	
Inhalation			
LC50	Rat	26316 mg/l, 8 Hours	
Oral			
LD50	Rat	16727 mg/kg	
Components	Species	Test Results	
PHENOL, 4-NONYL-, BRANCHED	(CAS 84852-15-3)		
<u>Acute</u>			
Dermal LD50	Rabbit	2140 mg/kg	
	Kabbit	2140 119/109	
Oral LD50	Rat	1600 mg/kg	
ED30	Nat	1000 mg/kg	
* Estimates for product may	be based on additional component data not shown.		
* Estimates for product may Skin corrosion/irritation	be based on additional component data not shown. Irritating to skin.		
, ,			
Skin corrosion/irritation Serious eye damage/eye	Irritating to skin. Irritating to eyes.		
Skin corrosion/irritation Serious eye damage/eye irritation	Irritating to skin. Irritating to eyes.		
Skin corrosion/irritation Serious eye damage/eye irritation Respiratory or skin sensitizat	Irritating to skin. Irritating to eyes.		
Skin corrosion/irritation Serious eye damage/eye irritation Respiratory or skin sensitizati Respiratory sensitization	Irritating to skin. Irritating to eyes. ion Not a respiratory sensitizer.		
Skin corrosion/irritation Serious eye damage/eye irritation Respiratory or skin sensitizat Respiratory sensitization Skin sensitization	Irritating to skin. Irritating to eyes. ion Not a respiratory sensitizer. May cause an allergic skin reaction.		
Skin corrosion/irritation Serious eye damage/eye irritation Respiratory or skin sensitization Respiratory sensitization Skin sensitization Germ cell mutagenicity Carcinogenicity	Irritating to skin. Irritating to eyes. ion Not a respiratory sensitizer. May cause an allergic skin reaction. Not available. This product contains crystalline silica. Silica is a k		

OSHA Specifically Regulat	ed Substances	(29 CFR 1910.1001-1053)			
QUARTZ (CAS 14808-60- US. National Toxicology Pr	-7)	Cancer			
QUARTZ (CAS 14808-60-		Known To Be Human Ca	rcinogen.		
Reproductive toxicity		May damage fertility or the unborn child.			
Specific target organ toxicity - single exposure	Not classified.				
Specific target organ toxicity - repeated exposure	Not classified.				
Aspiration hazard	Not an aspiration hazard.				
Chronic effects	Prolonged inh	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.			
12. Ecological information	on				
Ecotoxicity	The product c	ontains a substance which is toxic to aqua	tic organisms.		
Product		Species	Test Results		
NOVOCOAT™ EP3700FG CER	AMIC CARBIDE	HARDENER			
Aquatic					
Crustacea	EC50	Daphnia	1.5705 mg/l, 48 hours		
Fish	LC50	Fish	4.993 mg/l, 96 hours		
Acute					
Crustacea	EC50	Daphnia	1.9716 mg/l, 48 hours estimated		
Fish	LC50	Fish	0.8842 mg/l, 96 hours estimated		
Components		Species	Test Results		
BISPHENOL A (CAS 80-05-7)					
Aquatic					
Acute					
	EC50	Water flea (Daphnia magna)	>= 9.2 - <= 11.4 mg/l, 48 hours		
Fish	LC50	Fathead minnow (Pimephales promelas)	>= 3.6 - <= 5.4 mg/l, 96 hours		
PHENOL, 4-NONYL-, BRANCH	ED (CAS 84852-	·15-3)			
Aquatic					
Acute	5650		0.0000 // 40.1		
	EC50	Clam (Mulinia lateralis)	0.0379 mg/l, 48 hours		
Fish	LC50	Winter flounder (Pleuronectes americanus)	0.017 mg/l, 96 hours		
* Estimates for product may l	be based on add	itional component data not shown.			
Persistence and degradability	No data is ava	ilable on the degradability of this product.			
Bioaccumulative potential	No data availa	ble.			
Partition coefficient n-octa	anol / water (le				
BISPHENOL A		3.32 5.71			
PHENOL, 4-NONYL-, BRANCH Mobility in soil	No data availa				
Other adverse effects			letion photochemical ozone creation		
other deverse enects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.				
13. Disposal consideration	ons				
Disposal instructions	the material u in accordance	nder controlled conditions in an approved	or special waste collection point. Incinerate incinerator. Dispose of contents/container regulations. When this product as supplied ion of a RCRA waste under 40 CFR 261.		
Local disposal regulations		ordance with all applicable regulations.			
	-	le chauld be perigned in discussion betwee	on the year the producer and the weste		

Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT


Not regulated as dangerous goods.

ΙΑΤΑ

UN number	UN3077
UN proper shipping name	Environmentally hazardous substance, solid, n.o.s. (METAXYLENEDIAMINE)
Transport hazard class(es)	
Class	9
Subsidiary hazard	-
Packing group	III
Environmental hazards	YES
ERG Code	9L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
IMDG	
UN number	UN3077
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (METAXYLENEDIAMINE), MARINE POLLUTANT
Transport hazard class(es)	
Class	9
Subsidiary hazard	-
Packing group	III
Environmental hazards	
Marine pollutant	Yes
EmS	F-A, S-F
Special precautions for	Read safety instructions, SDS and emergency procedures before handling.
user	
Transport in bulk according to Annex II of MARPOL 73/78	Not applicable. Not established.

Annex II of MARPC and the IBC Code

IATA; IMDG



Marine pollutant



General information	IMDG Regulated Marin	e Polluta	nt.	
15. Regulatory informati	on			
US federal regulations	All components are on	the U.S.	EPA TSCA Invento	ry List.
Toxic Substances Control A	Act (TSCA)		more components or ry or are designated	of the mixture are not on the TSCA 8(b) d "inactive".
TSCA Section 12(b) Ex	port Notification (40 0	CFR 707	, Subpt. D)	
PHENOL, 4-NONYL-, TSCA Chemical Action	BRANCHED (CAS 84852 Plans, Chemicals of C		1.0 % One-Time E	xport Notification only.
	BRANCHED (CAS 84852			I Plan and Nonylphenol Ethoxylates (NPEs) Action Plan Ficant New Use Rules (SNURs) (40 CFR
	BRANCHED (CAS 84852	-15-3)	721.10765	
CERCLA Hazardous Substa	•			
BISPHENOL A (CAS 80-05 SARA 304 Emergency relea	5-7)		Listed.	
Not regulated.				
OSHA Specifically Regulate	•	R 1910.	1001-1053)	
QUARTZ (CAS 14808-60-	7)		Cancer lung effects immune system eff kidney effects	fects
Superfund Amendments and R	eauthorization Act of	1986 (9	•	
SARA 302 Extremely hazar Not listed.			,	
SARA 311/312 Hazardous chemical	Yes			
Classified hazard categories	Skin corrosion or irritat Serious eye damage or Respiratory or skin sen Reproductive toxicity	· eye irrit		
SARA 313 (TRI reporting) Chemical name		CAS I	number	% by wt.
BISPHENOL A PHENOL, 4-NONYL-, BRA	NCHED	80-0 8485	5-7 2-15-3	1 - 10 1 - 10
Other federal regulations				
Clean Air Act (CAA) Section BISPHENOL A (CAS 80-05 Clean Air Act (CAA) Section	5-7)			R 68.130)
Not regulated.			•	
Safe Drinking Water Act (SDWA)	Not regulated.			
US state regulations				
US. California. Candidate C subd. (a))	chemicals List. Safer C	Consum	er Products Regu	lations (Cal. Code Regs, tit. 22, 69502.3,
	5-7) NCHED (CAS 84852-15-3		er Products Regu	lations (Cal. Code Regs, tit. 22, 69502.3,
subd. (a)) BISPHENOL A (CAS 80-05 PHENOL, 4-NONYL-, BRA	5-7) NCHED (CAS 84852-15-3		er Products Regu	lations (Cal. Code Regs, tit. 22, 69502.3,
subd. (a)) BISPHENOL A (CAS 80-05 PHENOL, 4-NONYL-, BRA QUARTZ (CAS 14808-60- California Proposition 65 WARNING: Thi Cal	5-7) NCHED (CAS 84852-15-3 7) is product can expose yo ifornia to cause cancer, a	3) ou to che and BISI	micals including QU PHENOL A, which is	JARTZ, which is known to the State of known to the State of California to cause
subd. (a)) BISPHENOL A (CAS 80-05 PHENOL, 4-NONYL-, BRA QUARTZ (CAS 14808-60- California Proposition 65 WARNING: Thi Cal bir	5-7) NCHED (CAS 84852-15-3 7) is product can expose yo ifornia to cause cancer, a th defects or other repro	3) ou to che and BISI oductive	micals including QL PHENOL A, which is harm. For more infe	JARTZ, which is known to the State of known to the State of California to cause ormation go to www.P65Warnings.ca.gov.
subd. (a)) BISPHENOL A (CAS 80-05 PHENOL, 4-NONYL-, BRA QUARTZ (CAS 14808-60- California Proposition 65 WARNING: Thi Cal	5-7) NCHED (CAS 84852-15-3 7) is product can expose yo ifornia to cause cancer, a th defects or other repro 65 - CRT: Listed date/ -60-7)	3) ou to che and BISI oductive /Carcine	micals including QU PHENOL A, which is harm. For more info ogenic substance Listed: October 1,	JARTZ, which is known to the State of known to the State of California to cause ormation go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Female reproductive toxin

BISPHENOL A (CAS 80-05-7) Listed: May 11, 2015

International Inventories		
Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	04-19-2023
Revision date	04-18-2024
Version #	04
NFPA ratings	Health: 2 Flammability: 1 Instability: 0
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Ergon Armor cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.
Revision information	This document has undergone significant changes and should be reviewed in its entirety.