

FLEXJOINT™ U500 Sealant


Mixing Guide - Caulking Cartridge




Use an Albion B26 T600 or similar 26:1 thrust ratio dispensing gun for the most consistent mix.
Lower thrust ratios can lead to inconsistent results.

MIXING INSTRUCTIONS


1. Shake the cartridge well for 1 minute before use.




2. Unscrew the locking nut and remove the plug.




3. Place the static mixer over the cartridge neck and secure tightly with the locking nut.




4. Pull back the pistons in the caulking gun and securely load the cartridge in the cradle.




5. Hold the gun straight up at a 90° angle and slowly pull the trigger to purge any air from the unit. Drive the material to the top of the mixer.



6. Tilt the gun down and purge the first 3-4 shots of the material into a disposable cup. The gun should remain tilted downward whenever the cartridge is in use.



7. To reuse later, tilt the cartridge down, remove the mixer, wipe the excess material off the cartridge neck, then replace the plug and screw on the locking nut. Use a new static mixer with the next use.



Rev. 01/2025

TERMS AND CONDITIONS OF SALE

While statements, technical information and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user. For all Terms and Conditions of Sale see ergonarmor.com.