

1. Identification

Product identifier **BLACKHAWKTM 5360 ROOFING ADHESIVE**

Other means of identification None.

Recommended use Cold Adhesive

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name Armor Limited, Inc.
Address 2410 US-15 South, Sumter, SC 29150

After hours telephone number 1-877-982-7667

Normal work hours telephone number 1-877-982-7667

Website www.armor-inc.com

E-mail customerservice@armor-inc.com

Emergency 24-hour telephone number CHEMTREC North America: +1-800-424-9300, International: +1-703-527-3887

Information on operation hours 8:00 a.m. to 5:00 p.m.

2. Hazard(s) identification

Hazards for the product as sold

Physical hazards	Flammable liquids	Category 3
Health hazards	Acute toxicity, inhalation	Category 4
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2
	Germ cell mutagenicity	Category 1
	Carcinogenicity	Category 1
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	

Label elements



Signal word Danger

Hazard statement Flammable liquid and vapor. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause genetic defects. May cause cancer. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Wear protective gloves/protective clothing/eye protection/face protection. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Keep container tightly closed. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area.

Response

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If exposed or concerned: Get medical advice/attention. Take off contaminated clothing and wash before reuse. Call a poison center/doctor if you feel unwell. Specific treatment see Section 4 of this SDS. In case of fire: Use appropriate media for extinction.

Storage

Keep container tightly closed. Store locked up. Store in a well-ventilated place. Keep cool.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

Vapors containing hydrogen sulfide may accumulate during storage or transport. HYDROGEN SULFIDE (H₂S) can be harmful if inhaled.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS No./Unique ID	%
ASPHALT		8052-42-4	20 - 40
MINERAL SPIRITS		8052-41-3/64742-48-9	10 - 20
SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.		64742-95-6	1 - 10
ATTAPULGITE CLAY, HYDROUS MAGNESIUM ALUMINUM SILICATE		12174-11-7	1 - 5
1,2,4-Trimethylbenzene		95-63-6	0 - 5
QUARTZ		14808-60-7	< 1
Other components below reportable levels			53.6549737

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a physician if symptoms develop or persist.

Skin contact

Wash the skin immediately with soap and water. Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. Get medical attention if irritation develops and persists.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Call a physician or poison control center immediately.

Most important symptoms/effects, acute and delayed

Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects. May cause drowsiness or dizziness. Nausea, vomiting. Headache. May cause skin dryness or cracking. Unconsciousness. Fatigue. Aspiration may cause pulmonary edema and pneumonitis.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

If you feel unwell, seek medical advice (show the label where possible). Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Move containers from fire area if you can do so without risk. Use water spray to keep fire-exposed containers cool.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Do not breathe mist/vapors. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Use appropriate containment to avoid environmental contamination. Ventilate closed spaces before entering them. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Wash area with soap and water. Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground. Avoid release to the environment.

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist/vapors. Do not taste or swallow. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Hydrogen sulfide, a very highly toxic gas, may be present with this material. Keep face clear of tank and/or tank car openings.
Conditions for safe storage, including any incompatibilities	Eliminate sources of ignition. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Ground/bond container and equipment. Store locked up. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
MINERAL SPIRITS	PEL	2900 mg/m3 500 ppm	
QUARTZ (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.

US. OSHA Table Z-3 Permissible Exposure Limits (PEL) for Mineral Dusts (29 CFR 1910.1000)

Components	Type	Value	Form
QUARTZ (CAS 14808-60-7)	TWA	0.1 mg/m3 2.4 mppcf	Respirable. Respirable.

US. ACGIH Threshold Limit Values (TLV)

Components	Type	Value	Form
1,2,4-Trimethylbenzene (CAS 95-63-6)	TWA	10 ppm	
ASPHALT (CAS 8052-42-4)	TWA	0.5 mg/m3	Inhalable fume.
MINERAL SPIRITS	TWA	100 ppm	
QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.

NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended

Components	Type	Value
MINERAL SPIRITS	IDLH	20000 mg/m3
QUARTZ (CAS 14808-60-7)	IDLH	50 mg/m3

US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL)

Components	Type	Value	Form
1,2,4-Trimethylbenzene (CAS 95-63-6)	TWA	125 mg/m3 25 ppm	
ASPHALT (CAS 8052-42-4)	Ceiling	5 mg/m3	Fume.
MINERAL SPIRITS	Ceiling	1800 mg/m3	
	TWA	350 mg/m3	
QUARTZ (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.

Biological limit values

ACGIH Biological Exposure Indices (BEI)

Components	Value	Determinant	Specimen	Sampling Time
ASPHALT (CAS 8052-42-4)	2.5 µg/l	1-Hydroxypyrene, with hydrolysis (1-HP)	Urine	*

* - For sampling details, please see the source document.

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke.

9. Physical and chemical properties

Physical state	Liquid.
Form	Liquid. Viscous.
Color	Brown to Black
Odor	Mild Petroleum Odor
Melting point/freezing point	Not available.
Boiling point or initial boiling point and boiling range	Not available.
Flammability	Not applicable.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Flash point	> 100.0 - < 140.0 °F (> 37.8 - < 60.0 °C) Cleveland Open Cup
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
pH	Not available.
Kinematic viscosity	Not available.
Solubility	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Vapor pressure	Not available.
Density and/or relative density	Not available.
Vapor density	Not available.
Particle characteristics	Not available.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Acids. Strong oxidizing agents. Fluorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information**Information on likely routes of exposure**

Inhalation	May be harmful if inhaled.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye irritation.
Ingestion	May be harmful if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.

Symptoms related to the physical, chemical and toxicological characteristics	Aspiration may cause pulmonary edema and pneumonitis. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. May cause redness and pain. Contact may cause redness, burning, drying, and cracking of the skin, and skin damage. May cause drowsiness and dizziness. Headache. Nausea, vomiting.
---	--

Information on toxicological effects

Acute toxicity Harmful if inhaled.

Product	Species	Test Results
BLACKHAWK™ 5360 ROOFING ADHESIVE		
Acute		
Dermal		
ATEmix		2204 mg/kg bw
Oral		
ATEmix		61630 mg/kg bw

Components	Species	Test Results
1,2,4-Trimethylbenzene (CAS 95-63-6)		
Acute		
Dermal		
LD50	Rabbit	> 3160 mg/kg
Inhalation		
<i>Vapor</i>		
LC50	Rat	> 10.2 mg/l, 4 Hours
Point estimate*		11 mg/l
Oral		
LD50	Rat	3280 mg/kg
ASPHALT (CAS 8052-42-4)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Oral		
LD50	Rat	> 5000 mg/kg

* Point estimate = Converted acute toxicity point estimate

Skin corrosion/irritation Causes skin irritation.

Corrosivity

1,2,4-Trimethylbenzene

Result: Skin irritation
Species: Rabbit

Serious eye damage/eye irritation Causes serious eye irritation.

Eye

1,2,4-Trimethylbenzene

Result: Irritation to eyes, reversing within 21 days

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Skin sensitization

1,2,4-Trimethylbenzene

Maximization test
Result: Negative
Species: Guinea pig

Germ cell mutagenicity May cause genetic defects.

Germ cell mutagenicity: Ames test

1,2,4-Trimethylbenzene

In vitro
Result: Negative

Germ cell mutagenicity: Micronucleus

1,2,4-Trimethylbenzene

In vivo
Result: Negative
Species: Mouse

Mutagenicity

1,2,4-Trimethylbenzene

EC B10: Mutagenicity (in vitro mammalian cytogenetic test)
Result: Negative

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

ASPHALT (CAS 8052-42-4)	2B Possibly carcinogenic to humans.
ATTAPULGITE CLAY, HYDROUS MAGNESIUM	2B Possibly carcinogenic to humans.
ALUMINUM SILICATE (CAS 12174-11-7)	
	3 Not classifiable as to carcinogenicity to humans.
MINERAL SPIRITS (CAS 8052-41-3/64742-48-9)	3 Not classifiable as to carcinogenicity to humans.
QUARTZ (CAS 14808-60-7)	1 Carcinogenic to humans.
SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM. (CAS 64742-95-6)	3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

QUARTZ (CAS 14808-60-7)	Cancer
-------------------------	--------

US. National Toxicology Program (NTP) Report on Carcinogens

ASPHALT (CAS 8052-42-4)	Known To Be Human Carcinogen.
ATTAPULGITE CLAY, HYDROUS MAGNESIUM	Reasonably Anticipated to be a Human Carcinogen.
ALUMINUM SILICATE (CAS 12174-11-7)	
QUARTZ (CAS 14808-60-7)	Known To Be Human Carcinogen.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Reproductivity

1,2,4-Trimethylbenzene	Embryo-foetal development (Inhalation) Result: Negative Species: Rat Three-generation reproduction toxicity study Result: Negative Species: Rat
------------------------	--

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure May cause damage to organs through prolonged or repeated exposure.

1,2,4-Trimethylbenzene	1230 mg/m ³ NOAEL (Inhalation) Species: Rat Test Duration: 90 days 600 mg/kg NOAEL (Ingestion) Species: Rat Test Duration: 90 days
------------------------	--

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Causes damage to organs through prolonged or repeated exposure. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Product		Species	Test Results
BLACKHAWK™ 5360 ROOFING ADHESIVE			
Aquatic			
Crustacea	EC50	Daphnia	8394.4443 mg/l, 48 hours
Fish	LC50	Fish	50.8981 mg/l, 96 hours
Components			
1,2,4-Trimethylbenzene (CAS 95-63-6)			
Aquatic			
<i>Acute</i>			
Algae	EC50	Algae	2.356 mg/l, 96 Hours
Crustacea	LC50	Daphnia magna	3.6 mg/l, 48 hours
Fish	LC50	Pimephales promelas	7.72 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential**Partition coefficient n-octanol / water (log Kow)**

1,2,4-Trimethylbenzene	3.78
------------------------	------

Mobility in soil No data available.

Other adverse effects	The product contains volatile organic compounds which have a photochemical ozone creation potential.
------------------------------	--

13. Disposal considerations

Disposal instructions	Dispose of this material and its container to hazardous or special waste collection point. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	D001: Waste Flammable material with a flash point <140 F D018: Waste Benzene The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number	UN1999
UN proper shipping name	Tars, liquid including road oils and cut back bitumens
Transport hazard class(es)	
Class	3
Subsidiary hazard	-
Label(s)	3
Packing group	III
Environmental hazards	
Marine pollutant	No.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	B1, B13, IB3, T1, TP3
Packaging exceptions	150
Packaging non bulk	203
Packaging bulk	242

IATA

UN number	UN1999
UN proper shipping name	Tars, liquid including road asphalt and oils, bitumen and cut backs
Transport hazard class(es)	
Class	3
Subsidiary hazard	-
Packing group	III
Environmental hazards	No.
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.

IMDG

UN number	UN1999
UN proper shipping name	TARS, LIQUID including road oils, and cutback bitumens
Transport hazard class(es)	
Class	3
Subsidiary hazard	-
Packing group	III
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-E

Special precautions for user

Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to IMO instruments Not established.

DOT



IATA; IMDG



General information

If shipped by ground in individual containers that are less than 119 gallons (450 L): Not regulated as a hazardous material (49 CFR 173.121). If shipped by vessel in individual containers that are less than 119 gallons (450 L) each, then IMDG 2.3.2.5 exception applies. Not subject to the provisions for marking, labelling, and testing of packages. "Transport in accordance with 2.3.2.5 of the IMDG code."

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

One or more components of the mixture are not on the TSCA 8(b) inventory or are designated "inactive".

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

QUARTZ (CAS 14808-60-7)

Cancer
lung effects
immune system effects
kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312

Yes

Hazardous chemical

Classified hazard categories

Flammable (gases, aerosols, liquids, or solids)
Acute toxicity (any route of exposure)
Skin corrosion or irritation
Serious eye damage or eye irritation
Germ cell mutagenicity
Carcinogenicity
Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
1,2,4-Trimethylbenzene	95-63-6	0 - 5

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

ASPHALT (CAS 8052-42-4)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.**US state regulations****US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

1,2,4-Trimethylbenzene (CAS 95-63-6)

ASPHALT (CAS 8052-42-4)

ATTAPULGITE CLAY, HYDROUS MAGNESIUM ALUMINUM SILICATE (CAS 12174-11-7)

MINERAL SPIRITS (CAS 8052-41-3/64742-48-9)

QUARTZ (CAS 14808-60-7)

SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM. (CAS 64742-95-6)

California Proposition 65

WARNING: WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

ATTAPULGITE CLAY, HYDROUS MAGNESIUM

Listed: December 28, 1999

ALUMINUM SILICATE (CAS 12174-11-7)

QUARTZ (CAS 14808-60-7)

Listed: October 1, 1988

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	11-24-2020
Revision date	08-05-2025
Version #	05
NFPA ratings	Health: 2 Flammability: 2 Instability: 0

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.