

1. Identification

Product identifier	NOVOCOATTM SC3100 HT LINING PART A (ALL COLORS)
Other means of identification	None.
Recommended use	Lining
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
Company Name	Armor Limited, Inc.
Address	2410 US-15 South, Sumter, SC 29150
After hours telephone number	1-877-982-7667
Normal work hours telephone number	1-877-982-7667
Website	www.armor-inc.com
E-mail	customerservice@armor-inc.com
Emergency 24-hour telephone number	CHEMTREC North America: +1-800-424-9300, International: +1-703-527-3887
Information on operation hours	8:00 a.m. to 5:00 p.m.

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2B
	Sensitization, skin	Category 1B
	Carcinogenicity	Category 2
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	

Label elements



Signal word	Warning
Hazard statement	Suspected of causing cancer. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction.

Precautionary statement

Prevention	Obtain special instructions before use. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not handle until all safety precautions have been read and understood. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Avoid release to the environment.
Response	IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Take off contaminated clothing and wash it before reuse. Specific treatment see Section 4 of this SDS. If eye irritation persists: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention.
Storage	Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
PHENOL-FORMALDEHYDE POLYMER GLYCIDYL ETHER		28064-14-4	20 - 50
BISPHENOL A-(EPICHLOROHYDRIN) EPOXY RESIN		25068-38-6	15 - 30
QUARTZ		14808-60-7	5 - 15
1,3-DIGLYCIDYLOXYBENZENE		101-90-6	1 - 10
Other components below reportable levels			20 - 40

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention, if needed.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Call a POISON CENTER or doctor/physician if you feel unwell. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. For minor skin contact, avoid spreading material on unaffected skin. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Continue rinsing. Get medical attention immediately.
Ingestion	Call a physician or poison control center immediately. Rinse mouth thoroughly. Never give anything by mouth to a victim who is unconscious or is having convulsions. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.
Most important symptoms/effects, acute and delayed	Skin irritation. May cause an allergic skin reaction. Dermatitis. Rash. Irritation of eyes. Irritant effects. May cause redness and pain. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Take off contaminated clothing and shoes immediately. In case of shortness of breath, give oxygen. IF exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Alcohol foam. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Water. Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Fire may produce irritating, corrosive and/or toxic gases.
Special protective equipment and precautions for firefighters	Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. In the event of fire, cool tanks with water spray. Use water spray to cool unopened containers. Cool containers exposed to flames with water until well after the fire is out. Water runoff can cause environmental damage.
Specific methods	In the event of fire, cool tanks with water spray. Use water spray to cool unopened containers.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Immediately evacuate personnel to safe areas. Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Avoid skin contact and inhalation of vapors during disposal of spills. Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Extinguish all flames in the vicinity.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Do not breathe mist or vapor. Do not get this material in contact with eyes. Do not taste or swallow. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Do not use in areas without adequate ventilation. Wear appropriate personal protective equipment. Wash thoroughly after handling. Avoid release to the environment. Do not empty into drains.

Conditions for safe storage, including any incompatibilities

CAUTION Store locked up. Keep away from heat, sparks and open flame. Store in a closed container away from incompatible materials. Store in tightly closed container. Store in a well-ventilated place. Keep away from food, drink and animal feedingstuffs. Store away from incompatible materials (see Section 10 of the SDS). Store in accordance with local/regional/national/international regulation.

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
QUARTZ (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
QUARTZ (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
QUARTZ (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection	Safety glasses. If risk of splashing, wear safety goggles or face shield.
Skin protection	
Hand protection	Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves.
Other	Wear appropriate clothing to prevent any possibility of skin contact.
Respiratory protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.
---------------------------------------	---

9. Physical and chemical properties**Appearance**

Physical state	Liquid.
Form	Liquid.
Color	Not available.

Odor	Not available.
-------------	----------------

Odor threshold	Not available.
-----------------------	----------------

pH	7 estimated
-----------	-------------

Melting point/freezing point	Not available.
-------------------------------------	----------------

Initial boiling point and boiling range	> 392 °F (> 200 °C)
--	---------------------

Flash point	> 302.0 °F (> 150.0 °C)
--------------------	-------------------------

Evaporation rate	Not available.
-------------------------	----------------

Flammability (solid, gas)	Not applicable.
----------------------------------	-----------------

Upper/lower flammability or explosive limits

Explosive limit - lower (%)	Not available.
------------------------------------	----------------

Explosive limit - upper (%)	Not available.
------------------------------------	----------------

Vapor pressure	82 Pa at 20°C
-----------------------	---------------

Vapor density	Not available.
----------------------	----------------

Relative density	Not available.
-------------------------	----------------

Solubility(ies)

Solubility (water)	Not available.
---------------------------	----------------

Partition coefficient (n-octanol/water)	> 3
--	-----

Auto-ignition temperature	572 °F (300 °C)
----------------------------------	-----------------

Decomposition temperature	Not available.
----------------------------------	----------------

Viscosity	Not available.
------------------	----------------

Other information

Density	12.39 lb/gal estimated
----------------	------------------------

Specific gravity	1.48 estimated
-------------------------	----------------

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
-------------------	---

Chemical stability	Stable.
---------------------------	---------

Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
---	---

Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
----------------------------	---

Incompatible materials	Peroxides. Chlorine. Strong acids, alkalies and oxidizing agents.
-------------------------------	---

Hazardous decomposition products If product is burned hazardous gases such as oxides of carbon and nitrogen and various hydrocarbons may be produced.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes eye irritation.

Ingestion Suspected of causing cancer by ingestion. However, ingestion is not likely to be a primary route of occupational exposure.

Symptoms related to the physical, chemical and toxicological characteristics Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Not known.

Product	Species	Test Results
NOVOCOAT™ SC3100 HT LINING PART A (ALL COLORS)		
Acute		
Dermal		
LD50	Rat	2.174e+006 mg/kg
Inhalation		
LC50	Rat	28740 mg/l, 4 Hours
Oral		
LD50	Rat	51 g/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Irritating to skin. Causes severe eye irritation.

Serious eye damage/eye irritation Causes eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Possible cancer hazard based on tests with laboratory animals. Suspected of causing cancer. This product contains crystalline silica. Silica is a known carcinogen; however in this encapsulated form the normal routes of exposure are unavailable.

IARC Monographs. Overall Evaluation of Carcinogenicity

1,3-DIGLYCIDYLOXYBENZENE (CAS 101-90-6) 2B Possibly carcinogenic to humans.
QUARTZ (CAS 14808-60-7) 1 Carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

QUARTZ (CAS 14808-60-7) Cancer

US. National Toxicology Program (NTP) Report on Carcinogens

1,3-DIGLYCIDYLOXYBENZENE (CAS 101-90-6) Reasonably Anticipated to be a Human Carcinogen.
QUARTZ (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product contains a substance which is toxic to aquatic organisms.

Product	Species		Test Results
NOVOCOAT™ SC3100 HT LINING PART A (ALL COLORS)			
Aquatic			
Crustacea	EC50	Daphnia	12.6536, 48 hours
Fish	LC50	Fish	7.2985, 96 hours
Acute			
Crustacea	EC50	Daphnia	319.9663, 48 hours estimated
Fish	LC50	Fish	12354.8311, 96 hours estimated

Components	Species		Test Results
PHENOL-FORMALDEHYDE POLYMER GLYCIDYL ETHER (CAS 28064-14-4)			
Aquatic			
Acute			
Fish	LC50	Fish	> 1 - < 10 mg/l

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)	
NOVOCOAT™ SC3100 HT LINING PART A (ALL COLORS)	> 3

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation potential.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Dispose of contents/container in accordance with local/regional/national/international regulations. When this product as supplied is to be discarded as waste, it does not meet the definition of a RCRA waste under 40 CFR 261.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Offer rinsed packaging material to local recycling facilities.

14. Transport information

DOT
Not regulated as dangerous goods.

IATA	
UN number	UN3082
UN proper shipping name	Environmentally hazardous substance, liquid, n.o.s. (BISPHENOL A-(EPICHLOROHYDRIN) EPOXY RESIN)
Transport hazard class(es)	
Class	9
Subsidiary risk	-
Packing group	III
Environmental hazards	No.
ERG Code	9L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.

IMDG	
UN number	UN3082

UN proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A-(EPICHLOROHYDRIN) EPOXY RESIN), MARINE POLLUTANT

Transport hazard class(es)

Class 9

Subsidiary risk -

Packing group III

Environmental hazards

Marine pollutant YES

EmS F-A, S-F


Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Not established.


Annex II of MARPOL 73/78

and the IBC Code

IATA; IMDG



Marine pollutant



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

QUARTZ (CAS 14808-60-7)

Cancer
lung effects
immune system effects
kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

Classified hazard categories

Skin corrosion or irritation
Serious eye damage or eye irritation
Respiratory or skin sensitization
Carcinogenicity
Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
1,3-DIGLYCIDYLOXYBENZENE	101-90-6	1 - 10

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Contains component(s) regulated under the Safe Drinking Water Act.

US state regulations**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

1,3-DIGLYCIDYLOXYBENZENE (CAS 101-90-6)

QUARTZ (CAS 14808-60-7)

California Proposition 65

WARNING: WARNING: This product contains a chemical known to the State of California to cause cancer. This product can expose you to chemicals including QUARTZ, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

1,3-DIGLYCIDYLOXYBENZENE (CAS 101-90-6)	Listed: July 1, 1989
QUARTZ (CAS 14808-60-7)	Listed: October 1, 1988

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 06-15-2020

Revision date 02-20-2023

Version # 04

NFPA ratings
Health: 2
Flammability: 0
Instability: 0

References
EPA: AQUIRE database
US. IARC Monographs on Occupational Exposures to Chemical Agents

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Armor cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

Revision information

Product and Company Identification: Alternate Trade Names
Toxicological Information: Toxicological Data
Regulatory Information: United States
GHS: Classification