# SAFETY DATA SHEET



# 1. Identification

**Product identifier ERTECH 3135** 

Other means of identification None

Recommended use Not available. **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

**Company Name** ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.

**Address** 2829 Lakeland Drive Jackson, MS 39232

**USA** 

After hours telephone

number

1-800-222-7122

**Normal work hours** 

telephone number

1-877-982-7667

Website www.ergonarmor.com E-mail sds@ergon.com

**Emergency 24-hour** telephone number

CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

Information on operation

8:00 a.m. to 5:00 p.m.

hours

# 2. Hazard(s) identification

**Physical hazards** Not classified. **Health hazards** Sensitization, skin

**Environmental hazards** Not classified. **OSHA** defined hazards Not classified.

**Label elements** 



Signal word

**Hazard statement** May cause an allergic skin reaction.

**Precautionary statement** 

**Prevention** Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing must not be

allowed out of the workplace. Wear protective gloves. Observe good industrial hygiene practices.

Category 1

Specific treatment see Section 4 of this SDS. IF ON SKIN: Wash with plenty of soap and water. If Response

skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Wash hands after handling.

**Storage** Store away from incompatible materials.

**Disposal** Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

None known.

**Supplemental information** Not applicable.

### 3. Composition/information on ingredients

**Mixtures** 

Material name: ERTECH 3135 SDS US

6160 Version #: 02 Revision date: 04-20-2018 Issue date: 02-24-2017

% **Chemical name** Common name and synonyms **CAS** number 8052-42-4 35 - 45 **ASPHALT** Other components below reportable levels 63.77

### 4. First-aid measures

**Inhalation** If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

Call a physician if symptoms develop or persist.

Skin contact If clothing sticks to the skin, do not remove. Lotion or hand cream may aid in the removal of

asphalt. Wash contact areas with soap and water. If needed, seek medical attention.

Immediately flush eyes with plenty of water for at least 15 minutes, Remove contact lenses, if **Eve contact** 

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. DO NOT induce vomiting. Get medical attention immediately. If ingestion of a large

amount does occur, call a poison control center immediately.

Direct contact with eyes may cause temporary irritation.

Most important

symptoms/effects, acute and

delaved

**Ingestion** 

**Indication of immediate** medical attention and special

Treat symptomatically.

treatment needed **General information** 

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

# 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from the chemical

**Special protective equipment** and precautions for

firefighters Fire fighting

equipment/instructions

**Specific methods** 

General fire hazards

Foam. Dry chemical powder. Carbon dioxide (CO2).

Water. Do not use water jet as an extinguisher, as this will spread the fire.

During fire, gases hazardous to health may be formed.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.

ALWAYS stay away from tanks engulfed in flame. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Move containers from fire area if you can do so without

risk. In the event of fire, cool tanks with water spray.

In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with

water spray.

No unusual fire or explosion hazards noted.

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Ventilate area and avoid breathing vapors or mist. For large spills, dike far ahead of liquid spill for later disposal. Do not release into sewers or waterways.

**Environmental precautions** 

Avoid discharge into drains, water courses or onto the ground.

Material name: ERTECH 3135 SDS US

## 7. Handling and storage

Precautions for safe handling Avoid prolonged exposure. Use only in well-ventilated areas. Hydrogen sulfide, a very highly toxic

gas, may be present with this material. Keep face clear of tank and/or tank car openings. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before

leaving the work site.

Conditions for safe storage,

including any incompatibilities Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in

original tightly closed container. Store in a well-ventilated place.

## 8. Exposure controls/personal protection

Occupational exposure limits

This mixture has no ingredients that have PEL, TLV, or other recommended exposure limit

**Biological limit values** 

No biological exposure limits noted for the ingredient(s).

Appropriate engineering

controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined

occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

**Eye/face protection** Chemical goggles and face shield are recommended. Wear safety glasses with side shields (or

goggles).

Skin protection

**Hand protection** Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style

gloves.

Other Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged

vapor contact. Plastic or rubber gloves, apron and boots.

**Respiratory protection** When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to

remove contaminants.

# 9. Physical and chemical properties

**Appearance** Heavy-consistency emulsion.

**Physical state** Liquid.

**Form** Liquid. Viscous

Color **Black** 

Odor Mild Petroleum Odor

**Odor threshold** Not available. рH 11 - 12 Melting point/freezing point 32 °F (0 °C) Initial boiling point and 212 °F (100 °C)

boiling range

> 212.0 °F (> 100.0 °C) Cleveland Open Cup Flash point

**Evaporation rate** Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits Flammability limit - lower Not available.

(%)

Flammability limit -

upper (%)

Not available.

**Explosive limit - lower** 

(%)

Not available.

**Explosive limit - upper** 

(%)

Not available.

Vapor pressure Not available. Vapor density Not available. Relative density 0.95 - 1.05 g/cm3

Material name: ERTECH 3135 6160 Version #: 02 Revision date: 04-20-2018 Issue date: 02-24-2017 Relative density temperature 39.2 °F (4 °C)

Solubility(ies)

Solubility (water) Slightly

Partition coefficient Not available.

(n-octanol/water)

**Auto-ignition temperature** > 700 °F (> 371.11 °C)

**Decomposition temperature** Not available.

**Viscosity** 500 cP Approx. (77 °F (25 °C))

Other information

**VOC** 0.2 lb/gal maximum

## 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport

**Chemical stability** Stable under normal temperature conditions. **Possibility of hazardous** Hazardous polymerization does not occur.

reactions

**Conditions to avoid** Avoid temperatures exceeding the flash point. Contact with incompatible materials. Do not overheat

product.

**Incompatible materials** Strong oxidizing agents.

**Hazardous decomposition**Upon decomposition, this product may yield sulfur dioxide, carbon monoxide, carbon dioxide and/or

**products** low molecular weight hydrocarbons. Hydrogen sulfide.

## 11. Toxicological information

### Information on likely routes of exposure

InhalationProlonged inhalation may be harmful.Skin contactMay cause an allergic skin reaction.

**Eye contact** May be irritating to eyes.

**Ingestion** Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

### Information on toxicological effects

**Acute toxicity** Not available.

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

May be irritating to eyes.

#### Respiratory or skin sensitization

**Respiratory sensitization** Not available.

**Skin sensitization** May cause skin disorders if contact is repeated or prolonged.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

**Carcinogenicity** This product contains crystalline silica. Silica is a known carcinogen; however in this encapsulated

form the normal routes of exposure are unavailable.

#### IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

## **US. National Toxicology Program (NTP) Report on Carcinogens**

Not listed.

**Reproductive toxicity** Not classified. **Specific target organ toxicity** Not classified.

- single exposure

Not classified.

Specific target organ toxicity

- repeated exposure

Material name: ERTECH 3135 SDS US

**Aspiration hazard** Not available.

**Chronic effects** Hazardous by OSHA criteria. Prolonged inhalation may be harmful. Prolonged exposure may cause

chronic effects. Not expected to be hazardous by WHMIS criteria.

**Further information** This product has no known adverse effect on human health.

## 12. Ecological information

**Ecotoxicity** Not expected to be harmful to aquatic organisms.

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential**No data available. **Mobility in soil**No data available.

**Other adverse effects**No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose in

accordance with all applicable regulations. No components are identified as hazardous wastes.

Disposal recommendations are based on uncontaminated material.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code**The waste code should be assigned in discussion between the user, the producer and the waste

disposal company. Not applicable.

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions). Avoid discharge into water courses or onto the ground.

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

## 14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

Transport in bulk according to Not available.

Annex II of MARPOL 73/78

and the IBC Code

### 15. Regulatory information

**US federal regulations** All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

**SARA 302 Extremely hazardous substance** 

Not listed.

**Classified hazard** 

Flammable (gases, aerosols, liquids, or solids)

**categories** Respiratory or skin sensitization

SARA 313 (TRI reporting)

Not regulated.

Material name: ERTECH 3135 SDS US

### Other federal regulations

### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

**US state regulations** WARNING: This product contains a chemical known to the State of California to cause cancer.

#### **California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer.

#### California Proposition 65 - CRT: Listed date/Carcinogenic substance

ASPHALT (CAS 8052-42-4) Listed: January 1, 1990

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

## 16. Other information, including date of preparation or last revision

 Issue date
 02-24-2017

 Revision date
 04-20-2018

Version # 02

**Further information** HMIS® is a registered trade and service mark of the NPCA.

NFPA ratings Health: 1

Flammability: 1 Instability: 0

**References** ACGIH

EPA: AQUIRE database

NLM: Hazardous Substances Data Base

US. IARC Monographs on Occupational Exposures to Chemical Agents

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written

based on the best knowledge and experience currently available.

**Revision information** This document has undergone significant changes and should be reviewed in its entirety

Material name: ERTECH 3135 SDS US