SAFETY DATA SHEET



1. Identification

Product identifier Blackhawk Precast Release 50

Other means of identification None.

Recommended use Not available. **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.

Address 2829 Lakeland Drive Jackson, MS 39232

USA

After hours telephone

number

1-800-222-7122

Normal work hours

telephone number

1-877-982-7667

Website www.ergonarmor.com E-mail sds@ergon.com

Emergency 24-hour telephone number

CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

Information on operation

8:00 a.m. to 5:00 p.m.

hours

2. Hazard(s) identification

Physical hazards Flammable liquids Category 4 **Health hazards** Germ cell mutagenicity Category 1B Carcinogenicity Category 1B

Specific target organ toxicity, repeated

exposure

Category 1 (central nervous system)

Aspiration hazard

Not classified.

Environmental hazards OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May be fatal if swallowed and enters airways. Combustible liquid. May cause genetic defects.

Precautionary statement

Observe good industrial hygiene practices. Wash thoroughly after handling. Do not handle until all **Prevention**

safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Obtain special instructions before use. Do not eat, drink or smoke when using this product. Wear protective gloves/eye protection/face protection. Do not breathe mist or

Category 1

Response IF SWALLOWED: Immediately call a POISON CENTER/doctor. Wash hands after handling. IF

SWALLOWED: Rinse mouth. Do NOT induce vomiting. In case of fire: Use appropriate media for

extinction. IF exposed or concerned: Get medical advice/attention.

Storage Store in a well-ventilated place. Keep cool. Store locked up.

Dispose of waste and residues in accordance with local authority requirements. Dispose of **Disposal**

contents/container in accordance with local/regional/national/international regulations.

Material name: Blackhawk Precast Release 50

SDS US 1/7 6041 Version #: 02 Revision date: 10-07-2016 Issue date: 05-13-2016

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

Not applicable.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%	
STODDARD SOLVENT		8052-41-3	> 75	
Other components below reportable levels			25	

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Rinse with water. Get medical attention if irritation develops and persists. Eye contact

Ingestion Rinse mouth. Get medical attention if symptoms occur. Most important Direct contact with eyes may cause temporary irritation.

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed

Treat symptomatically.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment

and precautions for

firefighters

Move containers from fire area if you can do so without risk.

Fire fighting

equipment/instructions

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Methods and materials for containment and cleaning up Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. For personal protection, see section 8 of the SDS.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to

remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Avoid prolonged exposure. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Refrigeration recommended. Store away from

incompatible materials (see Section 10 of the SDS).

Material name: Blackhawk Precast Release 50

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components **Type Value** STODDARD SOLVENT (CAS PEL 2900 mg/m3 8052-41-3)

US. ACGIH Threshold Limit Values

Value Components **Type**

STODDARD SOLVENT (CAS **TWA** 100 ppm 8052-41-3)

TWA

US. NIOSH: Pocket Guide to Chemical Hazards

Components **Type** Value STODDARD SOLVENT (CAS Ceiling 1800 mg/m3 8052-41-3)

Biological limit values No biological exposure limits noted for the ingredient(s).

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should Appropriate engineering be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other controls engineering controls to maintain airborne levels below recommended exposure limits. If exposure

limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves.

Other Wear appropriate chemical resistant clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene Always observe good personal hygiene measures, such as washing after handling the material and considerations

before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to

500 ppm

350 mg/m3

remove contaminants.

9. Physical and chemical properties

Appearance Clear, colorless liquid.

Physical state Liquid. **Form** Liquid. Color Colorless.

Odor Hydrocarbon-like. **Odor threshold** Not available. pН Not available. Melting point/freezing point Not available.

Initial boiling point and

boiling range

212 °F (100 °C) estimated

Flash point 153.0 °F (67.2 °C)

Evaporation rate Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower 0.9 % estimated

(%)

Flammability limit -

upper (%)

6 % estimated

Explosive limit - lower Not available.

(%)

Material name: Blackhawk Precast Release 50 6041 Version #: 02 Revision date: 10-07-2016 Issue date: 05-13-2016 SDS US

Explosive limit - upper

(%)

Not available.

Vapor pressureNot available.Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 450 °F (232.22 °C) estimated

Decomposition temperature Not available. **Viscosity** Not available.

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions. **Possibility of hazardous** Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contactNo adverse effects due to skin contact are expected. **Eye contact**Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Not available.

Skin corrosion/irritationProlonged skin contact may cause temporary irritation. **Serious eye damage/eye**Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

STODDARD SOLVENT (CAS 8052-41-3)

3 Not classifiable as to carcinogenicity to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity

- single exposure

Not classified.

Specific target organ toxicity Not classified.

- repeated exposure

Material name: Blackhawk Precast Release 50 SDS US

Aspiration hazard Not available.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

EcotoxicityThe product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

STODDARD SOLVENT 3.16 - 7.15

Mobility in soil No data available.

Other adverse effectsNo other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste codeThe waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product

residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied

14. Transport information

DOT

UN number UN1268

UN proper shipping name Petroleum distillates, n.o.s. or Petroleum products, n.o.s. (STODDARD SOLVENT)

Transport hazard class(es)
Class

Class 3
Subsidiary risk Label(s) 3
Packing group III

Special precautions for

user

Read safety instructions, SDS and emergency procedures before handling.

Special provisions 144, B1, IB3, T4, TP1, TP29

Packaging exceptions150Packaging non bulk203Packaging bulk242

IATA

UN number UN1268

UN proper shipping name Petroleum products, n.o.s.

Transport hazard class(es)

Class 3
Subsidiary risk Packing group III
Environmental hazards No.
ERG Code 3L

Special precautions for

usor

Read safety instructions, SDS and emergency procedures before handling.

u3Ci

Other information

Passenger and cargo Allowed with restrictions.

aircraft

Allowed with restrictions.

IMDG

UN number UN1268

UN proper shipping name PETROLEUM DISTILLATES, N.O.S. or PETROLEUM PRODUCTS, N.O.S.

Material name: Blackhawk Precast Release 50

Cargo aircraft only

Transport hazard class(es)

Class 3 **Subsidiary risk** Packing group III

Environmental hazards

Marine pollutant No. F-E, S-E **EmS**

Special precautions for Read safety instructions, SDS and emergency procedures before handling.

user

Transport in bulk according to Not available.

Annex II of MARPOL 73/78

and the IBC Code

DOT



IATA; IMDG



15. Regulatory information

US federal regulations All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - Yes **Hazard categories**

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 No

Hazardous chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Material name: Blackhawk Precast Release 50

SDS US 6041 Version #: 02 Revision date: 10-07-2016 Issue date: 05-13-2016

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

STODDARD SOLVENT (CAS 8052-41-3)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

05-13-2016 **Issue date Revision date** 10-07-2016

Version # 02

NFPA ratings Health: 2

> Flammability: 3 Instability: 0

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

> information and belief at the date of its publication. The information given is designed only as a quidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision information Product and Company Identification: Alternate Trade Names

> Hazard(s) identification: Hazard statement Hazard(s) identification: GHS Symbols

GHS: Classification

SDS US