SAFETY DATA SHEET



1. Identification

PENNCOAT 601 PRIMER **Product identifier**

Other means of identification Not available. Recommended use Not available. **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company Name ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.

Address 2829 Lakeland Drive Jackson, MS 39232

USA

After hours telephone

1-800-222-7122

number

Normal work hours telephone number

1-877-982-7667

Website www.ergonarmor.com E-mail sds@ergon.com

Emergency 24-hour telephone number

CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

Information on operation

hours

8:00 a.m. to 5:00 p.m.

2. Hazard(s) identification

Physical hazards Flammable liquids Category 2 **Health hazards** Acute toxicity, oral Category 4 Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2A Reproductive toxicity (the unborn child) Category 2 Specific target organ toxicity, single exposure Category 3 narcotic effects

Specific target organ toxicity, repeated

Category 2

Category 2

exposure

Environmental hazards Hazardous to the aquatic environment, acute Category 2

Hazardous to the aquatic environment, long-term hazard

OSHA defined hazards Not classified.

Label elements





Signal word Not available.

Hazard statement Causes skin irritation. Toxic to aquatic life. Toxic to aquatic life with long lasting effects. May cause

damage to organs through prolonged or repeated exposure. May cause drowsiness or dizziness.

Suspected of damaging the unborn child. Highly flammable liquid and vapor.

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Disposal Not available. Hazard(s) not otherwise None known.

classified (HNOC)

Supplemental information Not applicable.

Material name: PENNCOAT 601 PRIMER 5795 Version #: 02 Revision date: 12-30-2015 Issue date: 01-27-2015 1/9

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
TOLUENE		108-88-3	76
Other components below reportab	le levels		24

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur. **Most important** Direct contact with eyes may cause temporary irritation.

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed

Treat symptomatically.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Unsuitable extinguishing media

During fire, gases hazardous to health may be formed.

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire-fighting

Move containers from fire area if you can do so without risk.

equipment/instructions **Specific methods**

Use standard firefighting procedures and consider the hazards of other involved materials.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Conditions for safe storage, including any incompatibilities

Avoid prolonged exposure. Observe good industrial hygiene practices.

Store in original tightly closed container. Refrigeration recommended. Store away from

incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Туре	Value	
TOLUENE (CAS 108-88-3)	Ceiling	300 ppm	
	TWA	200 ppm	
US. ACGIH Threshold Limit Valu	ies		
Components	Туре	Value	
TOLUENE (CAS 108-88-3)	TWA	20 ppm	
US. NIOSH: Pocket Guide to Ch	emical Hazards		
Components	Туре	Value	
TOLUENE (CAS 108-88-3)	STEL	560 mg/m3	
		150 ppm	
	TWA	375 mg/m3	
		100 ppm	

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
TOLUENE (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

TOLUENE (CAS 108-88-3) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

TOLUENE (CAS 108-88-3) Skin designation applies.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Hand protection Wear protective gloves.

Skin protection

Other Wear appropriate chemical resistant clothing.

In case of insufficient ventilation, wear suitable respiratory equipment. Respiratory protection

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to

remove contaminants.

9. Physical and chemical properties

Black liquid **Appearance Physical state** Liquid. Liquid. **Form** Color Black Odor Solvent. **Odor threshold** Not available. Not available. Melting point/freezing point Not available.

Initial boiling point and

boiling range

228.2 - 231.8 °F (109 - 111 °C)

40.0 °F (4.4 °C) Tag Closed Cup Flash point

Evaporation rate Not available.

Material name: PENNCOAT 601 PRIMER

SDS US 5795 Version #: 02 Revision date: 12-30-2015 Issue date: 01-27-2015

Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit -

upper (%)

Not available.

Explosive limit - lower

(%)

Not available.

Explosive limit - upper

(%)

Not available.

Vapor pressure 22 mm Hg @ 20 C

Vapor density

Not available. **Relative density**

Solubility(ies)

Solubility (water) Insoluble **Partition coefficient** Not available.

(n-octanol/water)

Not available. **Auto-ignition temperature Decomposition temperature** Not available. **Viscosity** Not available.

Other information

Specific gravity 0.91 57 % VOC (Weight %)

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions. **Possibility of hazardous** Hazardous polymerization does not occur.

reactions

Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

Conditions to avoid

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion Expected to be a low ingestion hazard. **Inhalation** Prolonged inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected. **Eve contact** Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Product Test Results Species

PENNCOAT 601 PRIMER (CAS Mixture)

Acute Dermal

LD50 Rabbit 15952.6318 mg/kg estimated

18.5526 ml/kg estimated

Inhalation

LC50 Mouse 7000 ppm, 8 Hours estimated

526.3158 ppm, 24 Hours estimated

Rat 35131.5781 ppm, 1 Hours estimated

16052.6318 ppm, 2 Hours estimated

10526.3154 ppm, 4 Hours estimated

Product	Species	Test Results
Oral		
LD50	Rat	3.4211 g/kg estimated
Other		
LD50	Mouse	77.6316 mg/kg estimated
	Rat	1752.6316 mg/kg estimated
Components	Species	Test Results
TOLUENE (CAS 108-88-3)		
Acute		
Dermal		
LD50	Rabbit	12124 mg/kg
		14.1 ml/kg
Inhalation		
LC50	Mouse	5320 ppm, 8 Hours
		400 ppm, 24 Hours
	Rat	26700 ppm, 1 Hours
		12200 ppm, 2 Hours
		8000 ppm, 4 Hours
Oral		
LD50	Rat	2.6 g/kg
Other		- -
LD50	Mouse	59 mg/kg
	Rat	1332 mg/kg
		<u>.</u>

^{*} Estimates for product may be based on additional component data not shown.

Skin corrosion/irritationProlonged skin contact may cause temporary irritation. **Serious eye damage/eye**Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

TOLUENE (CAS 108-88-3) 3 Not classifiable as to carcinogenicity to humans.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity

- single exposure

Not classified.

Specific target organ toxicity

- repeated exposure

Not classified.

Aspiration hazard Not available.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

EcotoxicityThe product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product		Species	Test Results
PENNCOAT 601 PRIM	ER (CAS Mixture)		
Crustacea	EC50	Daphnia	13.4507 mg/l, 48 hours estimated
Fish	LC50	Fish	116.1168 mg/l, 96 hours estimated

Components Species Test Results

TOLUENE (CAS 108-88-3)

Aquatic

EC50 Water flea (Daphnia magna) 5.46 - 9.83 mg/l, 48 hours Crustacea

LC50 Fish Coho salmon, silver salmon 8.11 mg/l, 96 hours

(Oncorhynchus kisutch)

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

TOLUENE 2.73

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

US RCRA Hazardous Waste U List: Reference

TOLUENE (CAS 108-88-3) U220

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product

residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions).

Empty containers should be taken to an approved waste handling site for recycling or disposal. Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

UN number UN1866 **UN proper shipping name Resin Solution**

Transport hazard class(es)

Class 3 **Subsidiary risk** 3 Label(s) **Packing group** Π

Special precautions for

user

Read safety instructions, SDS and emergency procedures before handling.

IB2, T7, TP1, TP8, TP28 Special provisions

Packaging exceptions 150 202 Packaging non bulk **Packaging bulk** 242

IATA

UN1866 **UN** number **UN proper shipping name Resin Solution**

Transport hazard class(es)

3 **Class Subsidiary risk Packing group PGII Environmental hazards** No.

Special precautions for

user

Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

Forbidden.

aircraft Cargo aircraft only

Forbidden.

IMDG

UN number UN1866 **UN proper shipping name Resin Solution**

^{*} Estimates for product may be based on additional component data not shown.

Transport hazard class(es)

Class 3
Subsidiary risk Packing group II
Environmental hazards

Marine pollutant Yes

EmS F-E, S-E*

Special precautions for Read safety instructions, SDS and emergency procedures before handling.

user

Transport in bulk according to Not available. **Annex II of MARPOL 73/78**

Annex II of MARPOL 73/78 and the IBC Code

DOT



IATA; IMDG



Marine pollutant



15. Regulatory information

US federal regulations All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

TOLUENE (CAS 108-88-3) Listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
TOLUENE	108-88-3	76	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

TOLUENE (CAS 108-88-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2)

TOLUENE (CAS 108-88-3)

DEA Essential Chemical Code Number

TOLUENE (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

TOLUENE (CAS 108-88-3) 35 %WV

DEA Exempt Chemical Mixtures Code Number

TOLUENE (CAS 108-88-3) 594

US state regulations

US. Massachusetts RTK - Substance List

TOLUENE (CAS 108-88-3)

US. New Jersey Worker and Community Right-to-Know Act

TOLUENE (CAS 108-88-3) 500 LBS

US. Pennsylvania RTK - Hazardous Substances

TOLUENE (CAS 108-88-3)

US. Rhode Island RTK

TOLUENE (CAS 108-88-3)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Developmental toxin

TOLUENE (CAS 108-88-3) Listed: January 1, 1991

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

TOLUENE (CAS 108-88-3) Listed: August 7, 2009

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

Issue date 01-27-2015 **Revision date** 12-30-2015

5795 Version #: 02 Revision date: 12-30-2015 Issue date: 01-27-2015

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

Material name: PENNCOAT 601 PRIMER

Version # 02

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision Information Product and Company Identification: Product and Company Identification

Physical & Chemical Properties: Multiple Properties

GHS: Classification

Material name: PENNCOAT 601 PRIMER
5795 Version #: 02 Revision date: 12-30-2015 Issue date: 01-27-2015