



SELECTION & SPECIFICATION DATA

Generic Type	Fast Drying Asphalt Cutback
Description	BH 5157 is a coating that can be used for many purposes. This product has good corrosion and weather proof features. It also has excellent coverage and adhesion to marginly prepared surfaces. It is widely used to protect steel beams, steel pipes, and other metal parts. BH 5157 also functions well as a primer. BH 5157 has a very high solids content giving excellent coverage. It is supplied in the correct consistency for application and needs no thinning if kept air tight between uses.
Recommended Uses	Corrosion protection of: <ul style="list-style-type: none"> • Steel beams • Steel pipes • Engine chassis' Acts as an excellent primer for metal substrates.
Color	Black
Primer	Self-priming
Topcoats	Consult ErgonArmor
Finish	Gloss
Dry Film Thickness	3 – 5 mils
Solids Content	By Weight 55% +/- 5%
Theoretical Coverage Rate	220 square feet per gallon at 4 DFT
VOC Value(s)	<450g/L, 3.75 lbs/gal

SUBSTRATES & SURFACE PREPARATION

General	All surfaces must be clean and free from debris and loose scale material or anything that may interfere with adhesion or act as a bond breaker with the desired substrate.
----------------	--

MIXING & THINNING

Mixing	No mixing required. Ready to use as is.
Thinning	DO NOT THIN

APPLICATION EQUIPMENT GUIDELINES

Listed below are general equipment guidelines for the application of this product. Job site conditions may require modifications to these guidelines to achieve the desired results.

Airless Spray Single Leg or Pot	Pump Size 15:1 or greater Hose Length/Diameter: 20 ft x ½"
Brush	Apply with a wide fiber brush in order to create a smooth uniform film.
Roller	Use a low nap phenolic core roller.

CLEANUP & SAFETY

Cleanup	Use mineral spirits for suitable cleanup. In case of spillage, absorb and dispose of in accordance with local applicable regulations. Refer to SDS for more information.
Safety	Read and follow all caution statements on this product data sheet and on the SDS for this product. Wear protective clothing, gloves and eye protection.
Ventilation	Thorough air circulation must be used during and after application until the product is cured. User should test and monitor exposure levels to ensure all personnel are within safe limits. Consult product SDS for further information.

PACKAGING, HANDLING & STORAGE

Shelf Life	12 months at 75°F (24°C) when kept at recommended storage conditions and in original unopened containers.
Storage Temperature & Humidity	40° – 110°F (4°- 43°C) 0 – 100% Relative Humidity
Storage	Store Indoors. This product is not affected by excursions below these published storage temperatures, down to 10°F, for a duration of no more than 14 days. Always inspect the product prior to use to make sure it is smooth and homogeneous and properly mixed.
Sizes and Specifications	5 gallon (4.7 net fill) 55 gallon (53 net fill) 350-gallon carbon steel, returnable totes

Rev 02/18

SAFETY
Mixes and applications of this product present a number of hazards. Read and follow the hazard information, precautions and first aid directions on the individual product labels and material safety data sheets before using. While all statements, technical information, and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user. Please contact ErgonArmor for further information at 877.982.7667 or FAX 601-933-3381. For all Terms and Conditions of Sale see ergonarmor.com.

ORDERING INFORMATION
For additional information, prices, or to place an order, please contact your ErgonArmor sales representative. If you do not know the name of your sales representative, call 877-98ARMOR.